

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2007	7NHXL06.7DTC	3.4, 3.9, 4.5, 6.7	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger and Smoke Puff Limiter (Some Models)			Loader, Tractor and Other Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
56 ≤ kW < 75	Tier 2	STD	N/A	N/A	7.5	5.0	0.40	20	15	50
		CERT	--	--	6.6	1.1	0.27	14	11	23

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 6 day of November 2006.


 Annette Hebert, Chief
 Mobile Source Operations Division

Engine Model Summary Form

ATTACHMENT Pg 1 of 1

U-2-008-0068

Manufacturer: CNH UK LTD
 Engine category: Nonroad CI
 EPA Engine Family: 7NHXL06.7DTC
 Mfr Family Name: F4BE0454
 Process Code: New Submission

1. Engine Code	2. Engine Model	3. BHP@RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke@peak torque	8. Fuel Rate: (lbs/hr)@peak torque	9. Emission Control Device Per SAE J1930
N/A	F4BE0454F*D	99 @ 2100	82	N/A	295 @ 1400	97	N/A	EM. SPL. TC.
N/A	F4CE0454D*D	99 @ 2500	72	N/A	273 @ 1400	84	N/A	EM. SPL. TC.
N/A	F4BE0454A*D	99 @ 2300	75	N/A	280 @ 1400	87	N/A	EM. SPL. TC.
N/A	F4CE0454A*D	99 @ 2300	75	N/A	294 @ 1400	91	N/A	EM. SPL. TC.
N/A	F4GE0454A*D	99 @ 2300	75	N/A	294 @ 1400	91	N/A	EM. SPL. TC.
N/A	F4BE0454G*D	99 @ 2200	75	N/A	280 @ 1400	87	N/A	EM. SPL. TC.
N/A	F4BE0454B*D	99 @ 2100	79	N/A	288 @ 1400	90	N/A	EM. SPL. TC.
N/A	F4GE0454C*D	95 @ 2200	73	N/A	294 @ 1400	92	N/A	EM. SPL. TC.
N/A	F4CE0454E*D	90 @ 2500	65	N/A	258 @ 1400	79	N/A	EM. TC.
N/A	F4CE0454C*D	89 @ 2300	67	N/A	263 @ 1400	82	N/A	EM. TC.
N/A	F4GE0454F*D	89 @ 2300	67	N/A	263 @ 1400	82	N/A	EM. TC.
N/A	F4GE0454E*D	84 @ 2200	66	N/A	269 @ 1400	84	N/A	EM. SPL. TC.
N/A	F4CE0354A*D	78 @ 2300	78	N/A	221 @ 1400	92	N/A	EM. SPL. TC.
N/A	F4CE0354B*D	74 @ 2300	74	N/A	221 @ 1400	92	N/A	EM. TC.
N/A	F4CE0354C*D	67 @ 2300	67	N/A	192 @ 1400	80	N/A	EM. SPL. TC.
N/A	F4GE0454B*D	99 @ 2200	75	N/A	294 @ 1400	91	N/A	EM. TC.
N/A	F4GE0454G*D	80 @ 2000	70	N/A	266 @ 1400	82	N/A	EM. TC.
N/A	F4GE0454H*D	90 @ 2000	76	N/A	294 @ 1400	88	N/A	EM. TC.
N/A	F4GE0654A*D	99 @ 2000	55	N/A	325 @ 1400	67	N/A	EM. SPL. TC.
N/A	F4CE0454F*D	99 @ 2200	83.2	N/A	295 @ 1400	95.6	N/A	EM. SPL. TC.
N/A	F4GE0454J*D	99 @ 2200	83.2	N/A	294 @ 1400	96	N/A	EM. SPL. TC.
N/A	F4GE0454K*D	95 @ 2200	80	N/A	269 @ 1400	94	N/A	EM. SPL. TC.
N/A	F4GE0454M*D	84 @ 2200	71	N/A	269 @ 1400	87	N/A	EM. SPL. TC.