California Environmental Protection Agency AIR RESOURCES BOARD	DEUTZ AG	EXECUTIVE ORDER U-R-013-0224 New Off-Road Compression-Ignition Engines
---	----------	--

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR		DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2007	7DZXL06.5074	6.472	Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Direct Diesel Injection, Turbocharger, Charge Air Cooler, Exhaust -Gas Recirculation, Electronic Control Module, Smoke Puff Limiter			Loaders, Tractor, Dozer, Pump, Compressor, Generator Set, Other OEM Products			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

POWER STA	EMISSION		EXHAUST (g/kW-hr)					OPACITY (%)		
	STANDARD CATEGORY		нс	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
75 ≤ kW < 130	Tier 3	STD	N/A	N/A	4.0	5.0	0.30	20	15	50
130 <u><</u> kW < 225	Tier 3	STD	N/A	N/A	4.0	3.5	0.20	20	15	50
		FEL	-	-	4.0	-	0.30	-	-	-
		CERT	-	-	4.0	1.8	0.25	20	6	28

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief Mobile Source Operations Division

day of April 2007.

Engine Model Summary Form

Manufacturer: DEUTZ AG Engine category: Nonroad Cl EPA Engine Family: 7DZXL06.5074 Mfr Family Name: TCD914L06 MECH 75-130KW TIER3

New Submission

Process Code:

Attachment Eo# u-R-013-0224

	LIFCM							;	
	DDI, TC, CAC, EGR	~		~	2	~	~ ~	~	
rol 1930	ËG.	DDI, TC, CAC, EGR	DDI, TC, CAC, EGR	DDI, TC, CAC, EGR	DDI, TC, CAC, EGR	DDI, TC, CAC, EGR	DDI, TC, CAC, EGR	DDI, TC, CAC, EGR	
9.Emission Control evice Per SAE J193	CAC.	, CAC	. GAO	, CAC	CAC	CAC	CAC	, CAC	
Emissic Ce Per	DI TC	JI, TC	JI, TC	JI, TC	JI, TC	JI, TC	01, TC	JI, TC	×.,
e Devi	10	Ы	D	Ы	DL	Ы	6	Ы	
ate: k torqu	6	6		-		1	0	0	
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930	54.9	54.9	50.1	50.1	50.1	50.1	48.0	48.0	
.8 Irl/sdl)									
ate: 2peak	3								
7.Fuel Rate: mm/stroke@peak torque	10	103	94	94	94	8	6 6	6	
7. mm/			1.20						
g RPM oss)	t600	1600	1600	1600	1600	1600	1600	1600	
6.Torque @ RPM (SEA Gross)	625@1600	625@1600	600@1600	600@1600	600@1600	600@1600	580@1600	580@1600	
6.To (5	9	Θ	9	9	9	9	\$	LC)	
te: ak HP only)									のないのです。
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	69.8	63.8	99.3	53.3	66.7	60.9	56.6	50.9	1000 1000 1000 1000 1000 1000 1000 100
5.F (lbs/hr (for d									
A H H									
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	94.00	89	89	89	87	85	85	85	
4.Fue /stroke (for die			14 14 14 14 14 14 14 14 14 14 14 14 14 1						
mm .				Summer States					
(RPM ross)	2300	2150	2000	146.2@1800	168.3@2300	2150	2000	1800	
3.BHP@RPM (SAE Gross)	4.2 Q	167@2150	159.6@2000	16.2@	i8.3@	160.9@2150	151.5@2000	39.5 Q	
	80.17	-		1/		4		13 13	
lodel	ICD914L06 80.174.2@2300	06	00	06	06	90	90	rcD914L06 ¹⁰ 139.5@1800	
jine N	914L	rcd914L06	rcD914L06	rcD914L06	TCD914L06	rcD914L06	rcD914L06	914L	
2.Engine Model	TCD	TCD	TCD	TCD	100	TCD	TCD	TCD	
e Coc	129A	124A	119A	109A	C3C1125A	120A	113A	104A	
I.Engine Code	C3C1129A	C3CI124A	C3CI119A	C3C1109A	C3CI	C3C1120A	C3CI113A	C3CI104A	
÷.									