

## **KUBOTA CORPORATION**

EXECUTIVE ORDER U-R-025-0284 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2007	7KBXL01.5EAD	1.499	Diesel	5000		
SPECIAL	FEATURES & EMISSION	· · · · · · · · · · · · · · · · · · ·	TYPICAL EQUIPMENT APPLICATION			
[	Direct Diesel Injection, Tu Smoke Puff Limiter (Sor	urbocharger, ne Models)	Loader			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION STANDARD CATEGORY	EXHAUST (g/kW-hr)				OPACITY (%)				
POWER CLASS			нс	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
19 ≤ kW < 37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT			6.6	1.5	0.50	5	2	15

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of December 2006.

Annette Hebert, Chief

Mobile Source Operations Division

## **Engine Model Summary Form**

CONF. JEINIME

Manufacturer: KUBOTA Corporation

Engine category: Nonroad Cl EPA Engine Family: 7KBXL01.5EAD

Mfr Family Name: N/A

Process Code: New Submission

Attendament Esteu-R-0250284

	arran ka	en serve	60.52 50	v-1:*8%		ALC: USA	********
30						7	
9.Emission Control Device Per SAE J1930							
ion C er SA		И. SPI		SP		S.	
Emiss ce Pe				М Ш		Ž U	
8.Fuel Rate: (lbs/hr)@peak torque							
8.Fuel Rate: hr)@peak tor	16)	Ŋ	Š	બ		4	
G pe	<u>.</u>	2		7	<u>2</u>	12	
8.f bs/hr)						101	
7.Fuel Rate: mm/stroke@peak torque							
uel Rai troke@ torque		4 ت	(e)	40.5		0. T	
7.Fu m/stn to				-554 1 7			
E							
Σ	[8]	9	[0]	0	<u> </u>	0	
6.Torque @ RPM (SEA Gross)	9).	) 180	9.5	)180		08 F.	
EA G		.4@	(a)	.7@1	(O)	<b>D</b> 6:	
6.To	6	97	3	6	0.	6	
0							
5.Fuel Rate: bs/hr) @ peak HP (for diesels only)							
5.Fuel Rate: /hr) @ peak or diesels on	.01	8.2	(0)	5.0	0	6.7	
5.Fuel Rate: bs/hr) @ peak HF (for diesels only)							
ğ E				7.5			
A H							
4.Fuel Rate: \stroke @ peak (for diesel only)	· •	ω	0)	တ			
4.Fuel Rate: stroke @ pea or diesel only	88	38.8	415	35.9	(38)	38	
4.Fuel Rate: mm/stroke @ peak H (for diesel only)							
Ē							
¥ (§	00	8	00	8	00	8	
3.BHP@RPM (SAE Gross)	2)28	28	225	<b>2</b> 25	228	28	
3.BHP@RPM (SAE Gross)		3.4	37 4@250	37.4@2500	2 6@2800	2.6	
		Y			7	7	
<u> </u>	ES	ES	Si	ES	ES	ES	
Mod	DIFT	1-10	High	금	旨	<u></u>	
gine	3ªM	3-M-	3-M-	3-⊠	3-M-	3-₩	
Ē	0316	7150	150	1150	150	1150	
1.Engine Code 2.Engine Model	#SEFTIGHMESON DASORMINICAL	D1503-M-DI-T-ES01b D1503-M-DI-T-ES 43.4@2800	50g/MDJT-ES02 D1503-M-DJ-T-ES-	D1503+M-DI-T-ES02b D1503-M-DI-T-ES	1503-M401-1-ES03 D1503-M-DITLES	D1503-M-DI-T-ES03b D1503-M-DI-T-ES 42:6@2800	4.
ode	esol	ES01	ES02	ES02	ES03	ES03	
<u>ن</u> ق	1	7-T-	T IO	<u></u>	H	1-IO	
ingir	3-MF	13-M-	W	3-M-	WE	3-M-	
<u>+</u>	0150	D15C	212	D150	0150	D150	
	No. of the last	a	17.5	2	Deat	3	- 程度22