California Environmental Protection Agency AIR RESOURCES BOARD	YANMAR CO., LTD.	EXECUTIVE ORDER U-R-028-0347 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2007	7YDXL2.19K4N	2.190	Diesel	5000

SPECIAL FEATURES & EMISSION CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION
Direct Diesel Injection	Crane, Loader, Tractor, Dozer, Pump, Compressor, Excavator

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbons (HC), oxides of nitrogen (NOx), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
19 ≤ kW < 37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT	--	--	5.7	3.5	0.26	1	2	2

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 22nd day of December 2006.

Raphael Susnowitz

for Annette Hebert, Chief
Mobile Source Operations Division

ATTACHMENT, p1 of 2
V-R-028-0347

Return to Template

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate. mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
7YDXL2.19K4N	N/A	4TNV88-VM1	49.5/3000	31.2	20.6	106.9/1200	35.0	9.3	EM
7YDXL2.19K4N	N/A	4TNV88-D	49.5/3000	31.2	20.6	104.0/1200	33.6	8.9	EM
7YDXL2.19K4N	N/A	4TNV88-I	48.2/2900	30.9	19.7	104.0/1200	33.6	8.9	EM
7YDXL2.19K4N	N/A	4TNV88-K	46.9/2800	30.6	18.9	104.0/1200	33.6	8.9	EM
7YDXL2.19K4N	N/A	4TNV88-L	45.1/2700	30.4	18.1	104.0/1200	33.6	8.9	EM
7YDXL2.19K4N	N/A	4TNV88-M	43.3/2600	30.5	17.5	104.0/1200	33.0	8.7	EM
7YDXL2.19K4N	N/A	4TNV88-N	41.6/2500	30.3	16.7	105.1/1200	33.5	8.9	EM
7YDXL2.19K4N	N/A	4TNV88-P	39.8/2400	30.2	16.0	104.3/1200	33.1	8.8	EM
7YDXL2.19K4N	N/A	4TNV88-Q	38.1/2300	30.2	15.3	104.0/1300	34.5	9.9	EM
7YDXL2.19K4N	N/A	4TNV88-S	36.3/2200	29.2	14.2	103.7/1200	33.7	8.9	EM
7YDXL2.19K4N	N/A	4TNV88-V	34.7/2100	29.3	13.6	104.0/1000	35.0	7.7	EM
7YDXL2.19K4N	N/A	4TNV88-W	32.9/2000	28.8	12.7	102.5/1200	33.1	8.8	EM
7YDXL2.19K4N	N/A	4IRH8N-2	46.9/2800	30.6	18.9	104.0/1200	33.6	8.9	EM
7YDXL2.19K4N	N/A	4IRH8N-1	39.8/2400	29.8	15.8	102.5/1100	34.5	8.4	EM
7YDXL2.19K4N	N/A	4TNV88-XBV	38.6/2300	30.0	15.2	105.4/1300	34.7	9.9	EM
7YDXL2.19K4N	N/A	4D88E-5XAB	41.0/2350	30.6	15.8	106.2/1300	35.0	10.0	EM
7YDXL2.19K4N	N/A	4TNV88-XBX	38.6/2300	30.0	15.2	105.4/1300	34.7	9.9	EM
7YDXL2.19K4N	N/A	4D88E-5XA	41.0/2350	30.6	15.8	106.2/1300	35.0	10.0	EM
7YDXL2.19K4N	N/A	4D88E-5K	46.9/2800	30.5	18.8	107.3/1200	34.0	9.0	EM
7YDXL2.19K4N	N/A	4D88E-5M	43.3/2600	30.5	17.5	104.0/1200	33.0	8.7	EM
7YDXL2.19K4N	N/A	4D88E-5N	41.6/2500	30.3	16.7	105.1/1200	33.5	8.9	EM
7YDXL2.19K4N	N/A	4D88E-5P	39.8/2400	30.2	16.0	104.3/1200	33.1	8.8	EM
7YDXL2.19K4N	N/A	4D88E-5Q	38.1/2300	30.2	15.3	104.0/1300	34.5	9.9	EM
7YDXL2.19K4N	N/A	4D88E-5S	36.3/2200	29.2	14.2	103.7/1200	33.7	8.9	EM
7YDXL2.19K4N	N/A	4D88E-5W	32.9/2000	28.8	12.7	102.5/1200	33.1	8.8	EM
7YDXL2.19K4N	N/A	4TNV88-XYB	42.2/2400	30.9	16.3	106.2/1300	35.0	10.0	EM
7YDXL2.19K4N	N/A	4D88E-5XB	42.6/2400	31.2	16.5	106.2/1300	35.0	10.0	EM
7YDXL2.19K4N	N/A	D2.2ACAE2SW	49.5/3000	30.9	20.4	108.4/1200	34.3	9.1	EM
7YDXL2.19K4N	N/A	4TNV88-XMS	49.5/3000	30.9	20.4	108.4/1200	34.3	9.1	EM
7YDXL2.19K4N	N/A	4TNV88-XWA	46.9/2800	30.5	18.8	107.3/1200	34.0	9.0	EM
7YDXL2.19K4N	N/A	4TNV88-XWL	46.9/2800	30.5	18.8	107.3/1200	34.0	9.0	EM
7YDXL2.19K4N	N/A	D2.2ACAE2E1	36.3/2200	29.2	14.2	103.7/1200	33.7	8.9	EM

DDI

ATTACHMENT
p2 OF 2

Return to Template R/C

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
7YDXL2.19K4N	N/A	4TNV88-XNSS	46.9/2800	30.5	18.8	107.3/1200	34.0	9.0	EM DDI
7YDXL2.19K4N	N/A	4TNV88-XXUL	41.2/2700	27.8	16.5	93.3/1500	29.0	9.6	EM
7YDXL2.19K4N	N/A	4TNV88-XXBM	43.3/2600	29.5	16.9	104.0/1200	33.0	8.7	EM
7YDXL2.19K4N	N/A	4TNV88-XGP	49.5/3000	30.9	20.4	108.4/1200	34.3	9.1	EM
7YDXL2.19K4N	N/A	4TNV88-XXBD	49.5/3000	30.3	20.0	104.7/1200	33.6	8.9	EM
7YDXL2.19K4N	N/A	3NNDA	49.3/3000	29.5	19.5	104.5/1000	32.5	7.2	EM
7YDXL2.19K4N	N/A	3NNKA	46.6/2800	28.8	17.8	105.2/1100	33.2	8.0	EM
7YDXL2.19K4N	N/A	3NNLA	44.8/2700	28.4	16.9	105.8/1000	34.1	7.5	EM
7YDXL2.19K4N	N/A	3NNMA	43.0/2600	29.0	16.6	107.2/1200	34.4	9.1	EM
7YDXL2.19K4N	N/A	3NNNA	41.5/2500	29.0	16.0	105.3/1000	34.2	7.5	EM
7YDXL2.19K4N	N/A	3NNPA	39.6/2400	28.2	14.9	104.3/1100	33.5	8.1	EM
7YDXL2.19K4N	N/A	3NNQA	37.9/2300	27.9	14.1	105.7/1000	34.2	7.5	EM
7YDXL2.19K4N	N/A	3NNSA	36.1/2200	27.6	13.4	107.0/1000	34.7	7.6	EM
7YDXL2.19K4N	N/A	3NNVA	34.4/2100	27.6	12.8	106.9/1000	34.7	7.6	EM
7YDXL2.19K4N	N/A	3NNWA	32.6/2000	27.7	12.2	104.2/1000	34.1	7.5	EM
7YDXL2.19K4N	N/A	3NNPE	40.5/2400	29.4	15.5	104.3/1100	33.5	8.1	EM
7YDXL2.19K4N	N/A	3NNKC	42.5/2800	27.1	16.7	94.3/1600	28.9	10.2	EM
7YDXL2.19K4N	N/A	3NNLC	40.9/2700	26.5	15.8	93.8/1500	28.9	9.5	EM