



Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2007	7YDXL3.32K4N	3.319	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection			Crane, Loader, Tractor, Dozer, Pump, Compressor, Excavator	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbons (HC), oxides of nitrogen (NO<sub>x</sub>), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NO<sub>x</sub>), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
			HC	NO <sub>x</sub>	NMHC+NO <sub>x</sub>	CO	PM	ACCEL	LUG	PEAK
37 ≤ kW < 75	Tier 2	STD	N/A	N/A	7.5	5.0	0.40	20	15	50
		CERT	--	--	6.0	3.0	0.22	4	4	5

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

**This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.**

Executed at El Monte, California on this 22<sup>nd</sup> day of December 2006.

  
 Annette Hebert, Chief  
 Mobile Source Operations Division

# Engine Model Summary Form

*ATTACHMENT  
V-R-028-0351*

Manufacturer: Yanmar Co., Ltd.  
 Engine category: Nonroad CI  
 EPA Engine Family: 7YDXL3.32K4N  
 Mfr Family Name: N/A  
 Process Code: New Submission

1. Engine Code	2. Engine Model	3. BHP @ RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke @ peak torque	8. Fuel Rate: (lbs/hr) @ peak torque	9. Emission Control Device Per SAE J1930
N/A	4TNV98-VM11	71.7/2500	50.5	27.8	193.9/1300	63.5	18.2	EM DP1
N/A	4TNV98-N	59.9/2500	49.5	27.3	184.3/1000	60.1	13.2	EM
N/A	4TNV98-P	67.3/2400	49.1	26.0	183.6/1000	58.4	12.9	EM
N/A	4TNV98-Q	64.6/2300	48.6	24.6	182.1/1000	57.7	12.7	EM
N/A	4TNV98-S	62.1/2200	47.7	23.1	182.1/1000	57.7	12.7	EM
N/A	4TNV98-V	59.5/2100	48.2	22.3	182.1/1000	57.7	12.7	EM
N/A	4TNV98-W	57.0/2000	47.3	20.8	182.1/1000	57.7	12.7	EM
N/A	4D98E-2N	69.9/2500	49.5	27.3	184.3/1000	60.1	13.2	EM
N/A	4IR18N	69.9/2500	48.6	26.8	182.1/1000	55.1	12.1	EM
N/A	4TNV98-XDB	54.6/1900	47.5	19.9	180.6/1000	56.0	12.3	EM
N/A	4TNV98-YTBL	68.5/2450	49.3	26.6	184.3/1000	60.1	13.2	EM
N/A	4D98E-2XFB	66.4/2300	49.9	25.3	182.1/1000	57.7	12.7	EM
N/A	4TNV98-XBV	59.5/2000	50.1	22.1	185.1/1000	60.4	13.3	EM
N/A	4TNV98-XTBW	68.5/2300	51.2	26.0	192.4/1600	60.9	21.5	EM
N/A	4CG1-N	69.9/2500	49.5	27.3	184.3/1000	60.1	13.2	EM
N/A	4CG1-P	67.3/2400	49.1	26.0	183.6/1000	58.4	12.9	EM
N/A	4CG1-Q	64.6/2300	48.6	24.6	182.1/1000	57.7	12.7	EM
N/A	4CG1-S	62.1/2200	47.7	23.1	182.1/1000	57.7	12.7	EM
N/A	4CG1-V	59.5/2100	48.2	22.3	182.1/1000	57.7	12.7	EM
N/A	4CG1-W	57.0/2000	47.3	20.8	182.1/1000	57.7	12.7	EM
N/A	D3.4ACAE2EC	59.5/2100	48.2	22.3	182.1/1000	57.7	12.7	EM
N/A	4D98E-2Q	64.6/2300	48.6	24.6	182.1/1000	57.7	12.7	EM
N/A	D3.4ACAE2SW	67.3/2400	49.1	26.0	183.6/1000	58.4	12.9	EM
N/A	D3.4ACAE2EC	57.0/2000	47.3	20.8	182.1/1000	57.7	12.7	EM