

DAEDONG INDUSTRIAL CO., LTD.

EXECUTIVE ORDER U-R-044-0046 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)						
2007	7DCLL02.2D87	2.197 & 1.647	Diesel	5000						
	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION							
	Indirect Diesel Inje	ection	Tractor							
Aeroe-Aar Cale S	Application of the property of									

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION			E	XHAUST (g/kw-l		OPACITY (%)			
POWER CLASS	STANDARD CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
19 < KW < 37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT			6.5	1.8	0.42	4	5	7

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______day of April 2007.

Annette Hebert, Chief

Mobile Source Operations Division

ATTACHMENT 10F1

Engine Model Summary Form

Manufacturer: Daedong Industrial Co. Ltd.

Engine category: Nonroad CI

EPA Engine Family: 7DCLL02.2D87

Mfr Family Name: NA

Process Code: New Submission

4-8-044-00+6

	1				\$75	Ÿ.									N.		¥
8.Fuel Rate: 9.Emission Control (Ibs/hr)@peak torque Device Per SAE J1930	TIT NA	NA.	X	AN	Ą	*	W	¥	- A	¥	M	¥	NA	¥	NA	¥	AN
8.Fuel Rate: (lbs/hr)@peak torque	10.59	10.95	10,76	10.59	10.95	10.95	10.95	10.76	13,97	14.35	13.97	14.35	14.35	14.35	14.35	10.95	10.95
7.Fuel Rate: mm/stroke@peak torque	37.6	38.87	38.2	37.6	38.87	38.87	38.87	38.2	37.2	38.2	37.2	38.2	38.2	38.2	38.2	38.87	38.87
6. Torque @ RPM (SEA Gross)	75.6@1700	80.1@1700	77.1@1700	75.6@1700	80.1@1700	80.1@1700	80.1@1700	77.1@1700	102.5@1700	110.2@1700	102.5@1700	110.2@1700	110.2@1700	110.2@1700	110.2@1700	80.1@1700	80.1@1700
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	14.25	14.47	13.27	14.25	14.47	14.47	14.47	13.27	18.91	19.01	18.91	19.01	19.01	19.01	19:01	14.47	14.47
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	31.85	33.6	30.81	31.85	33.6	33,6	33.6	30.81	31.7	Administration of the state of	218	33.1	33.1	33.1	33.1	33.6	33.6
3.BHP@RPM (SAE Gross)	34.2@2700	34.1@2600	32.3@2600	34.2@2700	34.1@2600	34.1@2600	34.1@2600	32.3@2600	45@2700	45.2@2600	45@2700	45.2@2600	45.2@2600	45.2@2600	45.2@2600	34.1@2600	34.1@2600
2.Engine Model	3A165	4A220	4A220	4A220	4A220	4A220	4A220	4A220	3A165	3A165							
1.Engine Code	3A165B	3A165D	3A165LG-2	3A165LXF	3A165LXE	3A165LXH	3A165LXM	3A165LXLG	4A220	4A220B	4A220LXA	4A220LXB	4A220LXH	4A220LXM	4A220LXL	3A165LXB	3A165LXD