

ISUZU MOTORS LIMITED

EXECUTIVE ORDER U-R-006-0310 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

| MODEL YEAR | ENGINE FAMILY | DISPLACEMENT (liters) | FUEL TYPE | USEFUL LIFE (hours) |
|---------------------------|---|--|---------------------------|------------------------|
| 2009 | 9SZXL09.8HXA | 9.8 | Diesel | 8000 |
| SPECIAL | FEATURES & EMISSION | | TYPICAL EQUIPMENT | |
| Direct Dies Electronic | el Injection, Turbocharg Control Module, Exhau | er, Charge Air Cooler, st Gas Recirculation | Crane, Loader, Other Indi | ustrial Equipment |

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

| RATED | EMISSION | | | E | XHAUST (g/kW-l | nr) | | OF | PACITY (% | 6) |
|----------------|----------|------|-----|-----|----------------|-----|------|-------|-----------|------|
| POWER | CATEGORY | | HC | NOx | NMHC+NOx | CO | PM | ACCEL | LUG | PEAK |
| 225 ≤ kW < 450 | Tier 3 | STD | N/A | N/A | 4.0 | 3.5 | 0.20 | 20 | 15 | 50 |
| | | CERT | | | 3.5 | 0.9 | 0.15 | 16 | 6 | 27 |

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

_ day of September 2008.

Annette Hebert, Chief

Mobile Source Operations Division

imm the Alber

| | | | | Engine Model Summary Template | ummary le | mplate | | | |
|---------------|----------------|---|--------------------------|---|--|----------------------------------|--|--------------------------------------|---|
| | | | | ATTACHMENT | IMENT | | | 2-4-0 | U-R-006-0310 |
| Engine Family | 1. Engine Code | 3 B-P-GRPM mm Engine Code 2. Engine Model (SAE Gross) | 3.BHP@RPM (SAE Gross) | Shilan Rate Shilan Shilan Rate Shilan Shilan Shilan Rate Shilan | 5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only) | 6. Torque (1) RPM (SEA Gross) | 7.Fuel Rate: shrifstroke@peak forque | 8.Fuel Rate: (Ibs/hr)@peak torque | 9 Emission Control Device Per SAE J193 |
| 9SZXL09 8HXA | 6UZ1XDHAA-01 | AH-6UZ1X | 362.1@1950 | 1957XLD9.8HXA 6UZIXDHAA4T AH-6UZIX 3521@1950 196.0@1950 127.5@1950 1058@1500 216.0@1500 108.1@1500 ECM.TG.CAC.DF | 127.5@1950 | 1058@1500 | 276.0@1500 | 108.1@1500 | ECM, TC, CAC, DF EG-R |
| ASZXLD9 8HXA | 6UZ1XDHAA-02 | AH-6UZ1X | 348.7@1800 | ЧБЕХИДОВ ВНХА ВИZТИРНАЙ-И2 АН-БИZ1X 348.7@1800 202.0@1800 121.3@1800 1033@1500 211.0@1500 105.5@1500 ECИ.ТС.ОИС. UF | 121.3@1800 | 1033@1500 | 211.0@1500 | 105.6@1500 | ECM, TC, CAC, DF |
| 952XL09 8HXA | 6UZ1XDHAA-03 | AH-6UZ1X | 362.1@2000 | 952X.098HXA 6UZIXDHAA-03 AH-6UZIX 362.1@2000 195.0@2000 130.1@2000 1058@1500 216.0@1500 106.1@1500 J-FCM.TG, CAC, DF | 130.1@2000 | 1058@1500 | 216.0@1500 | 500 108.1@1500 (J. ECM, TC, CM | , ECM, TC, CAC, DF |