KUBOTA Corporation

EXECUTIVE ORDER U-R-025-0370 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR ENGINE FAMILY		DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2009	9KBXL01.1BCB	1.123	. Diesel	3000			
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION				
	Indirect Diesel Inje	ection	Tractor, Compressor, Generator Set, Other Industrial Equipment				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OF	OPACITY (%)		
POWER CLASS			HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK	
8 ≤ kW < 19	Tier 4	STD	N/A	N/A	7.5	6.6	0.40	20	15	50	
		CERT			6.7	1.4	0.19	5	4	10	

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______ 24^{1/4} day of December 2008.

Annette Hebert, Chief

Mobile Source Operations Division

Rophael Susnowity

Engine Model Summary Form

KUBOTA Corporation Manufacturer:

Nonroad Cl Engine category:

9KBXL01.1BCB EPA Engine Family:

Mfr Family Name: N/A

Running Change Process Code:

Attachment

Page 1 of 1

U-R-025-0370

D1105-ET 21.9@2800 21.7 11.6 52.9@7700 25.5 7.3 EM IDID. T 42.8@3200 21.7 11.6 52.7@2200 25.4 9.4 EM IDI105-ET 22.5@2700 21.9 10.8 52.7@2200 25.4 9.4 EM IDI105-ET 22.5@2700 21.9 9.9 56.5@1900 24.2 7.7 EM IDI105-ET 22.5@2700 21.9 9.9 56.5@1900 24.4 7.8 EM IDI105-ET 22.3@2700 21.9 9.2 55.6@1900 24.4 7.8 EM IDI105-ET 20.9@2400 22.1 8.9 56.5@1900 24.4 7.8 EM IDI105-ET 20.9@2400 22.1 8.9 56.5@1900 25.4 6.8 EM IDI105-ET 20.0@2400 22.1 8.9 56.7@1500 25.4 6.8 EM IDI105-ET 20.0@2400 22.1 8.9 55.7@1600 25.4 6.8 EM IDI105-ET 20.0@2200 21.9 8.1 56.7@1600 25.4 6.8 EM IDI105-ET 40.0@2200 21.9 8.1 56.7@1600 25.4 6.8 EM IDI105-ET 41.8@2200 21.9 8.1 56.7@1600 25.4 6.8 EM IDI105-ET 41.8@2200 21.9 8.4 56.2@1600 25.2 6.8 EM IDI105-ET 41.8@2200 21.9 8.4 56.2@1600 25.2 6.8 EM IDI105-ET 41.8@2200 21.9 8.4 56.2@1600 25.4 6.8 EM IDI105-ET 41.8@2200 21.9 8.4 56.2@1600 25.4 6.8 EM IDI105-ET 41.8@2200 21.9 8.4 56.2@1600 25.4 6.8 EM IDI105-ET 41.8@2200 21.9 8.4 56.2@1600 25.2 6.8 EM IDI105-ET 41.8@2200 21.9 8.4 56.2@1600 25.4 6.8 EM IDI105-ET 41.8@2200 21.9 8.4 56.2@1600 25.2 6.8 EM IDI105-ET 41.8 61.8 EM IDI105-ET 41.8 EM IDI105-ET
185. 248@3200 21.7 116 52.7@2200 25.4 9.4 24.8@3000 22.9 10.8 53.4@1900 25.4 9.4 24.3@2800 22.9 10.8 53.4@1900 25.4 8.1 22.5@2700 21.9 9.9 50.5@1900 24.4 7.8 22.3@2700 21.9 9.2 52.6@1700 25.4 6.8 20.8@2400 22.1 8.9 52.7@1600 25.4 6.8 20.8@2400 22.1 8.9 52.7@1600 25.4 6.8 19.8@2200 21.9 8.1 52.7@1600 25.4 6.8 19.8@2200 21.9 8.4 52.2@1600 25.2 6.8
24.8@3000 22.3 11.2 52.7@2200 25.4 9.4 24.3@2800 22.9 10.8 53.4@1900 25.4 8.1 22.5@2700 21.9 9.8 50.5@1900 24.4 7.7 22.3@2500 21.9 9.8 50.5@1900 24.4 7.8 21.3@2500 21.9 9.2 52.6@1700 25.4 7.2 20.9@2400 22.1 8.9 52.5@1600 25.4 6.8 20.8@2400 22.1 8.9 52.5@1600 25.2 6.8 19.0@2250 21.4 8.1 50.7@1600 25.4 6.8 19.0@2200 21.9 8.4 52.2@1600 25.2 6.8
24.3@2800 22.9 10.8 53.4@1900 25.4 8.1 22.5@2700 21.9 9.9 50.5@1900 24.2 7.7 22.3@2700 21.6 9.8 50.9@1900 24.4 7.8 21.3@2500 21.9 9.2 52.6@1700 25.4 7.2 20.9@2400 22.1 8.9 52.2@1600 25.5 6.8 20.8@2400 22.1 8.9 52.2@1600 25.2 6.8 19.8@2200 21.9 8.1 50.7@1500 25.4 6.8 19.8@2300 21.9 8.4 52.2@1600 25.2 6.8
22.5@2700 21.9 9.9 50.5@1800 24.2 7.7 22.3@2700 21.6 9.8 50.9@1900 24.4 7.8 21.3@2500 21.9 9.2 52.6@1700 25.4 7.2 20.9@2400 22.1 8.9 52.7@1600 25.4 6.8 20.8@2400 22.1 8.9 52.7@1600 25.2 6.8 19.0@2200 21.9 8.1 50.7@1500 25.4 6.8 19.8@2300 21.9 8.4 52.2@1600 25.2 6.8
22.3@2700 216 98 50.9@1900 24.4 7.8 21.3@2500 219 9.2 52.6@1700 25.4 7.2 20.9@2400 22.2 8.9 52.7@1600 25.4 6.8 20.8@2400 22.1 8.9 52.5@1600 25.2 6.8 1\\$\text{\scale}\$\times\$ 19.0@2200 21.9 8.1 50.7@1500 25.4 6.8 19.8@2200 21.9 8.1 52.7@1600 25.4 6.8 19.8@2200 21.9 8.4 52.2@1600 25.2 6.8
20.9@2400 21.9 9.2 52.6@1700 25.4 7.2 20.9@2400 22.2 8.9 52.7@1600 25.4 6.8 20.8@2400 22.1 8.9 52.7@1600 25.2 6.8 6.2 (4.2) 49.0@2250 21.9 8.1 50.7@1500 25.4 6.8 (4.2) 49.0@2200 21.9 8.4 52.2@1600 25.2 6.8 (4.2) 49.8@2300 21.9 8.4 52.2@1600 25.2 6.8 (4.2) 42.0
20.9@2400 22.2 8.9 52.7@1600 25.4 6.8 20.8@2400 22.1 8.9 52.5@1600 25.2 6.8 14.
20.8@2400 22.1 8.9 52.5@1600 25.2 6.8 (4.2. 19.0@2250 21.4 8.1 50.7@1500 24.6 6.2 (4.3. 19.0@2200 21.9 8.1 52.7@1600 25.4 6.8 19.8@2300 21.9 8.4 52.2@1600 25.2 6.8 (19.8@2300 21.9 8.4 52.2@1600 25.2 6.8
(4.7 19.0@2250 21.4 8.1 50.7@1500 24.6 6.2 (6.8 19.0@2200 21.9 8.1 52.7@1600 25.2 6.8 (6.8 19.8@2300 21.9 8.4 52.2@1600 25.2 6.8 (6.8 19.8@2300 21.9 (7.4 1.2 1.2 19.8 19.8 19.8 19.8 19.8 19.8 19.8 19.8
19.0@2200 21.9 8.1 52.7@1600 25.4 6.8 19.8@2300 21.9 8.4 52.2@1600 25.2 6.8
19.8@2300 21.9 8.4 52.2@1600 25.2 6.8
Date: 07 (29 / 200
002
002)
002
\vdash