



Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2010	AJDXL08.1037	8.1	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbo Charger, Charge Air Cooler, Smoke Puff Limiter, Electronic Control Module			Loaders, Tractor, Pump, Compressor, Generator Set and Other Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
130 ≤ kW < 450	Tier 3	STD	N/A	N/A	4.0	3.5	0.20	20	15	50
		FEL	--	--	6.3	--	--	--	--	--
		CERT	--	--	6.1	0.8	0.15	10	3	18

**BE IT FURTHER RESOLVED:** That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

**This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.**

Executed at El Monte, California on this 21<sup>ST</sup> day of December 2009.

*M. Hebert* FOR AGM  
Annette Hebert, Chief  
Mobile Source Operations Division

Engine Model Summary Form

Manufacturer: John Deere Power Systems  
Engine category: Nonroad CI  
EPA Engine Family: AJDXL08.1037  
Mfr Family Name: 450HF  
Process Code: New Submission

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
6081HF070A	6081H	335.26@2200	160.00@2200	116.85@2200	1126.85@1400	226@1400	108.03@1400	EM EC SPL
6081HN006	6081H	383.54@2200	181.20@2200	134.42@2200	1087.03@1600	219@1600	118.17@1600	EM EC SPL
6081HTJ07A	6081H	181.04@2000	96.20@2000	64.82@2000	678.47@1400	135.3@1400	63.94@1400	EM EC SPL
6081HTJ08A	6081H	241.39@2000	123.00@2000	83.12@2000	907.08@1400	172.5@1400	81.35@1400	EM EC SPL
6081HTJ09A	6081H	274.91@2200	131.70@2200	97.89@2200	884.96@1400	163.7@1400	77.17@1400	EM EC SPL
6081HTJ07	6081H	181.04@2000	96.20@2000	64.89@2000	678.47@1400	135.3@1400	63.89@1400	EM EC SPL
6081HTJ08	6081H	241.39@2000	123.00@2000	83.01@2000	907.08@1400	172.5@1400	81.44@1400	EM EC SPL
6081HTJ09	6081H	274.91@2200	131.70@2200	97.80@2200	884.96@1400	163.7@1400	77.25@1400	EM EC SPL

TCAS, DD  
↓