California Environmental Protection Agency AIR RESOURCES BOARD

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003:

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2010	ANHXL06.7DCA	6.7	Diesel	8000			
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION				
Direct Turboch	t Diesel Injection, Engine harger, Charge Air Cooler Recirculation	Control Module, , and Exhaust Gas	Loader, Tractor, Dozer, Gener and Other Industrial Equip	rator Set, ment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)			
CLASS			HC	NOx	NMHC+NOx	со	РM	ACCEL	LUG	PEAK	
75 ≤ kW < 130	Tier 3	STD	N/A	N/A	4.0	5.0	0.30	20	15	50	
130 ≤ kW < 225	Tier 3	Tier 3 STD		N/A	4.0	3.5	0.20	20	15	50	
		FEL	N/A	N/A	N/A	N/A	0.14	N/A	N/A	N/A	
		CERT			3.3	0.9	0.07	9	1	12	

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this day of April 2010.

Annette Hebert, Chief Mobile Source Operations Division

Engine Model Summary Template

U-12-008-0095 Atlachmen+ 7/30/2010

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torqu	9.Emission Control Device Per SAE J1930	DAI, CAC	ecm _t c the
ANHXL06.7DCA	667TA/EBU	F4HE9687G*J	255 @ 2100	132	N/A	789 @ 1500	153.2	N/A	EM. EC. CAC.		
ANHXL06.7DCA	667TA/EBA	F4HE9684D*J	237 @ 2100	121	N/A	752 @ 1500	144	N/A	EM. EC. CAC		
ANHXL06.7DCA	667TA/EBB	F4HE9684P*J/ F4DE9684P*J	235 @ 2200	116	N/A	752 @ 1500	144	N/A	EM. EC. CAC		
ANHXL06.7DCA	667TA/EBG	F4HE9687P*J	235 @ 2000	116	N/A	752@ 1500	144	N/A	EN. EC. CAC		
ANHXL06.7DCA	667TA/EBD	F4HE9684E*J	227 @ 2000	120	N/A	739 @ 1500	143	N/A	EN. EC. CAC		
ANHXL06.7DCA	N/A	F4HE9684A*J/ F4DE9684A*J	207 @ 2200	115	N/A	701 @ 1400	141	N/A	EM. EC/CAC		Salar sugar subscription and an and subscription
ANHXL06.7DCA	667TA/EBC	F4DE9684L*J/ F4HE9684L*J	231 @ 2200	115	N/A	712 @1600	141	N/A	EM EQ. CAC		
ANHXL06.7DCA	667TA/EBE	F4DE9684S*J/ F4HE9684S*J	215 @ 2200	110	N/A	692 @ 1600	139	N/A	EM.EC. CAC		
ANHXL06.7DCA	667TA/EBH	F4DE9684B*J/ F4DE9687K*J	235 @ 2200	118	N/A	726 @ 1500	143	N/A	EM. EC. CAC		and the state of the
ANHXL06.7DCA	667TA/EBN	F4DE9684N*J/ F4HE9684N*J	201 @ 2200	103	N/A	645 @ 1600	129	N/A	EM. EC. CAC		-
ANHXL06.7DCA	N/A	F4DE9687J*J	207 @ 2200	102	N/A	701 @ 1600	136	N/A	EM. AC. CAC		
ANHXL06.7DCA	667TA/EBF	F4HE9684V*J/ F4DE9684V*J	211 @ 2000	116	N/A	702 @ 1400	139	N/A	EM. EC. CAC		The state of the s
ANHXL06.7DCA	667TA/EBM	F4HE9684J*J	204 @ 2100	109	N/A	690 @ 1500	139	N/A	EM. EC. CAC.		
ANHXL06.7DCA	667TA/EBJ	F4DE9684C*J	211 @ 2200	107	N/A	639 @ 1400	127.5	N/A	EM EQ. CAC.		Tel Mandala a di seria da da se
ANHXL06.7DCA	667TA/EBK	F4DE9684D*J	194 @ 2200	102	N/A	633 @ 1400	127	N/A	EM EC CAC.		
ANHXL06.7DCA	667TA/EBL	F4DE9684E*J	180 @ 2200	93	N/A	623 @ 1400	124	N/A	EM. EC. CAC.		and a star from player stars. Vestige
ANHXL06.7DCA	667TA/EBP	F4DE9684H*J	165 @ 2200	89	N/A	571 @ 1400	118	N/A	EN. EC. CAC.		
ANHXL06.7DCA	N/A	F4HE9687A*J	207 @ 2200	102	N/A	701 @ 1400	136	N/A	EM. EC. CAC.		No.7.5+ Part doors white surgers and
ANHXL06.7DCA	667TA/EBR	F4HE9687S*J	227 @2200	111.8	N/A	708 @ 1400	135.3	N/A	EM. EC. CAC.		
ANHXL06.7DCA	667TA/EBV	F4DE9684M*J/ F4HE9684M*J	243 @ 2200	127	N/A	752 @ 1500	152	N/A	EM. EC. CAC.		a under all successful and the second state
ANHXL06.7DCA	667TA/EBX	F4HE9687T*J/ F4DE9687T*J	250 @ 2200	126	N/A	788 @ 1500	153	N/A	EM.EC.CAC.		
ANHXL06.7DCA	667TA/EBY	F4HE9687N*J/ F4DE9687N*J	220 @ 2200	114	N/A	752 @ 1500	152	N/A	EM.EC.CAC.		
ANHXL06.7DCA	667TA/EB2	F4HE9687C*J	221 @ 2200	113	N/A	686 @ 1500	137	Ń/A	EM.EC.CAC.		
ANHXL06.7DCA	667TA/EB3	F4HE9687W*J	173 @ 2200	90	N/A	586 @ 1500	120	N/A	EM.EC.CAC		
ANHXL06.7DCA	667TA/EB4	F4HE96871*J	221 @ 2200	113	N/A	683 @ 1500	130	N/A	EM.EC.CAC.		
										V	