DAIMLER AG

EXECUTIVE ORDER U-R-016-0088 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2010	AMBXL07.2RJA	4.25, 4.8, 6.37, 7.2	Diesel	8000		
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION			
Direct Dies	sel Injection, Turbocharg Engine Control M	er, Charge Air Cooler, odule	Crane, Loader, Tractor, Dozer, Pump, Compressor			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kw-hr)					OPACITY (%)		
POWER CLASS	STANDARD CATEGORY		нс	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
75 <u><</u> KW<130	Tier 3	STD	N/A	N/A	4.0	5.0	0.30	20	15	50
130 <u><</u> KW<450	Tier 3	STD	N/A	N/A	4.0	3.5	0.20	20	15	50
		CERT			3.6	1.8	0.18	14	2	29

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

This Executive Order hereby supersedes Executive Order U-R-016-0085 dated January 28, 2010.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______

Annette Hebert, Chief

Mobile Source Operations Division

amutt Haber

ATTACHMENTIOFI

Engine Model Symmary Template

U-R-016-0088 218-12010

•	•	,		4.Fuel Rate:	5.Fuel Rate:		7.Fuel Rate:	3-12010	
Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	mm/stroke @ peak HP (for diesel only)	(lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	mm/stroke@peak torque	8.Fuel Rate: 9.Ei (lbs/hr)@peak torqueDevic	nission Control e Per SAE J1930
AMBXL07.2RJA	926 LA.E3A/1	OM926LA	322 @ 2200	161	115.1	959 @ 1450	188	88.2 DOLT	, ECM, CAC
AMBXL07.2RJA	926 LA.E3A/2	OM926LA	295 @ 2200	151	107.8	885 @ 1450	175	82.2	(all ratings)
AAADXI 07 3D IA	000 4 5244	OMOSCI A	075 @ 0000	428	00.8	044 @ 4400	404	70.0	
AMBXL07.2RJA	906 LA.E3A/1	OM906LA	275 @ 2200	138	98.8	811 @ 1400	161	73.3	<u> </u>
AMBXL07.2RJA	906 LA.E3A/2	OM906LA	255 @ 2200	129	92.2	737 @ 1400	148	67.5	
AMBXL07.2RJA	906 LA.E3A/3	OM906LA	228 @ 2200	121	_86.6	597 @ 1400	122	55.6	
AMBXL07.2RJA	906 LA.E3A/4	OM906LA	201 @ 2200	109	77.9	553 @ 1400	114	51.8	·
AMBXL07.2RJA	906 LA.E3A/5	OM906LA	174 @ 2200	94	67.4	516 @ 1400	106	` 68.4	
AMBXL07.2RJA	904 LA.E3A/1	OM904LA	173 @ 2200	131	62.5	498 @ 1400	148	44.9	
AMBXL07.2RJA	904 LA.E3A/2	OM904LA	148 @ 2200	111	53.2	428 @ 1400	125	38	
AMBXL07.2RJA	904 LA.E3A/3	OM904LA	121 @ 2200	92	43.9	347 @ 1400	103	31.3	
AMBXL07.2RJA	904 LA.E3A/4	OM904LA	101 @ 2200	78	37.3	295 @ 1400	89	27.1	
AMBXL07.2RJA	924 LA.E3A/1	OM924LA	195 @ 2200	152	73.4	520 @ 1400	158	48.5	