California Environmental Protection Agency

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours) 3000		
2010	AHZXL.722C90	0.722	Diesel			
	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION			
	Mechanical Direct Ir	jection	Pump, Generator Set, Other Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)				OPACITY (%)			
POWER CLASS			нс	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
8 ≤ kW < 19	Tier 4	STD	N/A	N/A	7.5 .	6.6	0.40	N/A	N/A	N/A
		CERT			7.3	4.6	0.20			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

day of February 2010.

Annette Hebert, Chief Mobile Source Operations Division

Motorenfabrik Hatz Nonroad CI

Attachment page 1 of 1

E0# U-R-034-0228 1/27/2010

Engine Model Summary Template

RECTRONAL C

Engine Family	1.Engine Code	2.Engine Model	3.8HP@RPM (SAEGross)	6.Foel Flank : minAstroke (2) peak HP (for diese i <u>on k)</u>	5.Fiel Rate: (10s/N) @ peak HP (10s/desets only)	6.Torque @ RPM (SEA Gross)	7.Fiel Rate: mm#tole@peak torgie	B.Fitel Rate; (bs/hi)@peaktorqite	9.8% is in Col Device Per SAE J	
AHZXL.722C90	N/A	1D90 S/Z/V/W	14,7@3000	41,5	6,9	25,9@3000	41.5	6,9	Mechanical	ſ
AHZXL.722C90	N/A	1090 S/Z/V/W	14,6 @2950	41,5	6,8	14,6@2950	41,5	6,9		•
AHZXL.722C90	N/A	1090 S/Z/V/W	14,5@2900	41,5	6,7	14,6@2900	41,5	6,7		
AHZXL.722C90	N/A	1090 S/Z/V/W	14,3@2850	41,5	6,6	14,8@2850	41,5	6,6		
AHZXL.722C90	N/A	1090 S/Z/V/W	14,2@2800	41,5	0,5	14,6@2800	41,5	6,5		
AHZXL.722C90	N/A	1090 S/Z/V/W	14,1@2750	41,5	6,4	14,6@2750	41,5	6,4		
AHZXL.722C90	N/A	1090 S/Z/V/W	13,9@2700	41,5	6,2	14,6@2700	41,5	6,2		
AHZXL.722C90	N/A	1090 S/Z/V/W	13.7@2850	41,5	6.1	14,6@2650	41,5	6,1		
AHZXL.722C90	N/A	1090 S/Z/V/W	13,5@2600	41,5	6.0	14,6@2600	41,5	6,0		
AHZXL.722C90	N/A	1090 S/Z/V/W	13,4@2550	41,5	5,9	14,6@2550	41,5	5,9		
AHZXL.722C90	N/A	1090 S/Z/V/W	13,1@2500	41,5	5,8	14,6@2500	41,5	5,8		
AHZXL.722C90	N/A	1090 S/Z/V/W	13,0@2450	41,5	5,7	14,6@2450	41,5	5,7		
AHZXL.722C90	N/A	1090 S/Z/V/W	12,7@2400	41,5	5,6	14,6@2400	41,5	5,6		
AHZXL.722C90	N/A	1090 S/Z/V/W	12,6@2350	41,5	5,4	14,6@2350	41,5	5,4		
AHZXL.722C90	N/A	1090 S/Z/V/W	12,3@2300	41,5	5,3	14,6@2300	41,5	5,3		
AHZXL.722C90	N/A	1090 S/Z/V/W	12,1@2250	41,5	5,2	14,6@2250	41,5	5,2		
AHZXL.722C90	N/A	1090 S/Z/V/W	11,9@2200	41,5	5,1	14,6@2200	41,5	5,1		
AHZXL.722C90	N/A	1090 S/Z/V/W	11,7@2150	41,5	5,0	14,6@2150	41,5	5,0		
AHZXL.722C90	N/A	1090 S/Z/V/W	11.4@2100	41,5	4,9	14,6@2100	41,5	4,9		
AHZXL.722C90	N/A	1090 S/Z/V/W	11,1@2050	41,5	4,7	14,6@2050	41,5	4,7		
AHZXL.722C90	N/A	1090 S/Z/V/W	10,9@2000	41,5	4,6	14,6@2000	41,5	4,6	T	