JOHN DEERE POWER SYSTEMS

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	L ENGINE FAMILY DISPLACEMENT (liters)		FUEL TYPE	USEFUL LIFE (hours)			
2011	BJDXL03.0113	2.4, 3.0	Diesel	8000			
SPECIAL	FEATURES & EMISSION		TYPICAL EQUIPMENT APPLICATION				
Direct Dies Electr	el Injection, Turbocharge onic Control Module, Sm	er, Charge Air Cooler, noke Puff Limiter	Loaders, Pump, Compressor, Generator Set, Other Industrial Equipment				

The engine models and codes are attached.

California Environmental Protection Agency

AIR RESOURCES BOARD

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr) C						PACITY (%)	
CLASS			нс	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
56 <u><</u> kW < 75	Tier 3	STD	N/A	N/A	4.7	5.0	0.40	20	15	50
		CERT			4.1	1.7	0.21	7	4	12

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

day of December 2010.

Annette Hebert, Chief Mobile Source Operations Division

11-10-2010

Page lof 1 E0#: U-R-004-0418

Engine Model Summary Form

Manufacturer:	John Deere Powe
Engine category:	Nonroad Cl
EPA Engine Family:	BJDXL03.0113
Mfr Family Name:	250HAA
Process Code:	New Submission

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (ibs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emiesion Control Device Per SAE J1930		
4024HF285A	4024H	80.47@2800	54.30@2800	34.18@2800	211.66@2000	69.3@2000	31.09@2000	EM EC SPL	\square DDI,	1C, CAC
5030HF285A	5030H	99.24@2800	50.70@2800	39.89@2800	251.48@2000	63.4@2000	35.63@2000	EM EC SPL		
5030HF285F	5030H	76.44@2400	45.10@2400	30.41@2400	203.54@1800	51.9@1800	26.28@1800	EM EC SPL		
5030HF285E	5030H	82.48@2400	47.80@2400	32.24@2400	225.67@1800	56,8@1800	28.75@1800	EM EC SPL		
5030HF285D	5030H	91.19@2400	52.30@2400	35.28@2400	251.48@1800	63.6@1800	32.21@1800	EM EC SPL		
5030HF285B	5030H	82.48@2800	45.20@2800	35.61@2800	209.44@2000	54.7@2000	30.76@2000	EM EC SPL] [
4024HF285C	4024H	80.47@2800	52.80@2800	33.25@2800	208.71@2000	65.9@2000	29.66@2000	EM EC SPL		
5030HF285G	5030H	96.56@1800	69.80@1800	35,32@1800				EM EC SPL] [
4024HF285B	4024H	80.47@1800	61,80@1800	29.33@1800				EM EC SPL] [
5030HF286	5030H	76.44@2800	41.30@2800	32.41@2800	189.53@2000	50.7@2000	28.44@2000	EM EC SPL		
5030HT012	5030H	91.19@2600	49.20@2600	35.96@2600	251.48@1950	64.2@1950	35.19@1950	EM EC SPL		,
5030HT011	5030H	83.15@2800	44.00@2800	34.62@2800	221.24@2000	59@2000	33.16@2000	EM EC SPL	LI V	
	· ·		1				· ·	100 C		
		<u></u>					100 C	1998 - 1998 - 1999 - 1998 - 1998 - 1998 - 1998 - 1998 - 1998 - 1998 - 1998 - 1998 - 1998 - 1998 - 1998 - 1998 -	4	
									4.	
		1							-	
I									-	
									-	
									4	
									-	
									-	
					_				-[·	
									-	
								,	-	
				,		• •		-1	-	