MOTORENFABRIK HATZ

EXECUTIVE ORDER U-R-034-0239 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2011	BHZXL.243C20	0.243	Diesel	3000			
	FEATURES & EMISSION (CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION				
	Mechanical Direct In	ection	Pump, Generator Set				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kw-hr)					OPACITY (%)		
POWER CLASS	STANDARD CATEGORY		НС	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
kW < 8	Tier 4 - Final	STD	N/A	NVA	7.5	8.0	0.60	N/A	N/A	N/A
		CERT	-	_	6.9	5.5	0.45			

BE IT FURTHER RESOLVED: That certification to the standards in 13 CCR 2423(b)(1)(A) -Table 1b listed above has been permitted pursuant to Endnote 2 of the same table.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Sections 2425 and 2426 (emission control system warranty).

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified pending submission of new emission control labels to comply with 13 CCR Section 2424 (emission control labels). The manufacturer has until May 16, 2011 to replace all existing MY2011 emission control labels to remove this conditional certification. Failure to resolve concerns by the specified date, shall be cause for the Executive Officer to rescind this conditional certification, in which case all engines covered under this conditional certification would be deemed uncertified and subject to civil penalties pursuant to Health and Safety Code Section 43154.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

_ day of February 2011.

Annette Hebert, Chief

Mobile Source Operations Division

Motorenfabrik Hatz Nonroad CI

Attachment page 1 of 2

E0#U-R-034-0239

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.8HP@RPM (SAEGross)	4.File (Parle) mm.stroke @ peak HP (for diese (on k)	5.F tel Rafe: (lbs/hr) @ peak HP (for diese is only)	6.Torque @ RPM (SEA Gross)	7.Fuel Bath: min.s troke@peak torque	8,Fitel Pate; (bs:An@peas brqite	9.8m ks los Control Device Per SAE J 1930	
BHZXL.243C20	N/A	1B20/1B20R	4,6@3600	11	2,2	6,7@ 360 0	11	2,2	Mechanical	DI
BHZXL.243C20	N/A	1B20/1B20R	4,6@3550	11	2,2	6, 8 @3550	11	2,2		
BHZXL.243C20	N/A	1820/1820R	4,6@3500	11	2,1	6,9 @ 3500	11	2,1	CONTROL BERTHAMAN AND AND AND AND AND AND AND AND AND A	
BHZXL.243C20	N/A	1B20/1B20R	4,6@3460	11	2,1	7,0@3 450	11	2,1		LALTTI AA NA TURKTUURI
BHZXL:243C20	N/A	1820/1820R	4,5@3400	11	2,1	6,9@3400	11	2,1		ERV JEV JE SKIR JEVERSKY E
BHZXL.243C20	N/A	1B20/1B20R	. 4,4@3350	11	2,1	7,0@3350	11	2,1		hat an area
BHZXL.243C20	N/A	1820/1820R	4,4@3300	11	2,0	7,1@3300	11	2,0		
BHZXL.243C20	N/A	1B20/1B20R	4,3@3250	11	2,0	7,2@3250	11	2,0		
BHZXL.243C20	N/A	1B20/1B20R	4,3@3200	11	2,0	7,1 @ 3200	11	2,0		
BHZXL.243C20	N/A	1820/1820R	4,3@3150	11	1,9	7,2@3150	11	1,9		
BHZXL.243C20	N/A	1B20/1B20R	4,3@3100	11	1,9	7,2@3100	11	1,9		
BHZXL:243C20	N/A	1B20/1B20R	4,2@3050	11	1,9	7,3@3050	11	1,9		
BHZXL.243C20	N/A	1820/1820R	4,2@3000	11,5	1,9	7,3@3000	11,5	1,9		
BHZXL.243C20	N/A	1820/1820R	4,1 @295 0	11,5	1,9	7,3@2950	11,5	1,9	Di Annopomorità de la Marine con contra dell'Annopomorità della colora	A CONTRACTOR OF THE ST
BHZXL,243C20	N/A	1B20/1B20R	4,0@2900	11,5	1,9	7,3@2900	11,5	1,9		1981 (23.2 ACT)
BHZXL.243C20	N/A	1820/1820R	3,9@2850	11,5	1,8	7,3@2850	11,5	1,8		MARTINE AND THE STREET A LABOR OF
BHZXL.243C20	N/A	1B20/1B20R	3,9@ 28 00	11,5	1,8	7,4@2800	11,5	1,8		THE VIOLENT CORNER OF
BHZXL.243C20	N/A	1B20/1B20R	3,9@ 2750	11,5	1,8	7,5@2750	11,5	1,8		
BHZXL.243C20	N/A	1820/1820R	3,9@2700	11,5	1,7	7,5@2700	11,5	1,7		
BHZXL.243C20	N/A	1B20/1B20R	3,8@26 50	11,5	1,7	7,6@2650	11,5	1,7		
BHZXL.243C20	N/A	19 20 /1920R	3,8@2600	11,5	1,7	7,6@2600	11,5	1,7		
BHZXL.243C20	N/A	1820/1 82 0R	3,8@2550	11,5 .	1,6	7,8@2550	11,5	1,6		
BHZXL.243C20	N/A	1820/1820R	3,7@2500	11,5	1,6	7,7@2500	11,5	1,8		
BHZXL.243C20	N/A	1820/1820R	3,6@2450	11,5	1,6	7,8@2450	11,5	1,8		
BHZXL.243C20	N/A	1B20/1B20R	3,6@2400	11,5	1,5	7,8@2400	11,5	1,5		4- 4-4
BHZXL.243C20	N/A	1 B20 /1B20R	3,5@2350	11,5	1,5	7,8@2350	11,5	1,5	V	

Motorenfabrik Hatz Nonroad CI

Attachment page 2 of 2

E0#U-R-034-0239 1/28/2011

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.6HP@RPM (SAEGross)	4.Fitel Parle: mm.&troke @ peak HP (for diesel only)	5.Fuel Rafe: (Ds:Ar) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.F vel Rafe: mm.s troke@peak torq ve	8.Fuel fiate; (lischn@peakforque	9.Bn ks be Coetrol Deulce Per SAE J 1930
BHZXL.243C20	N/A	1820/1820R	3,4@2300	11,5	1,5	7,8@2300	11,5	1,5	Mechanical DI
BHZXL.243C20	N/A	1820/1820R	3,3@2250	11,5	1,4	7,8@2250	11,5	1,4	
BHZXL.243C20	N/A	1820/1820R	3,2@2200	11,5	1,4	7,7@2200	11,5	1,4	11117
BHZXL.243C20	N/A	1820/1820R	3,1@2150	11,5	1,4	7,8@2150	11,5	1,4	
BHZXL.243C20	N/A	1820/1820R	2,9@2100	11,5	1,3	7,4@2100	11,5	1,3	
BHZXL.243C20	N/A	1820/1820R	2,8@2050	11,5	1,3	7,2@2050	11,5	1,3	
BHZXL.243C20	N/A	1820/1820R	2,8@2000	11,5	1,3	7,3@2000	11,5	1.3	