

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2011	BHZXL667C82	0.667	Diesel	3000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Mechanical Direct Injection			Pump, Generator Set, Other Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
8 ≤ kW < 19	Tier 4 - Final	STD	N/A	N/A	7.5	6.6	0.40	N/A	N/A	N/A
		CERT	--	--	7.2	3.0	0.26	--	--	--

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Sections 2425 and 2426 (emission control system warranty).

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified pending submission of new emission control labels to comply with 13 CCR Section 2424 (emission control labels). The manufacturer has until May 16, 2011 to replace all existing MY2011 emission control labels to remove this conditional certification. Failure to resolve concerns by the specified date, shall be cause for the Executive Officer to rescind this conditional certification, in which case all engines covered under this conditional certification would be deemed uncertified and subject to civil penalties pursuant to Health and Safety Code Section 43154.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 17th day of February 2011.

J. Lawrence
 Annette Hebert, Chief
 Mobile Source Operations Division

Motorenfabrik Hatz
Nonroad CI

Attachment

page 1 of 2

EO# U-R-034-0253

2/1/2011

[Return to Template](#)

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.HP@PPM (SAEGross)	4.Fuel Rate: mm.stroke @ peak HP (for diesel only)	5.Fuel Rate: (b3/10) @ peak HP (for diesel only)	6.Torque @ PPM (SAEGross)	7.Fuel Rate: mm.stroke @ peak torque	8.Fuel Rate: (b3/10) @ peak torque	9.Emission Cost Device Per SAE J
BHZXL667C82	N/A	1D81S/Z/T/U	13,8@3000	38,5	6,4	24,3@3000	38,5	6,4	Mechanical DI
BHZXL667C82	N/A	1D81S/Z/T/U	13,7@2950	38,5	6,3	24,4@2950	38,5	6,3	
BHZXL667C82	N/A	1D81S/Z/T/U	13,5@2900	38,5	6,2	24,6@2900	38,5	6,2	
BHZXL667C82	N/A	1D81S/Z/T/U	13,5@2850	38,5	6,1	25,0@2850	38,5	6,1	
BHZXL667C82	N/A	1D81S/Z/T/U	13,4@2800	38,5	6,0	25,2@2800	38,5	6,0	
BHZXL667C82	N/A	1D81S/Z/T/U	13,1@2750	38,5	5,9	25,2@2750	38,5	5,9	
BHZXL667C82	N/A	1D81S/Z/T/U	13,0@2700	38,5	5,8	25,4@2700	38,5	5,8	
BHZXL667C82	N/A	1D81S/Z/T/U	12,9@2650	38,5	5,7	25,6@2650	38,5	5,7	
BHZXL667C82	N/A	1D81S/Z/T/U	12,7@2600	38,5	5,6	25,8@2600	38,5	5,6	
BHZXL667C82	N/A	1D81S/Z/T/U	12,5@2550	38,5	5,5	25,8@2550	38,5	5,5	
BHZXL667C82	N/A	1D81S/Z/T/U	12,3@2500	38,5	5,4	26,0@2500	38,5	5,4	
BHZXL667C82	N/A	1D81S/Z/T/U	13,4@3000	37,5	6,3	23,6@3000	37,5	6,3	
BHZXL667C82	N/A	1D81S/Z/T/U	13,3@2950	37,5	6,2	23,7@2950	37,5	6,2	
BHZXL667C82	N/A	1D81S/Z/T/U	13,1@2900	37,5	6,1	23,9@2900	37,5	6,1	
BHZXL667C82	N/A	1D81S/Z/T/U	13,0@2850	37,5	6,0	24,1@2850	37,5	6,0	
BHZXL667C82	N/A	1D81S/Z/T/U	12,9@2800	37,5	5,9	24,2@2800	37,5	5,9	
BHZXL667C82	N/A	1D81S/Z/T/U	12,7@2750	37,5	5,7	24,4@2750	37,5	5,7	
BHZXL667C82	N/A	1D81S/Z/T/U	12,6@2700	37,5	5,6	24,6@2700	37,5	5,6	
BHZXL667C82	N/A	1D81S/Z/T/U	12,5@2650	37,5	5,5	24,8@2650	37,5	5,5	
BHZXL667C82	N/A	1D81S/Z/T/U	12,3@2600	37,0	5,4	25,0@2600	37,0	5,4	
BHZXL667C82	N/A	1D81S/Z/T/U	12,2@2550	37,0	5,3	25,2@2550	37,0	5,3	
BHZXL667C82	N/A	1D81S/Z/T/U	11,9@2500	37,0	5,2	25,2@2500	37,0	5,2	
BHZXL667C82	N/A	1D81S/Z/T/U	11,8@2450	37,0	5,1	25,4@2450	37,0	5,1	
BHZXL667C82	N/A	1D81S/Z/T/U	11,5@2400	37,0	5,0	25,3@2400	37,0	5,0	
BHZXL667C82	N/A	1D81S/Z/T/U	11,4@2350	37,0	4,8	25,6@2350	37,0	4,8	
BHZXL667C82	N/A	1D81S/Z/T/U	11,1@2300	37,0	4,7	25,5@2300	37,0	4,7	
BHZXL667C82	N/A	1D81S/Z/T/U	11,1@2250	37,0	4,6	26,1@2250	37,0	4,6	

Motorenfabrik Hatz
Nonroad CI

Attachment

EO# U-R-034-0253

page 2 of 2

2/1/2011

[Return to Template](#)

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm ³ /hr @ peak HP (for diesel only)	5.Fuel Rate: (lb./hr) @ peak HP (for diesel only)	6.Torque @ RPM (SAE Gross)	7.Fuel Rate: mm ³ /hr @ peak torque	8.Fuel Rate: (lb./hr) @ peak torque	9.Emissions Com Device Per SAE J
BHZXL667C82	N/A	1D81S/Z/T/U	10,9@2200	37,0	4,5	26,0@2200	37,0	4,5	Mechanical DI
BHZXL667C82	N/A	1D81S/Z/T/U	10,7@2150	37,0	4,4	26,3@2150	37,0	4,4	
BHZXL667C82	N/A	1D81C	12,7@3000	37,5	6,3	22,4@3000	37,5	6,3	
BHZXL667C82	N/A	1D81C	12,6@2950	37,5	6,2	22,5@2950	37,5	6,2	
BHZXL667C82	N/A	1D81C	12,5@2900	37,5	6,1	22,7@2900	37,5	6,1	
BHZXL667C82	N/A	1D81C	12,5@2850	37,5	6,0	23,1@2850	37,5	6,0	
BHZXL667C82	N/A	1D81C	12,2@2800	37,5	5,9	23,0@2800	37,5	5,9	
BHZXL667C82	N/A	1D81C	12,1@2750	37,5	5,7	23,1@2750	37,5	5,7	
BHZXL667C82	N/A	1D81C	11,8@2700	37,5	5,6	23,0@2700	37,5	5,6	
BHZXL667C82	N/A	1D81C	11,7@2650	37,5	5,5	23,2@2650	37,5	5,5	
BHZXL667C82	N/A	1D81C	11,7@2600	36,5	5,3	23,6@2600	36,5	5,3	
BHZXL667C82	N/A	1D81C	11,5@2550	36,5	5,2	23,8@2550	36,5	5,2	
BHZXL667C82	N/A	1D81C	11,4@2500	36,5	5,1	24,0@2500	36,5	5,1	
BHZXL667C82	N/A	1D81C	11,3@2450	35,5	4,8	24,2@2450	35,5	4,8	
BHZXL667C82	N/A	1D81C	11,0@2400	35,5	4,7	24,1@2400	35,5	4,7	
BHZXL667C82	N/A	1D81C	10,9@2350	35,5	4,7	24,4@2350	35,5	4,7	
BHZXL667C82	N/A	1D81C	10,7@2300	35,5	4,6	24,6@2300	35,5	4,6	

SUPERSEDED