

MOTORENFABRIK HATZ

EXECUTIVE ORDER U-R-034-0255 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY DISPLACEMENT (liters)		FUEL TYPE	USEFUL LIFE (hours)				
2011	BHZXL.667V83	0.667	Diesel 300					
	FEATURES & EMISSION (TYPICAL EQUIPMENT APPLICATION					
	Mechanical Direct In	jection	Pump, Compressor, Other Industria	al Equipment				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION			E	XHAUST (g/kw-ł	OPACITY (%)				
POWER CLASS	STANDARD CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
8 ≤ kW < 19	Tier 4 - Final	STD	N/A	N/A	7.5	6.6	0.40	N/A	N/A	N/A
		CERT			7.0	3.4	0.27			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Sections 2425 and 2426 (emission control system warranty).

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified pending submission of new emission control labels to comply with 13 CCR Section 2424 (emission control labels). The manufacturer has until May 16, 2011 to replace all existing MY2011 emission control labels to remove this conditional certification. Failure to resolve concerns by the specified date, shall be cause for the Executive Officer to rescind this conditional certification, in which case all engines covered under this conditional certification would be deemed uncertified and subject to civil penalties pursuant to Health and Safety Code Section 43154.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Mobile Source Operations Division

day of February 2011.

Motorenfabrik Hatz Nonroad CI

Attachment

page 1 of 2

E0#U-R-034-0255

2/1/2011

Return to Template

Engine Model Summary Template

			3.8HP@RPM	4.F se I P. ate : mm/s troke @ peak HP	5.F tel Rafe: (lbs/lif) @ peak HP	6.Torque @ RPM	7.Fiel Rate: mm.k trote@peak	8.Fiel Rate:	9.Baksios Cost	
Engine Family	1.Engine Code	2.Engine Model	(CAEGross)	(for diese i on i/)	(ibr diese is on ig	(SEA G ross)	poid se	(lbs/Ar)@peak torque		N :
BHZXL.667V83	N/A	1D81S/Z/T/U	13,8@3000	38,5	6,4	29,6@1800	40	4,0	Medicinical	DI
BHZXL.667V83	N/A	1D81S/Z/T/U	13,7@2950	38,5	6,3	29,6@1800	40	4,0		
BHZXL.667V83	N/A	1D81S/Z/T/U	13,5@2900	38,5	6,2	29,6@1800	40	4,0		
8HZXL.667V83	N/A	1D81S/Z/T/U	13,5@2850	38,5	6,1	29,6@1800	40	4.0		
8HZXL.667V83	N/A	1D81S/Z/T/U	13,4@2800	38,5	6,0	28,9@1800	39	3 ,9		
BHZXL.667V83	N/A	1D81S/Z/T/U	13,1@2750	38,5	5,9	28 ,9@ 1800	39	3,9		
BHZXL.667V83	N/A	1D81S/Z/T/U	13,0@2700	38,5	5 ,8	28,9@ 180 0	39	3,9		
BHZXL.867V83	N/A	1D81S/Z/T/U	12,9@2650	38,5	5,7	28,9@1800	39	3,9		
BHZXL.867V83	N/A	1D81S/Z/T/U	12,7@2600	38,5	5,6	28,1@1800	38,5	3,9		
BHZXL.667V83	N/A	1D81S/Z/T/U	12,5@2550	38,5	5,5	28,1@1800	38,5	3,9		
BHZXL.667V83	N/A	1D81S/Z/T/U	12,3@2500	38,5	5,4	28,1@1800	38,5	3,9		
BHZXL.667V83	N/A	1D81S/Z/T/U	13,4@3000	37,5	6,3	28,1@1800	38	3,8		
BHZXL,667V83	N/A	1D81S/Z/T/U	13,3@2950	37,5	6,2	28,1@1800	38	3,8		
BHZXL.667V83	N/A	1D81S/Z/T/U	13,1@2900	37,5	6,1	28,1@1800	38	3,8		
BHZXL.667V83	N/A	1D81S/Z/T/U	13,0@2850	37,5	6,0	28,1@1800	38	3,8		
8HZXL.667V83	N/A	1D81S/Z/T/U	12,9@2800	37,5	5,9	28,1@1800	38	3,8		
BHZXL.667V83	N/A	1D81S/Z/T/U	12,7@2750	37,5	5,7	28,1@1800	38	3,8		
BHZXL.667V83	N/A	1D81S/Z/T/U	12, 6@ 2700	37,5	5,6	28,1@1800	38	3,8	constit for the contract delayer to the second of	
BHZXL.667V83	N/A	1D81 S/ Z/T/U	12,5@2650	37,5	5,5	28,1@1800	38	3,8	a da a meso de seco	
BHZXL.667V83	N/A	1D81S/Z/T/U	12,3@2600	37	5,4	27,4@1800	37	3,7		
BHZXL.667V83	N/A	1D81S/Z/T/U	12,2@2550	37	5,3	27,4@1800	37	3,7		
BHZXL.667V83	N/A	1D81S/Z/T/U	11,9@2500	37	5,2	27,4@1800	37	3,7		
BHZXL.667V83	N/A	1D81\$/Z/T/U	11,8@2450	37	5,1	27,4@1800	37	3,7	A	
BHZXL,667V83	N/A	1D81S/Z/T/U	11,5@2400	37	5,0	26,6@1800	37	3,7		
8HZXL.667V83	N/A	1D81S/Z/T/U	11,4@2350	37	4,8	26,6@1800	37	3,7		
BHZXL.667V83	N/A	1D81 S/Z/ T/U	11,1@2300	37	4,7	26,6@1800	37	3,7		
BHZXL.667V83	N/A	1081C	12,7@3000	37,5	6,3	27,4@1800	38	3,8	V	

Motorenfabrik Hatz Nonroad CI Attachment

page 2 of 2

E0# U-R-034-0255

2/1/2011

	4.55	Acres consider	1 67.0	No. of Persons	1-80 4
	P 10	Sec. 3.4	1		late
IKA	TRIT	mac	in R		แสเด
10.350		10000	3.8		

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.8HP@RPM (SAEGross)	4.Fuel Parte: mm.\$troke @ peak HP (for dieselosik)	5.Fuel Rafe: (bs/hr) @ peak HP (for diesels only)	6.Torque @ BPM (SEA Gross)	7.Fiel Rate: mm.stroke@peak forgie	8.Fitel Rafe: (bs://n/@peak forque	9.6m k4 lon Cont Device Per SAE J
BHZXL.667V83	N/A	1D81C	12,6@2950	37,5	6,2	27,4@1800	38	3,8	Mechanical DI
BHZXL,667V83	N/A	1D81C	12,5@2900	37,5	6,1	27,4@1800	38	3,8	
BHZXL.667V83	N/A	1D81C	12,5@2850	37,5	6,0	27,4@1800	38	3,8	
BHZXL.667V83	N/A	1D81C	12,2@2800	37,5	, 5,9	27,4@1800	38	3,8	
BHZXL.667V83	N/A	1D81C	12,1@2750	37,5	5,7	27,4@1800	38	3,8	
BHZXL.667V83	N/A	1D81C	11,8@2700	37,5	5,8	27, 4@ 1800	38	3,8	
BHZXL.667V83	N/A	1D81C	11,7@2650	37,5	5 ,5	27,4@1800	38	3,8	
BHZXL.667V83	N/A	1D81C	11,7@2600	36,5	5,3	26,6@1800	37	3,7	
BHZXL.667V83	N/A	1D81C	11,5@2550	36,5	5,2	28,6@1800	37	3,7	
9HZXL.667V83	N/A	1D81C	11,4@2500	36,5	5,1	26,6@1800	37	3,7	412
BHZXL.667V83	N/A	1D81C	11,3@2450	35,5	4,8	25,2@1800	35	3,5	
BHZXL.667V83	N/A	1D81C	11,0@2400	35,5	4,7	25,2@1800	35	3,5	and the control of th
BHZXL.667V83	N/A	1D81C	10,9@2350	35,5	4,7	25,2@1800	35	3,5	
BHZXL.667V83	N/A	1D81C	10,7@2300	35,5	4,6	25,2@1800	35	3,5	V