

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2011	BHZXL997V40	0.997	Diesel	3000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Mechanical Direct Injection			Pump, Generator Set, Other Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NO_x), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NO_x), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NO _x	NMHC+NO _x	CO	PM	ACCEL	LUG	PEAK
8 ≤ kW < 19	Tier 4 - Final	STD	N/A	N/A	7.5	6.6	0.40	20	15	50
		CERT	—	—	7.1	3.4	0.23	15	9	28

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Sections 2425 and 2426 (emission control system warranty).

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified pending submission of new emission control labels to comply with 13 CCR Section 2424 (emission control labels). The manufacturer has until May 16, 2011 to replace all existing MY2011 emission control labels to remove this conditional certification. Failure to resolve concerns by the specified date, shall be cause for the Executive Officer to rescind this conditional certification, in which case all engines covered under this conditional certification would be deemed uncertified and subject to civil penalties pursuant to Health and Safety Code Section 43154.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 17th day of February 2011.

Annette Hebert
 Annette Hebert, Chief
 Mobile Source Operations Division

Motorenfabrik Hatz
 Nonroad CI

Attachment

page 1 of 2

EU# U-R-034-0259

2/2/2011

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.HP@RPM (SAE Gross)	4.Fuel Rate: mm ³ /stroke @ peak HP (br diesel only)	5.Fuel Rate: (br-A) @ peak HP (br diesel only)	6.Torque @ RPM (SAE Gross)	7.Fuel Rate: mm ³ /stroke @ peak torque	8.Fuel Rate: (br-A) @ peak torque	9.Emissions Control Device Per SAE J1930
BHZXL997V40	N/A	2G40 / 2G40H	21,7@3000	28	4,3	43,3@2000	29	3,2	Mechanical DI
BHZXL997V40	N/A	2G40 / 2G40H	21,4@2950	28	4,3	42,9@2000	28,5	3,2	
BHZXL997V40	N/A	2G40 / 2G40H	21,2@2900	28	4,2	42,9@2000	28,5	3,2	
BHZXL997V40	N/A	2G40 / 2G40H	20,9@2850	28	4,1	42,6@2000	28	3,1	
BHZXL997V40	N/A	2G40 / 2G40H	20,8@2800	28	4,1	42,6@2000	28	3,1	
BHZXL997V40	N/A	2G40 / 2G40H	20,4@2750	28	4,0	42,2@2000	27,5	3,1	
BHZXL997V40	N/A	2G40 / 2G40H	20,1@2700	28	3,9	42,2@2000	27,5	3,1	
BHZXL997V40	N/A	2G40 / 2G40H	19,8@2650	28	3,8	41,4@2000	27	3,0	
BHZXL997V40	N/A	2G40 / 2G40H	19,8@2600	28	3,8	41,4@2000	27	3,0	
BHZXL997V40	N/A	2G40 / 2G40H	20,8@3000	25	4,2	42,6@2000	28	3,1	
BHZXL997V40	N/A	2G40 / 2G40H	20,5@2950	25	4,1	42,2@2000	27,5	3,1	
BHZXL997V40	N/A	2G40 / 2G40H	20,2@2900	25	4,0	42,2@2000	27,5	3,1	
BHZXL997V40	N/A	2G40 / 2G40H	20,0@2850	25	4,0	41,4@2000	27	3,0	
BHZXL997V40	N/A	2G40 / 2G40H	19,7@2800	25	3,9	41,4@2000	27	3,0	
BHZXL997V40	N/A	2G40 / 2G40H	19,4@2750	25	3,8	41,1@2000	26,5	3,0	
BHZXL997V40	N/A	2G40 / 2G40H	19,2@2700	25	3,8	41,1@2000	26,5	3,0	
BHZXL997V40	N/A	2G40 / 2G40H	18,9@2650	25	3,7	40,7@2000	26	2,9	
BHZXL997V40	N/A	2G40 / 2G40H	18,8@2600	25	3,6	40,7@2000	26	2,9	
BHZXL997V40	N/A	2G40 / 2G40H	19,7@3000	24	4,0	41,1@2000	26,5	3,0	
BHZXL997V40	N/A	2G40 / 2G40H	19,6@2950	24	3,9	41,1@2000	26,5	3,0	
BHZXL997V40	N/A	2G40 / 2G40H	19,3@2900	24	3,9	40,7@2000	26	2,9	
BHZXL997V40	N/A	2G40 / 2G40H	19,0@2850	24	3,8	40,7@2000	26	2,9	
BHZXL997V40	N/A	2G40 / 2G40H	18,9@2800	24	3,7	40,7@2000	26	2,9	
BHZXL997V40	N/A	2G40 / 2G40H	18,8@2750	24	3,7	40,0@2000	25,5	2,8	
BHZXL997V40	N/A	2G40 / 2G40H	18,5@2700	24	3,6	40,0@2000	25,5	2,8	
BHZXL997V40	N/A	2G40 / 2G40H	18,2@2650	24	3,5	39,2@2000	25	2,8	

Motorenfabrik Hatz

Nonroad CI

Attachment

page 2 of 2

EO# 0-R-034-0259

2/2/2011

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm. ³ /stroke @ peak HP (for diesel only)	5.Fuel Rate: (lb./hr) @ peak HP (for diesel only)	6.Torque @ RPM (SAE Gross)	7.Fuel Rate: mm. ³ /stroke @ peak torque	8.Fuel Rate: (lb./hr) @ peak torque	9.Emissions Control Device Per SAE J1930
BHZXL997V40	N/A	2G40 / 2G40H	18,0@2600	24	3,5	39,2@2000	25	2,8	Mechanical DI
BHZXL997V40	N/A	2G40 / 2G40H	17,7@2550	24	3,4	39,2@2000	25	2,8	
BHZXL997V40	N/A	2G40 / 2G40H	17,4@2500	24	3,3	38,5@2000	24,5	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	17,0@2450	24	3,3	38,5@2000	24,5	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	16,8@2400	24	3,2	38,5@2000	24,5	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	16,5@2350	24	3,1	37,7@2000	24	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	16,1@2300	24	3,1	37,7@2000	24	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	15,7@2250	24	3,0	37,0@2000	24	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	15,4@2200	24	2,9	37,0@2000	24	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	15,1@2150	24	2,9	37,0@2000	24	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	14,7@2100	24	2,8	37,0@2000	24	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	14,4@2050	24	2,7	37,0@2000	24	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	14,1@2000	24	2,7	37,0@2000	24	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	18,4@3000	22	3,7	37,7@2000	24	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	18,2@2950	22	3,6	37,7@2000	24	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	18,1@2900	22	3,6	37,7@2000	24	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	17,9@2850	22	3,5	37,7@2000	24	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	17,7@2800	22	3,4	37,7@2000	24	2,7	
BHZXL997V40	N/A	2G40 / 2G40H	17,6@2750	22	3,4	37,0@2000	23,5	2,6	
BHZXL997V40	N/A	2G40 / 2G40H	17,3@2700	22	3,3	37,0@2000	23,5	2,6	
BHZXL997V40	N/A	2G40 / 2G40H	17,1@2650	22	3,2	36,3@2000	23	2,6	
BHZXL997V40	N/A	2G40 / 2G40H	16,9@2600	22	3,2	36,3@2000	23	2,6	
BHZXL997V40	N/A	2G40 / 2G40H	16,7@2550	22	3,1	35,5@2000	22,5	2,5	
BHZXL997V40	N/A	2G40 / 2G40H	16,5@2500	22	3,1	35,5@2000	22,5	2,5	