California Environmental Protection Agency

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMILY DISPLACEMENT (liters)		FUEL TYPE	USEFUL LIFE (hours)				
2011	BHZXL1.38SV2	1.038, 1.384	Diesel	3000				
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION					
	Mechanical Direct Ir	ijection	Pump, Compressor, Other Indu	istrial Equipment				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
CLASS			HC	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
8 ≤ kW < 19	Tier 4 - Final	STD	N/A	N/A	7.5	6.6	0.40	20	15	50
		CERT		·	7.3	4.6	0.28	4	3	5

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Sections 2425 and 2426 (emission control system warranty).

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified pending submission of new emission control labels to comply with 13 CCR Section 2424 (emission control labels). The manufacturer has until May 16, 2011 to replace all existing MY2011 emission control labels to remove this conditional certification. Failure to resolve concerns by the specified date, shall be cause for the Executive Officer to rescind this conditional certified and subject to civil penalties pursuant to Health and Safety Code Section 43154.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

day of February 2011.

nnette Hebert, Chief Mobile Source Operations Division

Attadiment

E0#U-R-034-0264

Nonroad CI

Motorenfabrik Hatz

-o-f 2 page

2/4/2011

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.8HP@RPM (SAEGIOSS)	4.Fitel Rate: mm.stroke @ peak HP (tor clese tor to	5.F tel Pate: (bs/it) @ peak HP (br diesels only)	6.Torq ae @ P.P.M (SEA Gross)	7.Fuel Pate: mm&troke@peak torque	8.F tel Rate: (Ix:Ai)@peak torqu	9.En issios Costrol e Device Per SAE J 1930	
BHZXL1.38SV2	N/A	31/35	22,3@3000	19,0	3,0	44@1800	20,0	1,8	Mechanical	DI
BHZXL1.38SV2	N/A	3W35	22,0@2950	19,0	3,0	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	21,9@2900	19,0	2,9	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	21,7@2850	19,0	2,9	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	31/35	21,5@2800	19,0	2,8	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	21,2@2750	19,0	2,8	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	21,1@2700	19,0	2,7	44@1800	20 ,0	1,9		
BHZXL1.38SV2	N/A	3W35	20,8@2650	19,0	2,7	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	20,5@2600	19,0	2,6	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	20,2@2550	19,0	2,8	44@1800	20,0	1,9		
9HZXL1.38SV2	√ N/A	31//35	19,8@2500	19,0	2,5	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	19,6@2450	19 .0	2,5	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	19,2@2400	19,0	2,4	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	18,9@2350	19,0	2.4	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	. 3₩35	18,5@2300	19,0	2,3	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	18,1@2250	19,0	2,3	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	17,7@2200	19,0	2,2	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	17,4@2150	19,0	2,2	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	17,0@2100	19,0	2,1	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	16,5@2050	1 9 ,0	2,1	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	31135	16,2@2000	19,0	2,0	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	31/35	15,8@1950	19,0	2,0	44@1800	20,0	1,9		
BHZXL1.38SV2	. N/A	3W35	15,4@1900	19,0	1,9	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	3W35	15,0@1850	19,0	1,9	44@1800	20,0	1,9		
BHZXL1.38SV2	N/A	31/35	14,6@1800	19,0	1,8	44@1800	20,0	1,9	1	
BHZXL1.38SV2	N/A	3\035	20,2@3000	17,0	2,7	38@1800	18,0	1,7	V	

Motorenfabrik Hatz Nonroad CI

Attachment

E0#U-R-034-0264

page 2 of 2

2/4/2011

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.8HP@RPM (SAEGIOSS)	4.Ftel Parle: mm.stroke @peak HP (for diese tosk)	5.Fitel Pate; (Ds/Ar) @ peak HP (Dr dissels only)	6.Torq te @ RPM (SEA Gross)	7.F vel Rate: mm.& troke@peak torq ve	8.Fiel Rate: (Ds/in)@peak torqu	9.En Issio: Costrol Device Per SAE J 1930	
BHZXL1.38SV2	N/A	3W35	20,0@2950	17,0	2,7	38@1800	18,0	1,7	Mechanical	DI
BHZXL1.38SV2	N/A	3W35	19,8@2900	17,0	2,6	38@1800	18,0	1,7		
BHZXL1.38SV2	N/A	3W35	19,7@2850	17,0	2,6	38@1800	18,0	1,7		
BHZXL1.38SV2	N/A	3W35	19,4@2800	17,0	2,5	38@1800	18,0	1,7		
BHZXL1.38SV2	N/A	3W35	19,3@2750	17,0	2,5	38@1800	18,0	1,7		
BHZXL1.38SV2	N/A	31/35	19,0@2700	17,0	2,4	38@1 80 0	18,0	1,7		
BHZXL1.38SV2	N/A	3W35	18,9@2650	17,0	2.4	38@1800	18,0	1,7		
BHZXL1.38SV2	N/A	3W35	18,6@2600	17,0	2,4	38@1800	18,0	1,7		
BHZXL1.38SV2	N/A	3W35	18,4@2550	17,0	2,3	38@1800	18,0	1,7		
BHZXL1.38SV2	N/A	3W35	18,1@2500	17,0	2.3	38@1800	18,0	1,7		
BHZXL1.38SV2	N/A	4W35	25,2@2350	19,0	3,2	80@1800	20,0	2,6		
BHZXL1.38SV2	N/A	4W35	24,8@2300	19,0	3,1	60@1800	20,0	2,6		
BHZXL1.38SV2	N/A	4W35	24,3@2250	19,0	3,0	80@1800	20,0	2,6		
BHZXL1.38SV2	N/A	4W35	23,9@2200	19,0	3,0	80@1800	20,0	2,8		
BHZXL1.38SV2	N/A	4W35	23,3@2150	19,0	2,9	60@1800	20,0	2,8		
BHZXL1.38SV2	N/A	4W35	22,8@2100	19,0	2,8	60@1800	20,0	2,8		
BHZXL1.38SV2	N/A	4\035	22,3@2050	. 19,0	2,8	60@1800	20,0	2,8		
BHZXL1.38SV2	N/A	4W35	21,7@2000	19,0	2,7	60@1800	20,0	2,8		
BHZXL1.38SV2	N/A	41/35	21,2@1950	19,0	2,6	57@1800	19,0	2,4		
BHZXL1.38SV2	N/A	41/35	20,7@1900	19,0	2,6	57@1800	19,0	2.4		
BHZXL1.38SV2	N/A	41/35	20,1@1850	19,0	2,5	57@1800	19,0	2,4		
BHZXL1.38SV2	N/A	41/35	19, 6@ 1800	. 19,0	2,4	57@1800	19,0	2,4		
BHZXL1.38SV2	N/A	41/35	25,3@2650	17,0	3,2	53@1800	18,0	2,3		
BHZXL1.38SV2	N/A	41135	24,9@2600	17,0	3,1	53@1800	18,0	2,3		
BHZXL1.38SV2	N/A	41/35	24,5@2550	17,0	3,1	53@1800	18,0	2,3		
BHZXL1.38SV2	N/A	4\v35	24,1@2500	17,0	3,0	53@1800	18,0	2,3	. V	