

KUBOTA Corporation

EXECUTIVE ORDER U-R-025-0534 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2012	CKBXL01.5BAD	1.123, 1.498	Diesel	5000
	FEATURES & EMISSION		TYPICAL EQUIPMENT	
in	direct Diesel Injection, T Smoke Puff Limiter (Sor	urbocharger, ne Models)	Tractor, Compressor, Ge Other Industrial Ed	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

POWER CLASS	EMISSION		EXHAUST (g/kw-hr)					OPACITY (%)		
	STANDARD CATEGORY		нс	NOx	NMHC+NOx	co	P M	ACCEL	LUG	PEAK
19 <u><</u> kW < 37	Interim Tier 4	STD	N/A	N/A	7.5	5.5	0.30	20	15	50
		CERT			5.3	0.7	0.13	7	1	20

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

_ day of December 2011.

Annette Hebert, Chief

Mobile Source Operations Division

Engine Model Summary Form

Manufacturer:

KUBOTA Corporation

Engine category:

Nonroad Cl

EPA Engine Family: CKBXL01.5BAD

Mfr Family Name: N/A

Process Code:

New Submission

Attachment page 1 of 1

E0#U-R-025-0534

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1	ol 930
D1105-T-ET01	D1105-T-ET	32.9@3000	28.2	14.2	65.0@2000	31.0	10.4	EM :	LIE,
D1105-T-ET01b	D1105-T-ET	32.9@3000	28.2	14.2	65.0@2000	31.0	10.4	EM,SPL	
D1105-T-ET02	D1105-T-ET	31.0@2850	27.6	13.2	63.5@2000	30.3	10.2	EM	
D1105-T-ET02b	D1105-T-ET	31.0@2850	27.6	13.2	63.5@2000	30.3	10.2	EM,SPL	
V1505-T-ET01	V1505-T-ET	44.3@3000	28.3	19.0	90.9@2000	31.5	14.1	EM	
V1505-T-ET01b	V1505-T-ET	44.3@3000	28.3	19.0	90.9@2000	31.5	14.1	EM,SPL	
V1505-T-ET02	V1505-T-ET	42.0@2850	28.0	17.8	90.5@2000	31.4	14.0	EM	1
V1505-T-ET02b	V1505-T-ET	42.0@2850	28.0	17.8	90.5@2000	31.4	14.0	EM,SPL	7
V1505-T-ET03	V1505-T-ET	44.3@3000	28.3	19.0	87.5@2000	30.0	13.4	EM	71
V1505-T-ET03b	V1505-T-ET	44.3@3000	28.3	19.0	87.5@2000	30.0	13.4	EM,SPL	T
V1505-T-ET04	V1505-T-ET	38.4@2400	28.9	15.5	90.9@2000	30.3	13.5	EM	T
V1505-T-ET04b	V1505-T-ET	38.4@2400	28.9	15.5	90.9@2000	30.3	13.5	EM,SPL	T
V1505-T-ET05	V1505-T-ET	44.3@3000	28.3	19.0	78.3@2000	26.9	12.0	EM	П
V1505-T-ET05b	V1505-T-ET	44.3@3000	28.3	19.0	78.3@2000	26.9	12.0	EM,SPL	
V1505-T-ET06	V1505-T-ET	41.0@2800	27.8	17.4	87.5@2000	30.0	13.4	EM	
V1505-T-ET06b	V1505-T-ET	41.0@2800	27.8	17.4	87.5@2000	30.0	13.4	EM,SPL	П
V1505-T-ET07	V1505-T-ET	36.3@2500	27.2	15.2	80.0@1900	27.5	11.7	EM	V
			1						
									_