EXECUTIVE ORDER U-R-025-0543 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR ENGINE FAMILY		DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2012	CKBXL02.4ECD	1.826, 2.434	Diesel	5000		
12 11	FEATURES & EMISSION		TYPICAL EQUIPMENT APPLICATION			
	Mechanical Direct In	jection	Wheel Loader, Skid Steer Loader			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)				OPACITY (%)			
			NMHC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
19 ≤ kW < 37	Interim Tier 4	STD	N/A	N/A	7.5	5.5	0.30	20	15	50
		CERT		-	6.2	2.0	0.23	1	1	1

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

277 day of December 2011.

M. Lucardos FOR AGM

Annette Hebert, Chief Mobile Source Operations Division

Engine Model Summary Form

Manufacturer:

KUBOTA Corporation

Engine category:

Nonroad Cl

EPA Engine Family: CKBXL02.4ECD

Mfr Family Name: N/A

Process Code:

Running Change

Artachment
page 1 of

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930	
4IRX3N	4IRX3N	48.9@2600	33.1	19.2	117.0@1600	36.0	12.9	EM, Mechanica	11
C1.8-DI-ET02	C1.8-DI-ET	30.6@2200	33.1	12.2	83.8@1400	35.8	8.4	EM .	,
C1.8-DI-ET05	C1.8-DI-ET	33.3@2400	33.8	13.6	83.8@1400	35.7	8.4	EM	
C2.4-DI-ET03	C2.4-DI-ET	41.8@2200	32.3	15.9	115.0@1400	36.0	11.3	EM	
C2.4-DI-ET06	C2.4-DI-ET	45.7@2400	34.1	18.3	115.0@1400	35.9	11.2	EM	
D1803-M-DI-ET01	D1803-M-DI-ET	37.4@2700	33.4	15.1	85.3@1600	35.4	9.5	EM	
D1803-M-DI-ET02	D1803-M-DI-ET	30.6@2200	331	12.2	83.8@1400	35.8	8.4	EM	
D1803-M-DI-ET03	D1803-M-DI-ET	36.1@2600	32.9	14.3	85.3@1600	35.4	9.5	EM	
D1803-M-DI-ET04	D1803-M-DI-ET	34.7@2500	32.6	13.7	85.3@1600	35.5	9.5	EM.	
D1803-M-DI-ET05	D1803-M-DI-ET	33.3@2400	33.8	13.6	83.8@1400	35.7	8.4	EM .	
D1803-M-DI-ET06	D1803-M-DI-ET	31.9@2300	32.7	12.6	83.8@1400	35.9	8.4	EM	
V2403-M-DI-ET01	V2403-M-DI-ET	48.9@2700	32.3	19.5	121.7@1500	38.0	12.7	EM	
V2403-M-DI-ET02	V2403-M-DI-ET	48.9@2700	32.3	19.5	117.0@1600	36.0	12.9	EM	
V2403-M-DI-ET03	V2403-M-DI-ET	41.8@2200	32.3	15.9	115.0@1400	36.0	11.3	EM	
V2403-M-DI-ET04	V2403-M-DI-ET	48.9@ 2600	33.1	19.2	117.0@1600	36.0	12.9	EM	
V2403-M-DI-ET05	V2403-M-DI-ET	47.6@2500	33.2	18.6	117.0@1600	36.4	13.0	EM	
V2403-M-DI-ET06	V2403-M-DI-ET	45.7@2400	34.1	18.3	115.0@1400	35.9	11.2	EM /	
V2403-M-DI-ET07	V2403-M-DI-ET	43.9@2300	33.5	17.2	115.0@1400	36.0	11.3	EM V	