

KUBOTA Corporation

EXECUTIVE ORDER U-R-025-0567 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2013	DKBXL.898KCB	0.599, 0.899	Diesel	3000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
	Indirect Diesel Inje	ection	Loader, Tractor, Generator Set, Other In	ndustrial Equipment		

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kw-hr)				OPACITY (%)			
POWER	STANDARD CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
0 ≤ kW < 19	Tier 4 Final	OPTIONAL STD	N/A	N/A	7.5	6.6	0.40	20	15	50
		CERT			5.6	2.0	0.31	8	6	13

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has complied with the more stringent set of standards from the various power categories in conformance with Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for 2008 and Later Tier 4 Off-Road Compression-Ignition Engines, Part I-C" adopted October 20, 2005.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

BE IT FURTHER RESOLVED: The listed engine family is conditionally certified pending submission of additional test data to verify compliance with useful-life emission standards. The manufacturer has until August 31, 2012 to provide test data to confirm or correct the certification emissions levels on this conditional certification. Failure to resolve concerns by the specified date, shall be cause for the Executive Officer to rescind this conditional certification, in which case all engines covered under this conditional certification would be deemed uncertified pursuant to Health and Safety Code Section 43153 and subject to civil penalties pursuant to Health and Safety Code Section 43154.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

__ day of July 2012.

Annette Hebert, Chief

Mobile Source Operations Division

Engine Model Summary Form

Manufacturer:

KUBOTA Corporation

Engine category:

Nonroad Cl

EPA Engine Family: DKBXL.898KCB

Mfr Family Name: N/A

Process Code:

New Submission

Attachment
page (of)

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque (8.Fuel Rate: lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
D902-EF01	D902-EF	24.8@3600	18.4	11.1	41.4@2600	19.5	8.5	EM IDF
D902-EF02	D902-EF	23.3@3400	18.6	10.6	40.6@2400	19.6	7.9	EM ,
D902-EF03	D902-EF	21.6@3200	17.5	9.4	41.4@2400	19.7	7.9	EM
D902-EF04	D902-EF	20.8@3000	18.0	9.1	41.1@2000	19.6	6.6	EM]
D902-EF05	D902-EF	20.2@3000	17.5	8.8	40.9@2000	19.4	6.5	EM
D902-EF06	D902-EF	18.0@2600	17.3	7.5	40.1@2200	18.8	6.9	EM
D902-EF07	D902-EF	16.2@2400	16.9	6.8	40.3@1900	19.1	6.1	EM
D902-EF08	D902-EF	16.1@2300	17.4	6.7	38.4@1800	18.0	5.4	EM
Z602-EF01	Z602-EF	16.9@3600	19.0	7.6	28.4@2200	20.2	5.0	EM
Z602-EF02	Z602-EF	16.8@3600	18.9	7.6	27.9@2600	20.0	5.8	EM
Z602-EF03	Z602-EF	14.5@3200	18.0	6.4	28.0@2400	20.1	5.4	EM
Z602-EF04	Z602-EF	12.7@2800	17.8	5.6	26.6@2300	19.0	4.9	EM
Z602-EF05	Z602-EF	11.7@2600	17.4	5.1	26.8@2100	19.4	4.6	EM
Z602-EF06	Z602-EF	10.7@2400	17.3	4.6	25.7@1900	17.9	3.8	EM
Z602-EF07	Z602-EF	9.9@2200	17.4	4.3	25.6@1800	19.1	3.8	EM V