Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2014	EFPXL03.4ADD	3.4	Diesel	8000			
	FEATURES & EMISSION		TYPICAL EQUIPMENT APPLICATION				
Coole	ic Direct Injection, Turbo r, Electronic Control Mod ation, Diesel Oxidation Ca Trap Oxidizer	ule, Exhaust Gas atalyst, and Periodic	Loader, Tractor, Dozer, and Other Industrial Equipment				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

POWER CLASS	EMISSION STANDARD		OPACITY (%)							
	CATEGORY		NMHC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
56 ≤ kW < 130	Interim Tier 4 /ALT NOx	STD	0.19	3.4	N/A	5.0	0.02	N/A	N/A	N/A
		CERT	0.01	3.1		0.1	0.02			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has complied with the more stringent set of standards from the various power categories in conformance with Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for 2008 and Later Tier 4 Off-Road Compression-Ignition Engines, Part I-C" adopted October 20, 2005.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

__ day of August 2013.

FOR Erik White, Chief

Mobile Source Operations Division

Engine Model Summary Template

U-12-015-0259 Attachment pg 1/2 7/18/2013

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
EFPXL03.4ADD	F5HFL413B*A	F5HFL413B*A	110 @ 2200	84.7	N/A	339 @ 140 0	102.3	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413C*A	F5DFL413C*A	87 @ 2300	66.0	N/A	300 @ 1500	90.5	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413B*A	F5DFL413B*A	96 @ 2300	73.1	N/A	327 @ 1500	98.7	· N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413A*A	F5DFL413A*A	103 @ 2300	78.1	N/A	337 @ 1500	101.6	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL413D*A	F5HFL413D*A	84 @ 2200	65.1	N/A	305 @ 150 0	82.4	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL413C*A	F5HFL413C*A	96 @ 2200	74.1	N/A	334 @ 1400	100.7	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL413G*A	F5HFL413G*A	82 @ 2000	66.9	N/A	26 5 @ 1400	79.3	N/A	DDI, ECM, TC, CAC, EGR, OC PTOX
EFPXL03.4ADD	F5HFL413F*A	F5HFL413F*A	90 @ 2000	73.8	N/A	295 @ 1400	88.1	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL414D*A	F5HFL414D*A	111 @ 2200	85.8	N/A	332 @ 1400	100.1	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL414C*A	F5HFL414C*A	100 @ 2200	77.2	N/A	309 @ 1400	93.4	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL414A*A	F5HFL414A*A	94 @ 2200	72.0	N/A	291 @ 1400	87.0	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL414F*A	F5HFL414F*A	88 @ 2200	67.9	N/A	273 @ 1400	81.5	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL414B*A	F5HFL414B*A	84 @ 2200	64.8	N/A	261 @ 1400	78.0	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL414G*A	F5HFL414G*A	115 @ 2500	82.7	N/A	309 @ 1600	93.8	· N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL414E*A	F5HFL414E*A	100 @ 2500	72.1	N/A	287 @ 1600	86.7	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL414H*A	F5HFL414H*A	89 @ 2500	64.3	N/A	253 @ 1600	76.1	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL413E*A	F5HFL413E*A	90 @ 2500	65.7	N/A	282 @ 1400	84.7	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL413A*A	F5HFL413A*A	114 @ 2500	81.7	N/A	339 @ 1400	102.3	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413D*A	F5DFL413D*A	76 @ 2300	58.9	N/A	259 @ 1500	77.7	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413H*A	F5DFL413H*A	112 @ 2300	85.5	N/A	337 @ 1500	101,6	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413J*A	F5DFL413J*A	105 @ 2300	80.0	N/A	327 @ 1500	98,7	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413K*A	F5DFL413K*A	97 @ 2300	74.0	N/A	300 @1500	90,5	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413L*A	F5DFL413L*A	84 @ 2300	64.5	N/A	259 @ 1500	77,7	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL414D*A	F5DFL414D*A	111 @ 2200	85.8	N/A	332 @1400	100.1	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL414C*A	F5DFL414C*A	100 @ 2200	77.2	N/A	309 @1400	93.4	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL414A*A	F5DFL414A*A	94 @ 2200	72.0	N/A	291 @1400	87.0	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL414B*A	F5DFL414B*A	84 @ 2200	64.8	N/A	261 @1400	78.0	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL414F*A	F5DFL414F*A	88 @ 2200	67.9	N/A	273 @1400	81.5	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX

Engine Model Summary Template

U-R-015-0259

Attachment pg 2/2 7/18/2013

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torqu	9.Emission Control leDevice Per SAE J1930
EFPXL03.4ADD	F5HFL413H*A	F5HFL413H*A	82 @ 2500	60.6	N/A	257 @1400	77.0	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL413J*A	F5HFL413J*A	96 @ 2000	79.0	N/A	305 @ 1400	91.0	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL414E*A	F5DFL414E*A	100 @ 2500	72.1	N/A	289 @ 1600	86.7	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL414G*A	F5DFL414G*A	115 @ 2500	82.7	N/A	311 @ 1600	93.8	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL414H*A	F5DFL414H*A	88 @ 2500	64.3	N/A	255 @ 1600	76.1	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL413S*A	F5HFL413S*A	82 @ 2300	· 61	N/A	247 @ 1500	73	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL413T*A	F5HFL413T*A	90 @ 2300	66	N/A	271 @ 1500	80	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL413M*A	F5HFL413M*A	96 @ 2300	71	N/A	301 @ 1600	89	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL413N*A	F5HFL413N*A	95 @ 2300	70	N/A	271 @ 1500	80	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL413P*A	F5HFL413P*A	100 @ 2300	74	N/A	297 @ 1500	87	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5HFL413R*A	F5HFL413R*A	103 @ 2300	78	N/A	299 @ 1700	89	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413S*A	F5DFL413S*A	82 @ 2300	61	N/A	247 @ 1500	73	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413T*A	F5DFL413T*A	90 @ 2300	66	/ N/A	271 @1500	80	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413M*A	F5DFL413M*A	96 @ 2300	71	N/A	301 @ 1600	89	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413N*A	F5DFL413N*A	95 @ 2 300	70	N/A	271 @1500	80	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413P*A	F5DFL413P*A	100 @ 2300	74	N/A	297 @ 1500	87	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX
EFPXL03.4ADD	F5DFL413R*A	F5DFL413R*A	103 @ 2300	78	N/A	299 @ 1700	89	N/A	DDI, ECM, TC, CAC, EGR,OC PTOX