

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2014	EFPXL06.7SDA	6.7	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Electronic Direct Injection, Turbocharger, Charge Air Cooler, Engine Control Module, Diesel Oxidation Catalyst, Selective Catalytic Reduction - Urea, Ammonia Oxidation Catalyst			Loader, Tractor, and Other Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NO<sub>x</sub>), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NO<sub>x</sub>), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			NMHC	NO <sub>x</sub>	NMHC+NO <sub>x</sub>	CO	PM	ACCEL	LUG	PEAK
130 ≤ kW ≤ 560	Tier 4 Final	STD	0.19	0.40	N/A	3.5	0.02	N/A	N/A	N/A
		CERT	0.01	0.22	--	0.04	0.02	--	--	--

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

**This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.**

Executed at El Monte, California on this 27<sup>th</sup> day of December 2013.

  
 for Erik White, Chief  
 Mobile Source Operations Division

### Engine Model Summary Template

U-R-015-0264

Attachment pg 1/1

12/26/2013

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
EFPXL06.7SDA	F4HFE613R*B	F4HFE613R*B	245 @ 2000	130	N/A	963 @ 1300	188	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE613X*B	F4HFE613X*B	226 @ 2000	111	N/A	742 @ 1500	135	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE613S*B	F4HFE613S*B	226 @ 2000	116	N/A	877 @ 1300	162	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE613J*B	F4HFE613J*B	221 @ 2200	106	N/A	767 @ 1500	144	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4DFE613J*B	F4DFE613J*B	221 @ 2200	106	N/A	767 @ 1500	144	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE613G*B	F4HFE613G*B	210 @ 2200	102	N/A	678 @ 1600	127	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE613K*B	F4HFE613K*B	202 @ 2200	97	N/A	696 @ 1500	129	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4DFE613K*B	F4DFE613K*B	202 @ 2200	97	N/A	696 @ 1500	129	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4DFE613M*B	F4DFE613M*B	188 @ 2200	94	N/A	648 @ 1500	122	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE613D*B	F4HFE613D*B	235 @ 2100	115	N/A	781 @ 1500	144	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE613B*B	F4HFE613B*B	256 @ 2200	118	N/A	859 @ 1500	157	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4DFE613B*B	F4DFE613B*B	256 @ 2200	118	N/A	859 @ 1500	157	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE613E*B	F4HFE613E*B	268 @ 2100	130	N/A	867 @ 1800	163	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE613C*B	F4HFE613C*B	275 @ 2100	133	N/A	881 @ 1800	164	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4DFE613H*B	F4DFE613H*B	236 @ 2200	106	N/A	815 @ 1500	148	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE613H*B	F4HFE613H*B	236 @ 2200	106	N/A	815 @ 1500	148	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE613F*B	F4HFE613F*B	284 @ 2200	131	N/A	859 @ 1500	155	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE613A*B	F4HFE613A*B	251 @ 2200	115	N/A	789 @ 1600	143	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE613U*B	F4HFE613U*B	251 @ 2200	118	N/A	859 @ 1500	157	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE6131*B	F4HFE6131*B	281 @ 2200	130	N/A	852 @ 1500	154	N/A	DDI ECM TC CAC SCR AMOX OC
EFPXL06.7SDA	F4HFE6134*B	F4HFE6134*B	295 @ 2200	139	N/A	881 @ 1700	163	N/A	DDI ECM TC CAC SCR AMOX OC