EXECUTIVE ORDER U-R-025-0621 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)	
2014	EKBXL02.4EKD	1.826, 2.435	Diesel		
	FEATURES & EMISSION		TYPICAL EQUIPMENT APPLICATION		
Exhaust C	ctronic Direct Injection, Gas Recirculation, Electr Oxidation Catalyst, Perio	onic Control Module,	Loader, Tractor, Pump, Compressor and Other Industrial Equipment		

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kW-hr)				OPACITY (%)			
POWER	STANDARD		NMHC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
19 ≤ kW < 56	Tier 4 Final	STD	N/A	N/A	4.7	5.0	0.03	N/A	N/A	N/A
		CERT			3.2	0.04	0.003			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has complied with the more stringent set of standards from the various power categories in conformance with Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for 2008 and Later Tier 4 Off-Road Compression-Ignition Engines, Part I-C" adopted October 20, 2005.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______ day of December 2013.

Erik White, Chief

Mobile Source Operations Division

Engine Model Summary Form

Manufacturer:

KUBOTA Corporation

Engine category:

Nonroad Cl

EPA Engine Family: **EKBXL02.4EKD**

Mfr Family Name:

N/A

Process Code:

Running Change

Attachment page 1 of 1

EO#U-R-025-0621

Date: 3/19/2014

V2403-CR-T-EF01 V V2403-CR-T-EF02 V	D1803-CR-T-EF		(for diesel only)	(lbs/hr) @ peak HP (for diesels only)	(SEA Gross)	mm/stroke@peak torque	(lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
V2403-CR-T-EF02 V	D1003-CK-1-EF	48.9@2700	43.1	19.5	109.4@1600	46.1	12.4	EM, DFI, TC, EGR, ECM, PTOX, OC
	V2403-CR-T-EF	67.3@2700	46.3	27.9	152.2@1600	48.7	17.4	EM, DFI, TC, EGR, ECM, PTOX, OC
V2403-CR-T-EF03 V	V2403-CR-T-EF	64.2@2700	43.2	26.1	144.3@1600	46.0	16.5	EM, DFI, TC, EGR, ECM, PTOX, OC
	V2403-CR-T-EF	60.1@2700	40.8	24.6	144.3@1600	46.0	16.5	EM, DFI, TC, EGR, ECM, PTOX, OC
V2403-CR-T-EF04 V	V2403-CR-T-EF	60.5@2600	41.5	24.1	144.3@1600	46.2	16.5	EM, DFI, TC, EGR, ECM, PTOX, OC
V2403-CR-T-EF05 V	V2403-CR-T-EF	55.1@2600	39.9	23.2	134.7@1600	44.0	15.7	EM, DFI, TC, EGR, ECM, PTOX, OC
V2403-CR-T-EF06 V	V2403-CR-T-EF	50.2@2600	36.5	21.2	121.1@1600	39.2	14.0	EM, DFI, TC, EGR, ECM, PTOX, OC
V2403-CR-T-EF07 V	V2403-CR-T-EF	61.7@2600	42.3	24.6	144.3@1600	46.2	16.5	EM, DFI, TC, EGR, ECM, PTOX, OC
V2403-CR-T-EF08 V	V2403-CR-T-EF	57.1@2400	42.2	22.6	144.3@1500	46.4	15.6	EM, DFI, TC, EGR, ECM, PTOX, OC
V2403-CR-T-EF09 V	V2403-CR-T-EF	52.3@2200	41.0	20.2	144.3@1500	46.4	15.6	EM, DFI, TC, EGR, ECM, PTOX, OC
V2403-CR-T-EF10 V	V2403-CR-T-EF	61.8@2600	42.4	24.6	144.3@1600	46.2	16.5	EM, DFI, TC, EGR, ECM, PTOX, OC
V2403-CR-T-EF11 V	V2403-CR-T-EF	59.4@2500	42.3	23.6	144.3@1600	46.2	16.5	EM, DFI, TC, EGR, ECM, PTOX, OC
V2403-CR-T-EF12 V	V2403-CR-T-EF	50.4@2700	35.3	21.3	121.1@1600	39.0	13.9	EM, DFI, TC, EGR, ECM, PTOX, OC
V2403-CR-T-EF13 V	V2403-CR-T-EF	52.2@2700	37.1	22.4	121.8@1600	40.4	14.5	EM, DFI, TC, EGR, ECM, PTOX, OC
V2403-CR-T-EF14 V	V2403-CR-T-EF	60.5@2700	41.1	24.8	140.2@1600	45.1	16.1	EM, DFI, TC, EGR, ECM, PTOX, OC
V2403-CR-T-EF15 V	V2403-CR-T-EF	57.9@2600	40.7	23.7	144.3@1600	46.2	16.5	EM, DFI, TC, EGR, ECM, PTOX, OC

DTI =	Direct	Fuel	Inj	ection
			V	