IHI SHIBAURA MACHINERY CORPORATION

EXECUTIVE ORDER U-R-026-0394 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2014	EH3XL2.22AB2	2.216	Diesel	5000
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT A	APPLICATION
	Indirect Diesel Inje	ection	Tractor, Loader, Industr	ial Equipment

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kw-hr)				OPACITY (%)			
POWER CLASS	STANDARD CATEGORY		НС	NOx	NMHC+NOx	СО	PM	ACCEL	LUG	PEAK
19 <u><</u> kW < 37	Tier 4 Final/ ALT 20% PM & NMHC+ NOx	STD	N/A	N/A	4.7	5.5	0.03	20	15	50
		FEL	N/A	N/A	5.1	N/A	0.30	N/A	N/A	N/A
		CERT			4.4	1.1	0.22	6	4	6

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

__ day of June 2014.

Innette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

ATTACHM ENT 10F | Engine Model Summary Template

W-R-026-0394 5/20/2014

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torqueDevice Per SAE J1930
EH3XL2.22AB2	404D-22	GN49/2800ABT 48.7@2800	48.7@2800	34.7+/-2.6	21.3+/-1.6	103.3@1800	36.0+/-2.6	14.2+/-1.0	IFI
EH3XL2.22AB2	404D-22	GN48/2600ABT 47.9@2600	47.9@2600	35.3+/-3.2	20.2+/-1.8	105.5@1800	36.3+/-2.6	14.3+/-1.0	FI
EH3XL2.22AB2	404D-22	GN46/2400ABT 45.7@2400	45.7@2400	36.2+/-2.2	19.1+/-1.2	105.5@1800	36.9+/-2.6	14.6+/-1.0	F.
EH3XL2.22AB2	C2.2	GN49/2800ABT 48.7@2800	48.7@2800	34.7+/-2.6	21.3+/-1.6	103.3@1800	36.0+/-2.6	14.2+/-1.0	E I
EH3XL2.22AB2	C2.2	GN48/2600ABT 47.9@2600	47.9@2600	35.3+/-3.2	20.2+/-1.8	105.5@1800	36.3+/-2.6	14.3+/-1.0	
EH3XL2.22AB2	C2.2	GN46/2400ABT 45.7@2400	45.7@2400	36.2+/-2.2	19.1+/-1.2	105.5@1800	36.9+/-2.6	14.6+/-1.0	IEI
EH3XL2.22AB2	N844L-D	45D/2600	45.0@2600	32.8+/-1.4	18.7+/-0.8	104.4@1800	37.2+/-2.4	14.7+/-0.9	F