California Environmental Protection Agency	IHI SHIBAURA MACHINERY	EXECUTIVE ORDER U-R-026-0409-1
OD Air Resources Board	CORPORATION	New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
FH3XL2.22AB2	2.216	Diesel	5000		
		TYPICAL EQUIPMENT APPLICATION			
Indirect Diesel Injection		Tractor, Loader, Excavator			
1	FH3XL2.22AB2	(liters) FH3XL2.22AB2 2.216 ATURES & EMISSION CONTROL SYSTEMS	(liters) FH3XL2.22AB2 2.216 ATURES & EMISSION CONTROL SYSTEMS TYPICAL EQUIPMENT A		

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION		EXHAUST (g/kw-hr)					OPACITY (%)			
	STANDARD CATEGORY		NMHC	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK	
19 <u><</u> kW < 37	Tier 4 Final/ ALT 20% PM	STD	N/A	N/A	4.7	5.5	0.03	20	15	PEAK 50 N/A	
		FEL	N/A	N/A	N/A	N/A	0.30	N/A	N/A	N/A	
		CERT			4.4	1.1	0.22	6	4	6	

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

This Executive Order hereby supersedes Executive Order U-R-026-0409 dated September 12, 2014.

Executed at El Monte, California on this ______day of September 2015.

nnette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Engine Model Summary Template

U-R-026-0409-1 R/C 9/10/2015

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque		9.Emission Control Device Per SAE J1930	
FH3XL2.22AB2	404D-22	GN49/2800ABT	48.7@2800	34.7+/-2.6	21.3+/-1.6	103.3@1800	36.0+/-2.6	14.2+/-1.0	1F1	
FH3XL2.22AB2	404D-22	GN48/2600ABT	47.9@2600	35.3+/-3.2	20.2+/-1.8	105.5@1800	36.3+/-2.6	14.3+/-1.0	IF1	9.98 ° 10. 2010 ° 10
FH3XL2.22AB2	404D-22	GN46/2400ABT	45.7@2400	36.2+/-2.2	19.1+/-1.2	105.5@1800	36.9+/-2.6	14.6+/-1.0		
FH3XL2.22AB2	C2.2	GN49/2800ABT	48.7@2800	34.7+/-2.6	21.3+/-1.6	103.3@1800	36.0+/-2.6	14.2+/-1.0		nggana ang Lan s
FH3XL2.22AB2	C2.2	GN48/2600ABT	47.9@2600	35.3+/-3.2	20.2+/-1.8	105.5@1800	36.3+/-2.6	14.3+/-1.0		end word
FH3XL2.22AB2	C2.2	GN46/2400ABT	45.7@2400	36.2+/-2.2	19.1+/-1.2	105.5@1800	36.9+/-2.6	14.6+/-1.0		***.277.6.85
FH3XL2.22AB2	N844L-D	45D/2600	45.0@2600	32.8+/-1.4	18.7+/-0.8	104.4@1800	37.2+/-2.4	14.7+/-0.9	IFI	MT-D'-Oba -D