EXECUTIVE ORDER U-R-025-0683 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)				
2016	GKBXL01.7ECB	1.648	Diesel	3000				
	FEATURES & EMISSION C		TYPICAL EQUIPMENT APPLICATION					
egstegger og de	Mechanical Direct Inj	ection	Tractor, Compressor, Generator Set, and Other Industrial Equipment					

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION	·		E	XHAUST (g/kw-l	OPACITY (%)				
	STANDARD CATEGORY		NMHC	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
8 ≤ kW < 19	Tier 4 Final	STD	N/A	N/A	7.5	6.6	0.40	20	15	50
		CERT		7 G G	6.5	2.3	0.32	4	6	6

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

day of December 2015.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

EO# U-R-025-0683

Engine Model Summary Form

Attachment page 1 of

KUBOTA Corporation Manufacturer:

Nonroad Cl Engine category:

GKBXL01.7ECB EPA Engine Family:

Mfr Family Name:

New Submission Process Code:

I	7825-77			1	A SE	Lifeal	- Down	- Carl	- E	17.2.1	Shar	19(5)	ESPEC	Tarkini.	100-21	12.00	r
									100			1	334	25 m		40.0	1
	47					100		1257	150		Sort Zaro	25	\$2.0 3.00	442.7	35	d (4)	
റ്റ								15			建杂的 加速的						
9.Emission Control Device Per SAE J1930	Sept. 7				驗	100		25	25.0		100					100	
o III	$\dot{-}$	-	<u>.</u>	-	= 1	100	0.14	30	200		32 32 3 34 3 4 34 3 4 3				100 April	A.J.	
S A	EM, DFI	EM, DFI	EM, DFI	EM, DFI	EM, DFI	43	1874	35	327			77561 1574	75.20 (5.53)		北京		
ig is	ij	٦,		_						0.59 to 0.50 to		120	7.5%				
P P					副		#16.45 #16.45	2000年		意图	5.2		经	提定	-0.0		
i ii ii	V					44		77.	184	選到	(XS)			7,242			
6 9							44	357	Fav		2.5	12 E			100		1
	, j. j.					140	海 湾		345								١.
. [322		25 Hz			100 m					-
				-			200.0		40-676 0-655 24-78-2	301351 11753	1287	#5·			NO.		l
			× 91				72			250 240 240				193	· [22]	160	
									15.7			F.S.	1,000	(1) (2) (2)		55. 17.2	
8.Fuel Rate: (lbs/hr)@peak torque					1.7	25	352		4.4	14.6		851	24.000 V.1.000			200	1
8.Fuel Rate: lbs/hr)@pea torque	~	_	'	_	~		07 25 a 040 5 3	221		200	75 T	- 機能	652		2000 2000 2000 2000		ŀ
⁻uel Ra' //hr)@pe torque	7.8	7.8	8.6	8.3	7.8		0-57-1 70-20-1			JE2L	360	. 23			100	188	
Sh th		ĺ										34		接受	13.7		1
8 <u>G</u>	*					22		*		1000		1500		300	2.0		1
			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			144			200			要	5		99.8		1
								英档		1972.5 1972.1		新	637	ME A	建		
7.Fuel Rate: mm/stroke@peak torque						185		19/2	1674					300	100	- Kú	
7.Fuel Rate: n/stroke@pe torque									25.5	74	-	145	1424		113	1000	ŀ
-uel Ra troke@ torque	31.1	Ψ.	32.2	-	31.1			100			1		J.C.				
la S E	3	31.1	32	31.1	31		7		100		72.6				439	變	1
17. 12. 14. 1		1					3.3	165	155			100	100	· \$5.5		296	
7 mn							. 1	740°				17.37	- 第.	ALEX LAGE			
=					34	91A	120/4 (A) (A)	275 275	震	255		120				196	
_								4600			綾				遊科		
6.Torque @ RPM (SEA Gross)	71.8@1500	71.8@1500	0	0	71.8@1500		584	發揮	100					25	1		1
R (SS)	50	22	60	71.8@1600	20	46	34,6	5.0	965.4	06.34							-
(g) 27.	2	2	2	2	2				7984	71.0	· · · · · · · · · · · · · · · · · · ·	##.	- 機種	100			1
Y. Ye	86	18	9	18	8		(2)			1	F	1831					1
S S	5	-	7	-	$\ddot{-}$	1340: 1440:					472	974		. 633			
D.9	7		7		~		經算	73	建			- 32		一層			ľ
		1	10%		100	97.14		9/10	45				1000		2 3 5 5 6 1 4 1	1837	4
Δ.	70.			'		***	是到	100		#						- 100	ŝ
	hit.	1				ine.	3513 2533	1889 E					257	185	1880		
ate eal		۱_ـ	1.00	l	(6-7)	(C) lott	954	## P	7.74	# <u>\$2</u> 4	- [6]				藥裝	- 26	ž
유민	7	10.4	Z	10.4	10.4	4	\$ 100 m	97		55		· [22]				7.5	į.
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	10.4	=	10.4	=	$\widetilde{\Sigma}$. 137-	Sign	136	232						
5.F		1		1		25±7	(2) (2)		444	譜			1	- 1/2			
. gg (b	4		7			0.00	553	957	7.2		A594	關					
				l · ·		38	墨語	1.3.5	W.Z		4.5						1
우	6.1		100	1	74	基	阿基	1	13/2		- 機能		135	1500 - 2000		1 44	
まさ	25	1			27	(1) (1)	4.5	100	F1937	200		98	100		要	1/2	١.
on the	1	1				20 X		100 E	1 2 2				130		100 AT		
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	28.3	28.3	28.3	28.3	28.3	變	<u>\$8</u>	47		100	25/		200		E #	. 8	Ĭ
les ies	28	18	28	18	188	12.5						(257.	· 建定				á
드호인		1		1	湿。	10 pm	455	145	130	- 50 L					蒙:		
fe fet									75			1/4	2			5.4 5.4 5.4	2
Ē		1	1						2	400				560	10.50		4
_	7	1										700 A	73.5	575		1 1800 1760	Ĭ
_			1			第	1307E		48			 数	2.76				7
M (§;	18	18	8	18	Ö		英語	227	#F.		243	53		300		1	
<u> </u>	2	12	12	121	12		12.4				8.55	56	153:1	3050			
3.BHP@RPM (SAE Gross)	24.8@2200	24.8@2200	24.8@2200	24.8@2200	24.8@2200	500			13.7	標 名	25	7-14 11-12-1	100				1
H SX	183	180	8	182	182	1600	200				423% 456.6	25.5	243		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		1
ري مي م	3	12	Š	12	12	7.	1991		3/4				製料				
	2					G Gr	99	1963	K/组	ivier.	100	翻		. J	34		
				1.	Tal.		- 331	\$ 5	53		9, W	100		37.			
ge	11.	ш	出	出	陆					33.5	27	17/2	100 P				
ş	世	D1.7A-DI-EF	15		=			2.1	8/17 8/17	572	25	ide:	1944.		16.6		
<u>حــ</u> ۵)	P	巨	T	17	I			(35)		E				建 な	500		ě
Ĕ.	≥	K	1	5	5			75.5			No.			250	特集		
ρ		1	18	18	Įģ.	. (3)	95.	120			W.5.2	1 (1 t) 2 (2 t)	震震	74.1			2
2.Engine Model	C1.7-M-DI-EF		15	D1703-M-DI-EF	Ξ		数 岩		<u> </u>				1			1 🎇	5
. ~		1		1"	F				E	7.					K		4
•		1	1	2	6			3.1			1.04812 2017					. His	
ğ	18	33	12	16.			基础		1974. (1975.)		\$ C			10.45			1
ŏ	11	悟	11	1 4	1 4	1881	模類		54		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	老生	Mel				4
<u>o</u>	ㅁ	금	19	19	19		[43]		524	25		9,5	13/4		J Japan		1
Æ	Įέ	14	M	ĮΣ	ĬΞ				100	27		12.0					
1.Engine Code	C1.7-M-DI-EF03.	D1.7A-DI-EF03	D1703-M-DI-EF01 D1703-M-DI-EF	D1703-M-DI-EF02	D1703-M-DI-EF03 D1703-M-DI-EF		150			Fat		V8[16]					1
Щ.	2	Δ	17	15	5		L.Y.					2.7		W			30
7	13.3	1	L _T	1"	11		1.5.1	t and		17.24	F		144	1.86	1 145	1 18	1