California Environmental Protection Agency

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2016	GJCBL04.8S12	4.765	Diesel	8,000			
	FEATURES & EMISSION		TYPICAL EQUIPMENT APPLICATION				
Electronic Direct Injection, Turbocharger, Charge Air Cooler, Electronic Control Module, Exhaust Gas Recirculation, Selective Catalytic Reduction-Urea, Ammonia Oxidation Catalyst			Crane, Loader, Tractor, Dozer, Pump, Compressor, Forklif				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kW-hr)					OPACITY (%)		
POWER CLASS	STANDARD		NMHC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
75 - 1044 - 400	Tion 4 Final	STD	0.19	0.40	N/A	5.0	0.02	• N/A	N/A	N/A
75 ≤ kW < 130	Tier 4 Final	CERT	0.08	.0.37		0.1	0.02			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______ day o

____ day of January 2016.

Emissions Compliance, Automotive Regulations and Science Division

U-R-049-0041

Engine Model Summary Template

ATTACHMENT

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM mr (SAE Gross)	4.Fuel Rate: m/stroke @ peak H (for diesel only)	5.Fuel Rate: IRlbs/hr) @ peak HP (for diesels only)					9.Emission Control Device Per SAE J1930
GJCBL04.8S12	448 TA4-108	C1A	145.2 @ 2000	109	53.9	413 @ 1500	122	41.1	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-108	C1C	145.2 @ 2000	109	53.9	413 @ 1500	122	41.1	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-108	D1A	145.2 @ 2000	109	53.9	413 @ 1500	122	41.1	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-129	D1A	173.3 @ 2050	135	62.2	509 @ 1500	149	50.3	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA 4 -129	E1A	173.3 @ 2050	135	62.2	509 @ 1500	149	50.3	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-129	E1C	173.3 @ 2050	135	62.2	509 @ 1500	149	50.3	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-108	I2A	145.2 @ 2000	109	53.9	413 @ 1500	122	41.1	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-129	I2A	173.3 @ 2050	135	62.2	509 @ 1500	149	50.3	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-108	12C	145.2 @ 2000	109	53.9	413 @ 1500	122	41.1	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-129	120	173.3 @ 2050	135	62.2	509 @ 1500	149	50.3	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-108	L1A	145.2 @ 2000	109	53.9	413 @ 1500	122	41.1	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-108	L1C	145.2 @ 2000	109	53.9	413 @ 1500	122	41.1	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-108	V1A	145.2 @ 2000	109	53.9	413 @ 1500	122	41.1	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-108	V1C	145.2 @ 2000	109	53.9 -	413 @ 1500	122	41.1	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-108	W1A	145.2 @ 2000	109	53.9	413 @ 1500	122	41.1	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX
GJCBL04.8S12	448 TA4-108	W1C	145.2 @ 2000	109	53.9	413 @ 1500	122	41.1	DFI, ECM, EGR,	TC, CAC, SCR-U, AMOX