Celifornia Environmental Protection Agency		EXECUTIVE ORDER U-R-002-0664
@ Air Resources Board	CUMMINS INC.	New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2018	JCEXL04.5AAJ	4.5	Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Electronic Direct Injection, Turbocharger, Electronic Control Module, Exhaust Gas Recirculation, Diesel Oxidation Catalyst, Selective Catalytic Reduction – Urea, Ammonia Oxidation Catalyst			Generator S	Set		

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kw-hr)					OPACITY (%)		
POWER CLASS	STANDARD	1000	NMHC	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
75 ≤ kW ≤ 560	Tier 4 Final	OPTIONAL STD	0.19	0.40	N/A	3.5	0.02	N/A	N/A	N/A
		CERT	0.01	0.21		0.00	0.01			

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has complied with the more stringent set of standards from the various power categories in conformance with Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for New 2011 and Later Tier 4 Off-Road Compression-Ignition Engines, Parts I-D" adopted October 20, 2005 and last amended October 25, 2012.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

day of September 2017.

nette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

Attreyveyt 13161 8/11/207

## Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (Ibs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque		9.Emission Control orqueDevice Per SAE J1930
JCEXL04.5AAJ	4665:FR94887	QSB4.5	180@1500	159	94.4	864@1500	161	95.7	ECM,EGR,DOC,SCR,
,									DDI,TC
JCEXL04.5AAJ	4665:FR94887	QSB4.5	206@1800	154	109.5	827@1800	156	111.5	ECM,EGR,DOC,SCR,
									DDI,TC
JCEXL04.5AAJ	4665:FR95275	QSB4.5	147@1500	126	74.7	717@1500	129	76.7	ECM,EGR,DOC,SCR,
									DDI,TC
JCEXL04.5AAJ	4665:FR95275	QSB4.5	169@1800	120	85.7	688@1800	124	88.2	ECM,EGR,DOC,SCR,
									DDI,TC
JCEXL04.5AAJ	4665:FR95274	QSB4.5	106@1500	88	52.4	518@1500	90	53.8	ECM,EGR,DOC,SCR,
									DDI,TC
JCEXL04.5AAJ	4665:FR95274	QSB4.5	124@1800	86	61.7	506@1800	89	63.2	ECM,EGR,DOC,SCR,
									DDI,TC
								tAm	ux 1

٢