## FPT INDUSTRIAL S.p.A.

EXECUTIVE ORDER U-R-015-0351

New Off-Road

Compression-Ignition Engines

Page 1 of 1 Pages

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2018	JFPXL03.4ADD	3.4	Diesel	8000		
	FEATURES & EMISSION		TYPICAL EQUIPMENT			
Electronic Direct Injection, Turbocharger, Charge Air Cooler, Electronic Control Module, Exhaust Gas Recirculation, Diesel Oxidation Catalyst, Periodic Trap Oxidizer			Loader, Tractor, Dozer, and Other Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION		EXHAUST (g/kw-hr)					OPACITY (%)		
CLASS	STANDARD CATEGORY		NMHC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
56 ≤ kW < 130	Tier 4 Final / ALT 5% NOx	OPTIONAL STD	0.19	0.40	N/A	5.0	0.02	N/A	N/A	N/A
		FEL	N/A	3.40	N/A	N/A	N/A	N/A	N/A	N/A
		CERT	0.01	2.83		0.03	0.01			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has complied with the more stringent set of standards from the various power categories in conformance with Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedure's for New 2011 and Later Tier 4 Off-Road Compression-Ignition Engines, Parts I-D" adopted October 20, 2005 and last amended October 25, 2012.

**BE IT FURTHER RESOLVED:** That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

day of September 2017.

Annette Hebert, Chief
Emissions Compliance, Automotive Regulations and Science Division

## **Engine Model Summary Template**

U-R-015-0351 Attenfant po 1/1 8/25/2017

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque		9.Emission Control leDevice Per SAE J1930
JFPXL03.4ADD	F5HFL413B*A	F5HFL413B*A	110 @ 2200	84.7	N/A	339 @ 1400	102.3	N/A	DDI, ECM, TC, CAC, EGR,DOC PTOX
JFPXL03.4ADD	F5HFL413J*A	F5HFL413J*A	96 @ 2000	79.0	N/A	305 @ 1400	91.0	N/A	DDI, ECM, TC, CAC, EGR,DOC PTOX
JFPXL03.4ADD	F5DFL413J*A	F5DFL413J*A	106 @ 2300	80	N/A	329 @ 1500	98.7	N/A	DDI, ECM, TC, CAC, EGR, DOC PTOX
JFPXL03.4ADD	F5DFL413K*A	F5DFL413K*A	98 @ 2300	74	N/A	301 @ 1500	90.5	N/A	DDI, ECM, TC, CAC, EGR,DOC PTOX
JFPXL03.4ADD	F5DFL413L*A	F5DFL413L*A	84 @ 2300	64.5	N/A	260 @ 1500	77.7	N/A	DDI, ECM, TC, CAC, EGR,DOC PTOX
JFPXL03.4ADD	F5DFL4131*A	F5DFL4131*A	98 @ 2300	76	N/A	313 @ 1200	96	N/A	DDI, ECM, TC, CAC, EGR,DOC PTOX