

IHI AGRI-TECH CORPORATION

EXECUTIVE ORDER U-R-026-0498 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2018	JH3XL2.22TD3	2.22, 1.662	Diesel	5000		
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION			
Electror Oxidat	ic Direct Injection, Engir ion Catalyst, Turbochar Recirculation	ne Control Module, ger, Exhaust Gas	Tractor, Generator, Other Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			NMHC	NOx	NMHC+NOx	СО	PM	ACCEL	LUG	PEAK
19 <u><</u> kW < 37	Tier 4 Final	STD	N/A	N/A	4.7	5.5	0.03	N/A	N/A	N/A
		CERT			4.7	2.5	0.03	-		

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

10

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

day of December 2017.

ATTACHMENTI OF1

Engine Model Summary Template U-R-026-0498

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7,Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control eDevice Per SAE J1930
JH3XL2.22TD3	N4LDI-T	4LT362800	48.8@2800	34.9	21.9	122@1800	41.4	16.7	DDI,ECM,TC,EGR, OC
JH3XL2.22TD3	N4LDI-T	4LT301800C	40.2@1800	37.0	15.0	117@1800	37.0	15,0	DDI,ECM,TC,EGR, OC
	different - communication and accommunication and accommunity of the communication of the com								COSSONIA PARA ANTONIA MARTINI ANTONIA MARTINI PARA PARA PARA PARA PARA PARA PARA PAR
JH3XL2.22TD3	N3LDI-T	4LT362400	48.3@2400	38.7	20.4	118@1800	38.2	15.1	DDI,ECM,TC,EGR, OC
JH3XL2.22TD3	N4LDI-T	4T362600-4503	48.8@2800	38.7	22.1	118@1600	39.9	14.0	DDI,ECM,TC,EGR, OC
JH3XL2.22TD3	N4LDI-T	4T362600-4504	48.8@2800	38.7	22.1	118@1600	39.9	14.0	DDI,ECM,TC,EGR, OC
JH3XL2.22TD3	N3LDI-T	3T272600-4518	36.2 @ 2600	36.9	15.8	89 @ 1600	37.9	10.0	DDI,ECM,TC,EGR, OC
JH3XL2.22TD3	N3LDI-T	3T272600-4519	36.2 @ 2600	36.9	15.8	89 @ 1600	37.9	10.0	DDI,ECM,TC,EGR, OC
JH3XL2.22TD3	N3LDI-T	3T302600-4509	40.0 @ 2600	39,8	17.0	89 @ 1600	39	10.3	DDI,ECM,TC,EGR, OC
JH3XL2.22TD3	N3LDI-T	3T302600-4510	40.0 @ 2600	39.8	17.0	89 @ 1600	39	10.3	DDI,ECM,TC,EGR, OC
JH3XL2.22TD3	N4LDI-T	4T362600-4507	48.8 @ 2600	38.7	22.1	118 @ 1600	39.9	14.0	DDI,ECM,TC,EGR, OC
JH3XL2.22TD3	N4LDI-T	4T362600-4508	48.8 @ 2600	38.7	22.1	118 @ 1600	39.9	14.0	DDI,ECM,TC,EGR, OC