Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR ENGINE FAMILY		DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2018	JFTGL02.2R3C	2.2	Diesel	8000		
	FEATURES & EMISSION		TYPICAL EQUIPMENT APPLICATION			
Charge Ai Injection	r Cooler, Oxidation Cata n, Electronic Control Mod Periodic Trap Oxid	lule, Turbocharger,	Loaders, Tractor, Dozer, Generator Set and Other Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
POWER			NMHC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
19 ≤ kW < 56	Tier 4 Final	OP <b>TION</b> AL STD	N/A	N/A	4.7	5.0	0.03	N/A	N/A	N/A
		CERT			4.6	0.1	0.02	-		

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has complied with the more stringent set of standards from the various power categories in conformance with Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for New 2011 and Later Tier 4 Off-Road Compression Ignition Engines, Part I-D" adopted October 20, 2005 and last amended October 25, 2012.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

3

\_ day of November 2017.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

## **Engine Model Summary Template**

10-19-2017

EO#: U-R-068-0008

(0)			4.Fuel Rate:	5.Fuel Rate:		7.Fuel Rate:	0 Food Bata		
Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	mm/stroke @ peak HP (for diesel only)	(lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
JFTGL02.2R3C	50D/1	50D/1	67 @ 2500	69.5	N/A	185 @ 1800	85.2	N/A	DDI ECM TC CAC OC PTOX
JFTGL02.2R3C	50D/2	50D/2	65 @ 2600	66.7	N/A	162 @ 1800	70.2	N/A	DDI ECM TC CAC OC PTOX
JFTGL02.2R3C	50D/3	50D/3	58 @ 2600	62.3	N/A	148 @ 1800	65.2	N/A	DDI ECM TC CAC OC PTOX
JFTGL02.2R3C	50D/4	50D/4	55 @ 2600	60.2	N/A	137 @ 1800	62.6	N/A	DDI ECM TC CAC OC PTOX
JFTGL02.2R3C	50D/5	50D/5	53 @ 2600	57.0	N/A	133 @ 1800	61.8	N/A	DDI ECM TC CAC OC PTOX
JFTGL02.2R3C	50D/6	50D/6	45 @ 2600	52.4	N/A	119 @ 1800	56.0	N/A	DDI ECM TC CAC OC PTOX
JFTGL02.2R3C	50D/7	50D/7	60 @ 2600	65.8	N/A	153 @ 1800	70.2	N/A	DDI ECM TC CAC OC PTOX
JFTGL02.2R3C	50D/8	50D/8	70 @ 2600	73.5	N/A	181 @ 1800	83.0	N/A	DDI ECM TC CAC OC PTOX

A Hach went: Page lof!