

CATERPILLAR INC.

EXECUTIVE ORDER U-R-001-0624 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2020	LCPXL15.2HTF	15.2	Diesel	8000			
SPECIA	AL FEATURES & EMISSIO	ON CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION				
Oxidation	Catalyst, Engine Conti	harger, Charge Air Cooler, rol Module, Periodic Trap duction-Urea, Ammonia talyst	Loader, Tractor, Dozer, Off-road Truck, Excavato Commercial Equipment				

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, Califomia Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kw-hr)					OPACITY (%)		
POWER CLASS	STANDARD		NMHC	NOx	NMHC+NOx	СО	PM	ACCEL	LUG	PEAK
130 ≤ kW ≤ 560	Tier 4 Final	STD	0.19	0.40	N/A	3.5	0.02	N/A	N/A	N/A
		FEL	N/A	N/A	-	N/A	0.01	N/A	N/A	N/A
		CERT	0.06	0.11		0.1	0.01	-		

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

My the

Allen Latons, Chief

Emissions Certification and Compliance Division

day of December 2019.

ATTACHMENT 1072

Engine Model Summary Template U-R-001-0624

R/C 1/27/2020

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
LCPXL15.2HTF	Cert Test 1	C15	578@2100	302	214	1955@1400	372	175	DFI,TC,ECM,CAC,EGR,PTOX,OC,SCR-U.AMOX
LCPXL15.2HTF	1	C15	485@1900	275.6	176.1	1891@1200	368.3	148.7	DFI,TC,ECM,CAC,EGR,PTOX, OC.SCR-U.AMOX
LCPXL15.2HTF	2	C15	473@2100	246.9	174.4	1600@1400	310.8	146.4	DFI,TC,ECM,CAC,EGR,PTOX,OC,SCR-U,AMOX
LCPXL15.2HTF	3	C15	473@2100	246.9	174.4	1600@1400	310.8	146.4	DFI,TC,ECM,CAC,EGR,PTOX,OC,SCR-U,AMOX
LCPXL15.2HTF	4	C15	539@2100	282.2	199.3	1820@1400	352.0	165.8	DFI,TC,ECM,CAC,EGR,PTOX, OC,SCR-U,AMOX
LCPXL15.2HTF	5	C15	578@2100	310.3	219.2	1955@1400	380.1	179.0	DFI,TC,ECM,CAC,EGR,PTOX, OC,SCR-U,AMOX
LCPXL15.2HTF	6	C15	485@1700	292.4	167.2	1698@1350	327.4	148.7	DFI,TC,ECM,CAC,EGR,PTOX, OC.SCR-U.AMOX
LCPXL15.2HTF	7	C15	314@2000	179.0	120.4	1438@1300	279.0	122.0	DFI,TC,ECM,CAC,EGR,PTOX, OC.SCR-U.AMOX
LCPXL15.2HTF	8	C15	426@1800	245.1	148.4	1568@1300	304.1	133.0	DFI,TC,ECM,CAC,EGR,PTOX, OC,SCR-U.AMOX
LCPXL15.2HTF	9	C15	409@2000	220.1	148.1	1693@1200	333.3	134.5	DFI,TC,ECM,CAC,EGR,PTOX, OC,SCR-U.AMOX
LCPXL15.2HTF	10	C15	539@2100	282.1	199.3	1820@1400	352.0	165.7	DFI,TC,ECM,CAC,EGR,PTOX,OC,SCR-U.AMOX
LCPXL15.2HTF	11	C15	314@2000	179.0	120.4	1438@1300	279.0	122.0	DFI,TC,ECM,CAC,EGR,PTOX, OC.SCR-U.AMOX
LCPXL15.2HTF	12	2506F	539@2100	282.2	199.3	1820@1400	352.0	165.8	DFI,TC,ECM,CAC,EGR,PTOX, OC.SCR-U.AMOX
LCPXL15.2HTF	13	2506F	578@2100	310.3	219.2	1955@1400	380.1	179.0	DFI,TC,ECM,CAC,EGR,PTOX, OC.SCR-U.AMOX
LCPXL15.2HTF	14	2506F	473@2100	246.9	174.4	1600@1400	310.8	146.4	DFI,TC,ECM,CAC,EGR,PTOX, OC.SCR-U.AMOX
LCPXL15.2HTF	15	2506F	473@2100	246.9	174.4	1600@1400	310.8	146.4	DFI,TC,ECM,CAC,EGR,PTOX, OC.SCR-U.AMOX
LCPXL15.2HTF	16	C15	416@2000	228.1	153.4	1752@1200	348.3	140.6	DFI,TC,ECM,CAC,EGR,PTOX, OC.SCR-U.AMOX
LCPXL15.2HTF	17	C15	378@2050	202.6	139.7	1578@1200	300.6	121.3	DFI,TC,ECM,CAC,EGR,PTOX, OC.SCR-U.AMOX
LCPXL15.2HTF	18	C15	409@2000	220.1	148.1	1693@1200	333.3	134.5	DFI,TC,ECM,CAC,EGR,PTOX, OC.SCR-U.AMOX
LCPXL15,2HTF	19	C15	485@1700	292.4	167.2	1698@1350	327.4	148.7	DFI,TC,ECM,CAC,EGR,PTOX,OC.SCR-U.AMOX

ATTACHMENT 20F2

Engine Model Summary Template U-R-001-0624

					1/27/2020						
Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)		7.Fuel Rate: mm/stroke@peak torque	8. Fuel Rate:	9.Emission Control Device Per SAE J1930		
LCPXL15.2HTF	20	C15	473@2100	246.9	174.4	1600@1400	310.8	146.4	DFI,TC,ECM,CAC,EGR,PTOX,OC,SCR-U,AMOX		
LCPXL15.2HTF	20 A ⊀	C15	473@2100	246.9	174.4	1600@1400	310.8	146.4	DFI,TC,ECM,CAC,EGR,PTOX,OC.SCR-U.AMOX		

* New Engine Code