

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2020	LCEXL03.8AAF	3.8	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Electronic Direct Injection, Turbocharger, Charge Air Cooler, Electronic Control Module, Diesel Particulate Filter, Diesel Oxidation Catalyst, Selective Catalytic Reduction – Urea, Ammonia Oxidation Catalyst			Crane, Loader, Tractor, Pump, Dozer, Compressor, Generator Set	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			NMHC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
75 ≤ kW < 130	Tier 4 Final	STD	0.19	0.40	N/A	5.0	0.02	N/A	N/A	N/A
		CERT	0.007	0.14	--	0.01	0.01	--	--	--

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 20th day of August 2019.



Allen Lyons, Chief
 Emissions Certification and Compliance Division

EO #: U-R-002-0728
 Attachment: Page 1 of 1
 7/21/2019

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lb/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lb/hr)@peak torque	9.Emission Control Device Per SAE J1930
CEXL03.8AAF	5342:FR95676	QSF3.8	173@2500	120.9	61.7	457@1500	139	44.1	ECM, DDC, TC, DOC, DPF, SCR, ASC
CEXL03.8AAF	5342:FR95677	QSF3.8	154@2500	126.5	53.4	457@1500	139	44.1	ECM, DDC, TC, DOC, DPF, SCR, ASC
CEXL03.8AAF	5342:FR96378	QSF3.8	148@2500	110.2	51.4	443@1500	133	41.9	ECM, DDC, TC, DOC, DPF, SCR, ASC
CEXL03.8AAF	5342:FR95678	QSF3.8	134@2500	100.8	47.0	406@1500	120	38.8	ECM, DDC, TC, DOC, DPF, SCR, ASC
CEXL03.8AAF	5342:FR95679	QSF3.8	121@2500	95.4	42.3	369@1500	107	35.1	ECM, DDC, TC, DOC, DPF, SCR, ASC
CEXL03.8AAF	5342:FR95680	QSF3.8	101@2500	97.7	39.0	369@1500	107	35.1	ECM, DDC, TC, DOC, DPF, SCR, ASC
CEXL03.8AAF	5342:FR95682	QSF3.8	164@2200	126.5	53.4	457@1500	139	44.1	ECM, DDC, TC, DOC, DPF, SCR, ASC
CEXL03.8AAF	5342:FR96379	QSF3.8	148@2200	110.2	51.4	443@1500	133	41.9	ECM, DDC, TC, EGR, DOC, DPF, SCR, ASC
CEXL03.8AAF	5342:FR95683	QSF3.8	134@2200	100.8	47.0	406@1500	120	38.8	ECM, DDC, TC, DOC, DPF, SCR, ASC
CEXL03.8AAF	5342:FR95684	QSF3.8	121@2200	95.4	42.3	369@1500	107	35.1	ECM, DDC, TC, DOC, DPF, SCR, ASC
CEXL03.8AAF	5342:FR95685	QSF3.8	101@2200	101.1	38.1	369@1500	107	35.1	ECM, DDC, TC, DOC, DPF, SCR, ASC

SCR-LI, AMOX
 DDICAC