

FPT INDUSTRIAL S.p.A.

EXECUTIVE ORDER U-R-015-0422-1 New Off-Road

Compression-Ignition Engines

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-15-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)	
2020	LFPXL12.9TDS	12.9	Diesel	8000	
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION		
Electronic Direct Injection, Engine Control Module, Turbocharger, Charge Air Cooler, Diesel Oxidation Catalyst, Selective Catalystic Reduction – Urea, Ammonia Oxidation Catalyst			Loader, Tractor, Generator Set, and Other Industrial Equipment		

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)				O	OPACITY (%)		
POWER CLASS			NMHC	NOx	NMHC+NOx	со	P M	ACCEL	LUG	PEAK
130 ≤ kW ≤ 560	Tier 4 Final	STD	0.19	0.40	N/A	3.5	0.02	N/A	N/A	N/A
		FEL	N/A	0.37	N/A	N/A	N/A	N/A	N/A	N/A
		CERT	0.000	0.16		0.01	0.02			

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order U-R-015-0422 dated August 20th, 2019.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this _______ day of March 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division

Engine Model Summary Template Eo # , U - R - 015 - 0422 - 1 Attalment ; Pg //, Date: 3/4/20

					Andrew on Administration and providing the date makes
	9. Emission Control	(lbs/hr)@peak torqueDevice Per SAE J1930	DDI ECM TC CAC DOC SCR-u AMOX	DDI ECM TC CAC DOC SCR-u AMOX	DDI ECM TC CAC DOC SCR-u AMOX
	8.Fuel Rate:	(lbs/hr)@peak tord	N/A	N/A	N/A
7.Fuel Rate:	mm/stroke@peak	torque	417	364	386
	6. Torque @ RPM	(SEA Gross)	2207 @ 1400	1950 @ 1400	2067 @ 1400
5.Fuel Rate:	(lbs/hr) @ peak HP	(for diesels only)	NA	N/A	N/A
4.Fuel Rate:	mm/stroke @ peak HP (lbs/hr) @ peak HP 6.Torque @ RPM	(for diesel only)	333	297	314
			666 @ 2100	595 @ 2100	626 @ 2100
		2.Engine Model	F3DFE613F*B	F3DFE613J*B	F3DFE613G*B
		Engine Family 1. Engine Code 2. Engine Model (SAE Gross)	F3DFE613F*B	F3DFE613J*B	F3DFE613G*B
	;	Engine Family	LFPXL12.9TDS F3DFE613F*B F3DFE613F*B 666 @ 2100	LFPXL12.9TDS F3DFE613J*B F3DFE613J*B 595 @ 2100	LFPXL12.9TDS F3DFE613G*B F3DFE613G*B 626 @ 2100