Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2020	LFTGL02.2R3N	2.2	Diesel	8000			
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT	APPLICATION			
Charge Air Cooler, Oxidation Catalyst, Electronic Direct Injection, Electronic Control Module, Turbocharger, Periodic Trap Oxidizer			Loaders, Tractor, Dozer, Generator Set, Road Sweeper				

The engine models and codes are attached.

CALIFORNIA

AIR RESOURCES BOARD

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			NMHC	NOx	NMHC+NOx	со	РМ	ACCEL	LUG	PEAK
19 ≤ kW < 56	Tier 4 Final	OPTIONAL STD	N/A	N/A	4.7	5.0	0.03	N/A	N/A	N/A
		CERT			4.6	0.1	0.02			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has complied with the more stringent set of standards from the various power categories in conformance with Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for New 2011 and Later Tier 4 Off-Road Compression Ignition Engines, Part I-D" adopted October 20, 2005 and last amended October 25, 2012.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

day of October 2019.

Allen Eyons, Chief Emissions Certification and Compliance Division

EOH: U-R-068-0012 Attachment: Page lofi 10/24/19

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: m/stroke @ peak HP (for diesel onty)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
LFTGL02.2R3N	50D/1	50D/1	67 @ 2500	69.5	N/A	185 @ 1800	85.2	N/A	DDI ECM TC CAC OC PTOX
LFTGL02.2R3N	50D/2	50D/2	65 @ 2600	66.7	N/A	162 @ 1800	70.2	N/A	DDI ECM TC CAC OC PTOX
LFTGL02.2R3N	50D/3	50D/3	58 @ 2600	62.3	N/A	148 @ 1800	65.2	N/A	DDI ECM TC CAC OC PTOX
LFTGL02.2R3N	50D/4	50D/4	55 @ 2600	60.2	N/A	137 @ 1800	62.6	N/A	DDI ECM TC CAC OC PTOX
LFTGL02.2R3N	50D/5	50D/5	53 @ 2600	57.0	N/A	133 @ 1800	61.8	N/A	DDI ECM TC CAC OC PTOX
LFTGL02.2R3N	50D/6	50D/6	45 @ 2600	52.4	N/A	119 @ 1800	56.0	N/A	DDI ECM TC CAC OC PTOX
LFTGL02.2R3N	50D/7	50D/7	60 @ 2600	65.8	N/A	153 @ 1800	70.2	N/A	DDI ECM TC CAC OC PTOX
LFTGL02.2R3N	50D/8	50D/8	70 @ 2600	73.5	N/A	181 @ 1800	83.0	N/A	DDI ECM TC CAC OC PTOX
LFTGL02.2R3N	50D/9	50D/9	67 @ 2600	72.5	N/A	171 @ 1800	78.8	N/A	DDI ECM TC CAC OC PTOX
LFTGL02.2R3N	50D/10	50D/10	72 @ 2600	76.0	N/A	181 @ 1800	83.0	N/A	DDI ECM TC CAC OC PTOX