

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2021	MCEXL03.8AAD	3.8	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Electronic Direct Injection, Turbocharger, Charge Air Cooler, Electronic Control Module, Exhaust Gas Recirculation, Selective Catalytic Reduction – Urea, Ammonia Oxidation Catalyst			Crane, Loader, Tractor, Dozer, Pump, Compressor, Compactor, Forklift, Telehandler	

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			NMHC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
56 ≤ kW < 130	Tier 4 Final	OPTIONAL STD	0.19	0.40	N/A	5.0	0.02	N/A	N/A	N/A
		FEL	N/A	0.46	N/A	N/A	0.04	N/A	N/A	N/A
		CERT	0.03	0.29	--	0.4	0.04	--	--	--

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has complied with the more stringent set of standards from the various power categories in conformance with Section 1039.230 (e) of the “California Exhaust Emission Standards and Test Procedures for New 2011 and Later Tier 4 Off-Road Compression-Ignition Engines, Parts I-D” adopted October 20, 2005 and last amended October 25, 2012.

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).



CUMMINS INC.

EXECUTIVE ORDER U-R-002-0763

New Off-Road
Compression-Ignition Engines
Page 2 of 2 Pages

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this 13th day of August 2020.

A handwritten signature in blue ink, appearing to read 'Allen Lyons'.

Allen Lyons, Chief
Emissions Certification and Compliance Division

Engine Model Summary Template

EO#: U-R-002-0763
Attachment page 1 of 1
Date: 06/30/2020

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: HP(lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
MCEXL03.8AAD	4142;FR94053	QSF3.8	130@2500	95	48.8	360@1600	110	39.6	SCR,DDI,TC,EGR,ECM, AMOX,CAC
MCEXL03.8AAD	4142;FR94289	QSF3.8	110@2500	76	42.6	306@1600	92	32.9	SCR,DDI,TC,EGR,ECM, AMOX,CAC
MCEXL03.8AAD	4142;FR94290	QSF3.8	130@2200	95	46.9	360@1600	110	39.6	SCR,DDI,TC,EGR,ECM, AMOX,CAC
MCEXL03.8AAD	4142;FR94291	QSF3.8	120@2200	94	42.3	360@1600	110	39.6	SCR,DDI,TC,EGR,ECM, AMOX,CAC
MCEXL03.8AAD	4142;FR94292	QSF3.8	100@2200	83	37.3	306@1600	92	32.9	SCR,DDI,TC,EGR,ECM, AMOX,CAC
MCEXL03.8AAD	4142;FR95339	QSF3.8	100@2200	84.6	34.9	306@1600	95.2	39.2	SCR,DDI,TC,EGR,ECM, AMOX,CAC