

CUMMINS INC.

EXECUTIVE ORDER U-R-002-0769New Off-Road

Compression-Ignition Engines

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2021	MCEXL03.8AAF	3.8	Diesel	8,000		
SPECIAL	FEATURES & EMISSION C	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION			
Selective (Oxidatio	ic Control Module, Electro Catalytic Reduction-Urea, on Catalyst, Periodic Trap Oxidation Catalyst, Charge	Turbocharger, Diesel Oxidizer, Ammonia	Crane, Loaders, Tractor, Dozer, Pump, Compressor, Forklift, Sweeper and Telehandler			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kw-hr)				OPACITY (%)			
POWER CLASS	STANDARD CATEGORY		NMHC	NOx	NMHC+NOx	СО	PM	ACCEL	LUG	PEAK
75 ≤ kW < 130	Tier 4 Final	STD	0.19	0.40	N/A	5.0	0.02	N/A	N/A	N/A
		CERT	0.01	0.14		0.01	0.01	1		

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this 2nd ____day of September 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division

Engine Model Summary Template

EO#: U-R-002-0769 Attachment page 1 of 1

		•	•
Date:	07/21	/20	20

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	ς 8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control eDevice Per SAE J1930
MCEXL03.8AAF	5342:FR95676	QSF3.8	173@2500	115.0	63.3	457@1500	133.5	44.1	ECM, SCR-U, TC,
									DOC, DPF, AMOX, DDI, CAC
MCEXL03.8AAF	5342:FR95677	QSF3.8	154@2500	102.0	56.1	457@1500	133.5	44.1	ECM, SCR-U, TC,
									DOC, DPF, AMOX, DDI, CAC
MCEXL03.8AAF	5342:FR96378	QSF3.8	148@2500	97.7	53.8	443@1500	126.9	41.9	ECM, SCR-U, TC,
									DOC, DPF, AMOX, DDI, CAC
MCEXL03.8AAF	5342:FR95678	QSF3.8	134@2500	89.5	49.2	406@1500	117.5	38.8	ECM, SCR-U, TC,
									DOC, DPF, AMOX, DDI, CAC
MCEXL03.8AAF	5342:FR95679	QSF3.8	121@2500	81.4	44.8	369@1500	106.2	35.1	ECM, SCR-U, TC,
									DOC, DPF, AMOX, DDI, CAC
MCEXL03.8AAF	5342:FR95680	QSF3.8	101@2500	70.1	38.6	369@1500	106.2	35.1	ECM, SCR-U, TC,
									DOC, DPF, AMOX, DDI, CAC
MCEXL03.8AAF	5342:FR95682	QSF3.8	154@2200	112.0	54.2	457@1500	133.5	44.1	ECM, SCR-U, TC,
									DOC, DPF, AMOX, DDI, CAC
MCEXL03.8AAF	5342:FR96379	QSF3.8	148@2200	107.6	52.1	443@1500	126.9	41.9	ECM, SCR-U, TC,
									DOC, DPF, AMOX, DDI, CAC
MCEXL03.8AAF	5342:FR95683	QSF3.8	134@2200	98.6	47.7	406@1500	117.5	38.8	ECM, SCR-U, TC,
									DOC, DPF, AMOX, DDI, CAC
MCEXL03.8AAF	5342:FR95684	QSF3.8	121@2200	88.8	43.0	369@1500	106.2	35.1	ECM, SCR-U, TC,
									DOC, DPF, AMOX, DDI, CAC
MCEXL03.8AAF	5342:FR95685	QSF3.8	101@2200	74.7	36.2	369@1500	106.2	35.1	ECM, SCR-U, TC,
									DOC, DPF, AMOX, DDI, CAC