

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2021	MVPXL16.1CJA	16.1	Diesel	8,000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Electronic Diesel Injection, Electronic Control Module, Charge Air Cooler, Turbocharger, Smoke Puff Limiter, Selective Catalytic Reduction – Urea, Exhaust Gas Recirculation, Ammonia Oxidation Catalyst			Crane, Loader, Pump, Compressor, Generator Set	

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			NMHC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
130 ≤ kW ≤ 560	Tier 4 Final	<b>STD</b>	0.19	0.40	N/A	3.5	0.02	N/A	N/A	N/A
		<b>FEL</b>	N/A	N/A	N/A	N/A	0.03	N/A	N/A	N/A
		<b>CERT</b>	0.01	0.17	--	0.1	0.02	--	--	--

**BE IT FURTHER RESOLVED:** That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

**BE IT FURTHER RESOLVED:** That the manufacturer has elected to include engine models in this engine family which are identified for "emergency vehicle use only". These "emergency vehicle use only" engines are exempt from requirements imposed pursuant to California law and the regulations adopted pursuant thereto for motor vehicle pollution control devices per California Vehicle Code Section 27156.2. The manufacturer must clearly label these engines for "emergency vehicle use only" on the engines' emission control label.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

**This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.**

Executed on this 24<sup>th</sup> day of November 2020.



Allen Lyons, Chief  
Emissions Certification and Compliance Division

**Attachment 1 of 1: Engine Models**

EO #: U-R-014-0186

Family: MVPXL16.1CJA

Attachment Revised: 11/18/2020

Model	Code	Trim	Config	Displacement	Displacement - Units	Peak Power	Peak Power - Units	Peak Power - Speed (rpm)	Peak Power - Fueling	Peak Power - Fuel Units	Peak Torque	Peak Torque - Units	Peak Torque - Speed (rpm)	Peak Torque - Fuel	Peak Torque - Fuel Units	OBD	GHG	Special	Notes
TAD1670VE	I	N/A	I6	16.1	Liters	543	horsepower	1900	186	lb/hr	2757	N-m	1260	155	lb/hr	N/A	N/A	None	None
TAD1671VE	II	N/A	I6	16.1	Liters	604	horsepower	1900	205	lb/hr	2897	N-m	1260	164	lb/hr	N/A	N/A	None	None
TAD1672VE	III	N/A	I6	16.1	Liters	690	horsepower	1800	234	lb/hr	3213	N-m	1260	182	lb/hr	N/A	N/A	None	None
TAD1672VE	IV (Emergency)	Emergency	I6	16.1	Liters	690	horsepower	1800	234	lb/hr	3213	N-m	1260	182	lb/hr	N/A	N/A	None	None