



FPT INDUSTRIAL S.p.A.

EXECUTIVE ORDER U-R-015-0479
New Off-Road
Compression-Ignition Engines

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2021	MFPXL03.6EH2	3.6	Diesel	8,000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Electronic Direct Injection, Charged Air Cooler, Exhaust Gas Recirculation, Electronic Control Module, Turbocharger, Diesel Oxidation, Periodic Trap Oxidizer, Selective Catalytic Reduction – Urea, Ammonia Oxidation Catalyst			Loader, Tractor, Dozer	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			NMHC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
56 ≤ kW < 130	Tier 4 Final	STD	0.19	0.40	N/A	5.0	0.02	N/A	N/A	N/A
		CERT	0.01	0.30	--	0.02	0.004	--	--	--

BE IT FURTHER RESOLVED: That for the listed engine models which include engines from different power categories in the same engine family, the manufacturer is complying with the more stringent set of standards from the 56 ≤ kW < 130 power categories in conformance with the incorporated Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for New 2011 and Later Tier 4 Off-Road Compression Ignition Engines, Part 1-D" adopted October 20, 2005 and last amended October 25, 2012.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this 21st day of January 2021.

Allen Lyons, Chief
Emissions Certification and Compliance Division

Attachment: Engine Models

EO #: U-R-015-0479

Family: MFPXL03.6EH2

Attachment Last Revised: 1/7/2021

Model	Code	Trim	Config	Displacement	Displacement - Units	Peak Power	Peak Power - Units	Peak Power - Speed (rpm)	Peak Power - Fueling	Peak Power - Fuel Units	Peak Torque	Peak Torque - Units	Peak Torque - Speed (rpm)	Peak Torque - Fuel Units	OBD	GHG	Special	Notes
F5LGL413 W*V	F5LGL41 3W*V		I4	3.6	Liters	118	horsepower	2300	93	mm3/stroke	382	lb-ft	1300	119				DDI CAC EGR ECM TC DOC DPF SCR AMOX
F5LGL413 X*V	F5LGL41 3X*V		I4	3.6	Liters	109	horsepower	2300	89	mm3/stroke	362	lb-ft	1300	109				DDI CAC EGR ECM TC DOC DPF SCR AMOX
F5LGL413 G*V	F5LGL41 3G*V		I4	3.6	Liters	98	horsepower	2300	80	mm3/stroke	300	lb-ft	1300	90				DDI CAC EGR ECM TC DOC DPF SCR AMOX
F5LGL413 H*V	F5LGL41 3H*V		I4	3.6	Liters	85	horsepower	2300	67	mm3/stroke	259	lb-ft	1300	78				DDI CAC EGR ECM TC DOC DPF SCR AMOX