

PERKINS ENGINES COMPANY LTD.

EXECUTIVE ORDER U-R-022-0286

New Off-Road Compression-Ignition Engines Page 1 of 2

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2021	MPKXL07.0VL1	7.01	Diesel	8000			
SPECIAL	FEATURES & EMISSION O	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION				
Cha Diesel Oxio Gas Reciro	ectronic Direct Injection, T arge Air Cooler, Engine C dation Catalyst, Periodic T culation, Exhaust Pressure Reduction-Urea, Ammoni	ontrol Module, rap Oxidizer, Exhaust e Regulator, Selective	Crane, Loaders, Tractor, Dozer, Pump, Compressor, Generator Set				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kw-hr)					OPACITY (%)		
POWER CLASS	STANDARD CATEGORY		NMHC	NOx	NMHC+NOx	СО	PM	ACCEL	LUG	PEAK
75 ≤ kW ≤ 560	Tier 4 Final	STD	0.19	0.40	N/A	3.5	0.02	N/A	N/A	N/A
		FEL	N/A	N/A	N/A	N/A	0.01	N/A	N/A	N/A
		CERT	0.01	0.37	1	0.04	0.004	1		-

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

BE IT FURTHER RESOLVED: That for the listed engine models which include engines from different power categories in the same engine family, the manufacturer is complying with the more stringent set of standards from the $130 \le kW \le 560$ power category in conformance with the incorporated Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for New 2011 and Later Tier 4 Off-Road Compression Ignition Engines, Part 1-D" adopted October 20, 2005 and last amended October 25, 2012.



PERKINS ENGINES COMPANY LTD.

EXECUTIVE ORDER U-R-022-0286

New Off-Road Compression-Ignition Engines Page 2 of 2

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this _____ day of October 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division

Engine Model Summary Template

Attachment page 1 of 1 EO#: U-R-022-0286 Date: 10/14/2020

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
MPKXL07.0VL1	6186/2200 Parent	1206J- E70TA/C7.1	202@2200	105.57	76.8	669@1400	130	60.2	DDI, TAA, ECM, DOC, PTOX, EGR, SCR, AMOX, EPR
MPKXL07.0VL1	4906/2200	1206J- E70TA/C7.1	202@2200	105	76.4	641@1400	125.2	57.9	DDI, TAA, ECM, DOC, PTOX, EGR, SCR, AMOX, EPR
MPKXL07.0VL1	4908/2200	1206J- E70TA/C7.1	174@2200	87.8	63.9	621@1400	117.9	54.6	DDI, TAA, ECM, DOC, PTOX, EGR, SCR, AMOX, EPR
MPKXL07.0VL1	4930/1800	1206J- E70TA/C7.1	188@1800	111.7	66.5	664@1400	129.0	59.7	DDI, TAA, ECM, DOC, PTOX, EGR, SCR, AMOX, EPR
MPKXL07.0VL1	4932/1800	1206J- E70TA/C7.1	168@1800	99.3	59.1	601@1400	118.3	54.8	DDI, TAA, ECM, DOC, PTOX, EGR, SCR, AMOX, EPR
MPKXL07.0VL1	4934/2200	1206J- E70TA/C7.1	187@2200	97.7	71.1	667@1400	130	60.2	DDI, TAA, ECM, DOC, PTOX, EGR, SCR, AMOX, EPR
MPKXL07.0VL1	5098/2000	1206J- E70TA/C7.1	176@2000	99.4	65.7	637@1400	122.4	56.6	DDI, TAA, ECM, DOC, PTOX, EGR, SCR, AMOX, EPR
MPKXL07.0VL1	4904/2200	1206J- E70TA/C7.1	174@2200	91.8	66.8	621@1400	118.4	54.8	DDI, TAA, ECM, DOC, PTOX, EGR, SCR, AMOX, EPR
MPKXL07.0VL1	6270/2200	1206J- E70TA/C7.1	173@2200	89.0	64.7	642@1400	123.0	56.9	DDI, TAA, ECM, DOC, PTOX, EGR, SCR, AMOX, EPR

TAA = TC + CAC

SCR-U Apply to all ratings