

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)					
2021	MYDXL01.3NPA	1.267	Diesel	3,000					
SPECIAL	FEATURES & EMISSION C	ONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION						
	Indirect Diesel Inje	ction	Crane, Dozer, Loader, Tractor, Pump, Compressor, Excavator						

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION			l	EXHAUST (g/kw-ł		OPACITY (%)				
	STANDARD CATEGORY		NMHC	NOx	NMHC+NOx	со	РМ	ACCEL	LUG	PEAK	
8 ≤ kW < 19	Tier 4 Final	STD	N/A	N/A	7.5	6.6	0.40	20	15	50	
		CERT			5.6	1.5	0.13	1	1	1	

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this $\frac{29th}{2}$ day of December 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division

<u>Attachment</u>	t 1 of 1: E	ngine M	odels	EO i	#: U-R-028-0961	Famil	y: <u>MYDXL01.3NP</u>	Atta	achment Revise	d: 11/30/202	0								
					Displacement -		Peak Power -	Peak Power -	Peak Power -	Peak Power -		Peak Torque -	Peak Torque -	Peak Torque -	Peak Torque -				
Model	Code	Trim	Config	Displacement	Units	Peak Power	Units	Speed (rpm)	Fueling	Fuel Units	Peak Torque	Units	Speed (rpm)	Fuel	Fuel Units	OBD	GHG	Special	Notes
4WNNPM	N/A	N/A	13	1.267	Liters	21.2	horsepower	2500	23.3	mm3/stroke	51.5	lb-ft	1700	24.0	mm3/stroke	N/A	N/A	None	None
4WNCAM	N/A	N/A	13	1.267	Liters	23.9	horsepower	3200	20.9	mm3/stroke	45.7	lb-ft	2000	21.8	mm3/stroke	N/A	N/A	None	None
4WNDAM	N/A	N/A	13	1.267	Liters	23.9	horsepower	3000	21.9	mm3/stroke	45.7	lb-ft	1900	21.7	mm3/stroke	N/A	N/A	None	None
4WNKAM	N/A	N/A	13	1.267	Liters	22.8	horsepower	2800	21.5	mm3/stroke	48.1	lb-ft	1900	23.1	mm3/stroke	N/A	N/A	None	None
4WNMAM	N/A	N/A	13	1.267	Liters	21.2	horsepower	2600	22.2	mm3/stroke	48.1	lb-ft	1900	23.5	mm3/stroke	N/A	N/A	None	None
4WNNAM	N/A	N/A	13	1.267	Liters	20.4	horsepower	2500	22.4	mm3/stroke	48.1	lb-ft	1900	23.4	mm3/stroke	N/A	N/A	None	None
4WNPAM	N/A	N/A	13	1.267	Liters	19.6	horsepower	2400	21.6	mm3/stroke	48.1	lb-ft	1800	23.2	mm3/stroke	N/A	N/A	None	None
4WNSAM	N/A	N/A	13	1.267	Liters	18.0	horsepower	2200	21.0	mm3/stroke	48.1	lb-ft	1600	23.4	mm3/stroke	N/A	N/A	None	None
4WNNFM	N/A	N/A	13	1.267	Liters	20.4	horsepower	2500	22.4	mm3/stroke	48.1	lb-ft	1900	23.4	mm3/stroke	N/A	N/A	None	None
4WNDAP	N/A	N/A	13	1.267	Liters	23.9	horsepower	3000	21.9	mm3/stroke	45.7	lb-ft	1900	21.7	mm3/stroke	N/A	N/A	None	None
4WNDXM	N/A	N/A	13	1.267	Liters	24.7	horsepower	3000	22.2	mm3/stroke	48.7	lb-ft	2100	23.0	mm3/stroke	N/A	N/A	None	None