

CUMMINS INC.

EXECUTIVE ORDER U-R-002-0806

New Off-Road Compression-Ignition Engines Page 1 of 2

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)				
2022	NCEXL04.5AAK	4.5	Diesel	8000				
SPECIA	L FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION					
Diesel Ox Turboch	nic Control Module, Per xidation Catalyst, Electr arger, Selective Catalyt e Air Cooler, Ammonia	onic Direct Injection, ic Reduction - Urea,	Crane, Loader, Dozer, Pump, (Compressor				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION				EXHAUST (g/kw-l	OPACITY (%)				
POWER CLASS	STANDARD CATEGORY		NMHC NOx		NMHC+NOx	СО	PM	ACCEL	LUG	PEAK
75 ≤ kW <130	Tier 4 Final STD		0.19	0.40	N/A	5.0	0.02	N/A	N/A	N/A
		CERT	0.05	0.12		0.01	0.01	-		

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

BE IT FURTHER RESOLVED: That the listed engine family is conditionally certified pending submission of additional test data to verify compliance with useful-life emission standards. The manufacturer must submit the necessary data by February 28, 2022 to confirm or correct the certification emissions levels on this conditional certification. Failure to submit the necessary data or resolve concerns by the specified date, shall be cause for the Executive Officer to rescind this conditional certification, in which case all engines covered under this conditional certification and introduced into commerce in the State of California shall be deemed uncertified pursuant to Health and Safety Code Section 43153 and subject to civil penalties pursuant to Health and Safety Code Section 43154.



CUMMINS INC.

EXECUTIVE ORDER U-R-002-0806

New Off-Road Compression-Ignition Engines Page 2 of 2

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this /4th day of January 2022.

Allen Lyons, Chief

Emissions Certification and Compliance Division

Attachment: Engine Models EO #: U-R-002-0806 Family: NCEXLO4.5AAK Attachment Last Revised: 9/8/2021

					Displacement -		Peak Power -	Peak Power -	Peak Power -	Peak Power - Fuel Peak Torque			Peak Torque -	Peak Torque - Fuel					
Model	Code	Trim	Config	Displacement	Units	Peak Power	Units	Speed (rpm)	Fueling	Units Peak Torque		Units	Speed (rpm)	Peak Torque - Fuel Units		OBD	GHG	Special	Notes
QSB4.5	OB1		14	4.5	Liters	173	horsepower	2000	130	mm3/stroke	575	lb-ft	1500	53	lb/hr				
QSB4.5	OB2		14	4.5	Liters	173	horsepower	2500	138	mm3/stroke	575	lb-ft	1500	54	lb/hr				
QSB4.5	OB3		14	4.5	Liters	162	horsepower	2500	125	mm3/stroke	520	lb-ft	1500	50	lb/hr				
QSB4.5	OB4		14	4.5	Liters	130	horsepower	2500	115	mm3/stroke	480	lb-ft	1500	44	lb/hr				
QSB4.5	OB5		14	4.5	Liters	173	horsepower	2200	138	mm3/stroke	575	lb-ft	1500	54	lb/hr				
QSB4.5	OB6		14	4.5	Liters	165	horsepower	2200	125	mm3/stroke	563	lb-ft	1500	43	lb/hr				
QSB4.5	OB7		14	4.5	Liters	154	horsepower	2200	115	mm3/stroke	525	lb-ft	1500	40	lb/hr				
QSB4.5	OB8		14	4.5	Liters	133	horsepower	2200	94	mm3/stroke	467	lb-ft	1500	34	lb/hr				
QSB4.5	ОВ9		14	4.5	Liters	121	horsepower	2200	86	mm3/stroke	369	lb-ft	1500	34	lb/hr				
QSB4.5	OB10		14	4.5	Liters	173	horsepower	2000	138	mm3/stroke	575	lb-ft	1500	54	lb/hr				
QSB4.5	OB11		14	4.5	Liters	165	horsepower	2000	126	mm3/stroke	563	lb-ft	1500	43	lb/hr				
QSB4.5	OB12		14	4.5	Liters	154	horsepower	2000	115	mm3/stroke	525	lb-ft	1500	40	lb/hr				