

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2022	NJCBL04.4S09	4.399	Diesel	8,000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Electronic Direct Injection, Electronic Control Module, Exhaust Gas Recirculation, Turbocharger, Charge Air Cooler, Selective Catalytic Reduction-Urea, Ammonia Oxidation Catalyst			Crane, Loader, Tractor, Dozer, Pump, Compressor, Forklift, Generator Set	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NO<sub>x</sub>), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NO<sub>x</sub>), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			NMHC	NO <sub>x</sub>	NMHC+NO <sub>x</sub>	CO	PM	ACCEL	LUG	PEAK
56 ≤ kW < 130	Tier 4 Final	<b>STD</b>	0.19	0.40	N/A	5.0	0.02	N/A	N/A	N/A
		<b>CERT</b>	0.07	0.35	--	0.2	0.02	--	--	--

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

**BE IT FURTHER RESOLVED:** That for the listed engine models which include engines from different power categories in the same engine family, the manufacturer is complying with the more stringent set of standards from the 56 ≤ kW < 130 power categories in conformance with the incorporated Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for New 2011 and Later Tier 4 Off-Road Compression Ignition Engines, Part 1-D" adopted October 20, 2005 and last amended October 25, 2012.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

**This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.**

This Executive Order hereby supersedes Executive Order U-R-049-0066 dated January 21, 2022.

Executed on this 15<sup>th</sup> day of April 2022.



Allen Lyons, Chief  
Emissions Certification and Compliance Division

Model	Code	Trim	Config	Displacement	Displacement - Units	Peak Power	Peak Power - Units	Peak Power - Speed (rpm)	Peak Power - Fueling	Peak Power - Fuel Units	Peak Torque	Peak Torque - Units	Peak Torque - Speed (rpm)	Peak Torque - Fuel Units	OBD	GHG	Special	Notes	
D1A	444 TA4-68	N/A	I4	4.399	Liters	91.6	horsepower	2000	56	mm3/stroke	319	N-m	1450	78	mm3/stroke	N/A	N/A	N/A	N/A
D1A	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2000	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
D1A	444 TA4-93	N/A	I4	4.399	Liters	125.1	horsepower	2000	75	mm3/stroke	406	N-m	1500	98	mm3/stroke	N/A	N/A	N/A	N/A
B1A	444 TA4-68	N/A	I4	4.399	Liters	91.6	horsepower	2050	56	mm3/stroke	319	N-m	1450	78	mm3/stroke	N/A	N/A	N/A	N/A
B1C	444 TA4-68	N/A	I4	4.399	Liters	91.6	horsepower	2050	56	mm3/stroke	319	N-m	1450	78	mm3/stroke	N/A	N/A	N/A	N/A
B1A	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2050	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
B1C	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2000	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
B1A	444 TA4-93	N/A	I4	4.399	Liters	125.1	horsepower	2050	75	mm3/stroke	406	N-m	1500	98	mm3/stroke	N/A	N/A	N/A	N/A
B1C	444 TA4-93	N/A	I4	4.399	Liters	125.1	horsepower	2200	75	mm3/stroke	406	N-m	1500	98	mm3/stroke	N/A	N/A	N/A	N/A
B2A	444 TA4-68	N/A	I4	4.399	Liters	91.6	horsepower	2200	56	mm3/stroke	319	N-m	1450	78	mm3/stroke	N/A	N/A	N/A	N/A
B2A	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2200	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
B2A	444 TA4-93	N/A	I4	4.399	Liters	125.1	horsepower	2200	75	mm3/stroke	406	N-m	1500	98	mm3/stroke	N/A	N/A	N/A	N/A
E1A	444 TA4-68	N/A	I4	4.399	Liters	91.6	horsepower	2200	56	mm3/stroke	319	N-m	1450	78	mm3/stroke	N/A	N/A	N/A	N/A
E1C	444 TA4-68	N/A	I4	4.399	Liters	91.6	horsepower	2200	56	mm3/stroke	319	N-m	1450	78	mm3/stroke	N/A	N/A	N/A	N/A
E1A	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2200	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
E1C	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2200	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
E1A	444 TA4-93	N/A	I4	4.399	Liters	125.1	horsepower	2200	75	mm3/stroke	406	N-m	1500	98	mm3/stroke	N/A	N/A	N/A	N/A
E1C	444 TA4-93	N/A	I4	4.399	Liters	125.1	horsepower	2200	75	mm3/stroke	406	N-m	1500	98	mm3/stroke	N/A	N/A	N/A	N/A
L1A	444 TA4-68	N/A	I4	4.399	Liters	91.6	horsepower	2200	56	mm3/stroke	319	N-m	1450	78	mm3/stroke	N/A	N/A	N/A	N/A
L1C	444 TA4-68	N/A	I4	4.399	Liters	91.6	horsepower	2200	56	mm3/stroke	319	N-m	1450	78	mm3/stroke	N/A	N/A	N/A	N/A
L1A	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2200	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
L1C	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2200	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
L1A	444 TA4-93	N/A	I4	4.399	Liters	125.1	horsepower	2200	75	mm3/stroke	406	N-m	1500	98	mm3/stroke	N/A	N/A	N/A	N/A
L1C	444 TA4-93	N/A	I4	4.399	Liters	125.1	horsepower	2200	75	mm3/stroke	406	N-m	1500	98	mm3/stroke	N/A	N/A	N/A	N/A
C1A	444 TA4-68	N/A	I4	4.399	Liters	91.6	horsepower	2200	56	mm3/stroke	319	N-m	1450	78	mm3/stroke	N/A	N/A	N/A	N/A
C1C	444 TA4-68	N/A	I4	4.399	Liters	91.6	horsepower	2200	56	mm3/stroke	319	N-m	1450	78	mm3/stroke	N/A	N/A	N/A	N/A
C1A	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2200	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
C1C	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2200	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
C1A	444 TA4-93	N/A	I4	4.399	Liters	125.1	horsepower	2200	75	mm3/stroke	406	N-m	1500	98	mm3/stroke	N/A	N/A	N/A	N/A
C1C	444 TA4-93	N/A	I4	4.399	Liters	125.1	horsepower	2200	75	mm3/stroke	406	N-m	1500	98	mm3/stroke	N/A	N/A	N/A	N/A



E2A	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2200	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
E2C	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2200	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
E3A	444 TA4-93	N/A	I4	4.399	Liters	125.1	horsepower	2200	75	mm3/stroke	406	N-m	1500	98	mm3/stroke	N/A	N/A	N/A	N/A
E3C	444 TA4-93	N/A	I4	4.399	Liters	125.1	horsepower	2200	75	mm3/stroke	406	N-m	1500	98	mm3/stroke	N/A	N/A	N/A	N/A
I3A	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2200	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
I3C	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2200	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
C2A	444 TA4-68	N/A	I4	4.399	Liters	91.6	horsepower	2200	56	mm3/stroke	319	N-m	1450	78	mm3/stroke	N/A	N/A	N/A	N/A
C2A	444 TA4-81	N/A	I4	4.399	Liters	109	horsepower	2200	66	mm3/stroke	380	N-m	1450	93	mm3/stroke	N/A	N/A	N/A	N/A
C2A	444 TA4-93	N/A	I4	4.399	Liters	125.1	horsepower	2200	75	mm3/stroke	406	N-m	1500	98	mm3/stroke	N/A	N/A	N/A	N/A