

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2023	PDZXL02.2115	2.194	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Common Rail Direct Injection, Turbocharger, Electronic Control Module, Exhaust Gas Recirculation, Diesel Oxidation Catalyst, Continuous Trap Oxidizer			Loader, Tractor, Dozer, Pump, Compressor, Material Handler	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			NMHC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
19 ≤ kW ≤ 56	Tier 4 Final	STD	N/A	N/A	4.7	5.0	0.03	N/A	N/A	N/A
		CERT	--	--	4.3	0.4	0.01	--	--	--


BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

BE IT FURTHER RESOLVED: That for the listed engine models which include engines from different power categories in the same engine family, the manufacturer is complying with the more stringent set of standards from the 37 ≤ kW < 56 power category in conformance with the incorporated Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for New 2011 and Later Tier 4 Off-Road Compression Ignition Engines, Part 1-D" adopted October 20, 2005 and last amended October 25, 2012.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this 31st day of August 2022.



Robin U. Lang, Chief
 Emissions Certification and Compliance Division

Attachment: Engine Models

EO #: U-R-013-0687

Family: PDZXL02.2115

Attachment Last Revised: 1/27/2023

Model	Code	Trim	Config	Displacement	Displacement - Units	Peak Power	Peak Power - Units	Peak Power - Speed (rpm)	Peak Power - Fueling	Peak Power - Fuel Units	Peak Torque	Peak Torque - Units	Peak Torque - Speed (rpm)	Peak Torque - Fuel	Peak Torque - Fuel Units	OBD	GHG	Special	Notes
TD2.2L3	C5EI44E		L3	2.194	Liters	59.7	horsepower	2200	23.8	lb/hr	147.5	lb-ft	1600	17.3	lb/hr				
TD2.2L3	C5EI44A		L3	2.194	Liters	59.7	horsepower	2600	24.6	lb/hr	147.5	lb-ft	1600	17.3	lb/hr				
TD2.2L3	C5EI44D		L3	2.194	Liters	59.7	horsepower	2300	24.1	lb/hr	147.5	lb-ft	1600	17.3	lb/hr				
TD2.2L3	C5EI36A		L3	2.194	Liters	48.8	horsepower	2600	20.7	lb/hr	132.8	lb-ft	1600	15.4	lb/hr				
TD2.2L3	C5EI36D		L3	2.194	Liters	48.8	horsepower	2300	18.5	lb/hr	132.8	lb-ft	1600	15.4	lb/hr				
TD2.2L3	C5EI36E		L3	2.194	Liters	48.8	horsepower	2200	19.4	lb/hr	132.8	lb-ft	1600	15.4	lb/hr				
TD2.2L3	C5EI30A		L3	2.194	Liters	40.2	horsepower	2600	18.1	lb/hr	110.6	lb-ft	1600	12.5	lb/hr				
TD2.2L3	C5EI30D		L3	2.194	Liters	40.2	horsepower	2300	16.2	lb/hr	110.6	lb-ft	1600	12.5	lb/hr				
TD2.2L3	C5EI30E		L3	2.194	Liters	40.2	horsepower	2200	16.6	lb/hr	110.6	lb-ft	1600	12.5	lb/hr				
TD2.2L3	C5EI30EL		L3	2.194	Liters	40.2	horsepower	2200	16.6	lb/hr	96.6	lb-ft	1600	10.9	lb/hr				
TD2.2L3	C5EI26A		L3	2.194	Liters	59.7	horsepower	2600	16.4	lb/hr	95.9	lb-ft	1600	10.9	lb/hr				
TD2.2L3	C5EI26D		L3	2.194	Liters	59.7	horsepower	2300	14.3	lb/hr	95.9	lb-ft	1600	10.9	lb/hr				
TD2.2L3	C5EI26E		L3	2.194	Liters	59.7	horsepower	2200	14.6	lb/hr	95.9	lb-ft	1600	10.9	lb/hr				
TD2.2L3	C5EI44AG		L3	2.194	Liters	59.7	horsepower	2600	24.6	lb/hr	147.5	lb-ft	1600	17.3	lb/hr				New Rating