

## YANMAR POWER TECHNOLOGY CO., LTD

## **EXECUTIVE ORDER U-R-028-1079**

New Off-Road
Compression-Ignition Engines
Page 1 of 1

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)				
2023	PYDXL02.1TDA	2.091	Diesel	8000				
SPECIA	L FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION					
Exhaust G	ctronic Direct Injection, Gas Recirculation, Electiodic Trap Oxidizer, Ox	ronic Control Module,	Crane, Loader, Tractor, Dozer, Pump, Compressor, Excavator					

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION				EXHAUST (g/kw-ł	OPACITY (%)				
POWER CLASS	STANDARD CATEGORY		NMHC	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
19 ≤ kW < 56	Tier 4 Final	STD	N/A	N/A	4.7	5.0	0.03	N/A	N/A	N/A
		CERT			3.3	0.1	0.001	-		

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

**BE IT FURTHER RESOLVED:** That for the listed engine models which include engines from different power categories in the same engine family, the manufacturer is complying with the more stringent set of standards from the 37 ≤ kW < 56 power category in conformance with the incorporated Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for New 2011 and Later Tier 4 Off-Road Compression Ignition Engines, Part 1-D" adopted October 20, 2005 and last amended October 25, 2012.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this /2th day of January 2023.

Robin U. Lang, Chief

**Emissions Certification and Compliance Division** 

Attachment: Engine Models EO #: U-R-028-1079 Family: PYDXL02.1TDA Attachment Last Revised: 12/29/2022

					Displacement -		Peak Power -	Peak Power -	Peak Power -	Peak Power - Fuel Peak Torque - Peak Torq			Peak Torque -	e - Peak Torque - Fuel					
Model	Code	Trim	Config	Displacement	Units	Peak Power	Units	Speed (rpm)	Fueling	Units	Peak Torque	Units	Speed (rpm)	Peak Torque - Fuel Units		OBD	GHG	Special	Notes
4RTDPC			14	2.091	Liters	61.4	horsepower	3000	36.7	mm3/stroke	129.0	lb-ft	1950	40.8	mm3/stroke				
4RTDAC			14	2.091	Liters	59.0	horsepower	3000	35.3	mm3/stroke	124.0	lb-ft	1950	39.3	mm3/stroke				
4RTKAC			14	2.091	Liters	55.1	horsepower	2800	34.8	mm3/stroke	124	lb-ft	1820	39	mm3/stroke				
4RTLAC			14	2.091	Liters	53	horsepower	2700	34.4	mm3/stroke	124	lb-ft	1755	38.8	mm3/stroke				
4RTMAC			14	2.091	Liters	50.8	horsepower	2600	33.9	mm3/stroke	124	lb-ft	1690	38.7	mm3/stroke				
4RTNAC			14	2.091	Liters	49.1	horsepower	2500	33.6	mm3/stroke	124	lb-ft	1625	38.6	mm3/stroke				
4RTPAC			14	2.091	Liters	47.6	horsepower	2400	33.9	mm3/stroke	125	lb-ft	1560	39.1	mm3/stroke				