

LS MTRON CO., LTD.

EXECUTIVE ORDER U-R-059-0039

New Off-Road Compression-Ignition Engines Page 1 of 1

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)						
2023	PLGCL02.5L4T	1.9	Diesel 5,000							
SPECIAL	FEATURES & EMISSION C	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION							
Exhaust	ectronic Direct Injection, T Gas Recirculation, Electro Oxidation Catalyst, Perio	onic Control Module,	Excavator, Loader, Tractor, F	orklift						

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION			ı	EXHAUST (g/kw-l	OPACITY (%)				
POWER CLASS	STANDARD CATEGORY		NMHC NOx		NMHC+NOx	со	PM	ACCEL	LUG	PEAK
37 ≤ kW < 56	Tier 4 Final	STD	N/A	N/A	4.7	5.5	0.03	N/A	N/A	N/A
		CERT		1	3.9	0.1	0.004	-		

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this _/st_ day of November 2022.

Robin U. Lang, Chief

Johns Ehri for

Emissions Certification and Compliance Division

Attachment: Engine Models EO #: U-R-059-0039 Family: PLGCL02.5L4T Attachment Last Revised: 10/24/2022

				Displacement - Peak Power - Peak Power - Peak Power - Peak Power - Fuel Peak Torque - Peak Torque - Peak Torque					Peak Torque - Fue	el .									
Model	Code	Trim	Config	Displacement	Units	Peak Power	Units	Speed (rpm)	Fueling	Units	Peak Torque	Units	Speed (rpm)	Peak Torque - Fuel	Units	OBD	GHG	Special	Notes
L4C25-T1	L4C25-T1	N/A	1-4	2.506	L	54	kW	2500	52	mm3/stroke	249.5	Nm	1600	58.8	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX
L4C25-T2	L4C25-T2	N/A	1-4	2.506	L	51	kW	2500	48.6	mm3/stroke	235.9	Nm	1600	55.4	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX
L4C25-T3	L4C25-T3	N/A	1-4	2.506	L	47	kW	2500	45	mm3/stroke	221.0	Nm	1600	51.6	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX
L4C25-T4	L4C25-T4	N/A	1-4	2.506	L	43	kW	2500	41.5	mm3/stroke	206.1	Nm	1600	48.6	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX
L4C25- T2A	L4C25- T2A	N/A	1-4	2.506	L	51	kW	2500	48.6	mm3/stroke	249.5	Nm	1600	58.8	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX
L4C25- T3A	L4C25- T3A	N/A	1-4	2.506	L	47	kW	2500	45	mm3/stroke	249.5	Nm	1600	58.8	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX
L4CRV-T1	L4CRV- T1	N/A	1-4	2.506	L	54.4	kW	2500	52	mm3/stroke	249.5	Nm	1600	58.8	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX
L4CRV- T2A	L4CRV- T2A	N/A	1-4	2.506	L	50.7	kW	2500	48.6	mm3/stroke	249.5	Nm	1600	58.8	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX
L4CRV-T2	L4CRV- T2	N/A	1-4	2.506	L	50.7	kW	2500	48.6	mm3/stroke	235.9	Nm	1600	55.4	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX
L4CRV- T3A	L4CRV- T3A	N/A	1-4	2.506	L	47.0	kW	2500	45	mm3/stroke	249.5	Nm	1600	58.8	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX
L4CRV-T3	L4CRV- T3	N/A	1-4	2.506	L	47.0	kW	2500	45	mm3/stroke	221.0	Nm	1600	51.6	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX
L4CRV-T4	L4CRV- T4	N/A	1-4	2.506	L	43.3	kW	2500	41.5	mm3/stroke	206.1	Nm	1600	48.6	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX
L4CRV-T5	L4CRV- T5	N/A	1-4	2.506	L	47	kW	2300	49.8	mm3/stroke	234.6	Nm	1600	58.2	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX
L4CRV-T6	L4CRV- T6	N/A	1-4	2.506	L	42	kW	2300	44.4	mm3/stroke	207.4	Nm	1600	50.4	mm3/stroke	N/A	N/A	N/A	DFI-TC-EGR-ECU-DOC-PTOX