

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

CUMMINS INC.

IT IS ORDERED AND RESOLVED: The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2024	RCEXL04.5AAL	Diesel	Dedicated	Diesel	Variable Speed

Emission Control Systems	Special Features
[1]: Electronic Direct Injection (EDI), Electronic Control Module (ECM), Turbocharger (TC), Charged Air Cooler (CAC), Selective Catalytic Reduction – Urea (SCR-U), Ammonia Oxidation Catalyst (AMOX), Diesel Oxidation Catalyst (DOC), Periodic Trap Oxidizer (PTOX)	None

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbons (NMHC), nitrogen oxides (NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kWh-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (*).

			Crit	eria	Smoke Opacity			
Applicable Standard	NMHC	NOx	СО	PM	ACL	LUG	PEAK	
	STD	0.19	0.40	3.5	0.02	*	*	*
Tier 4 Final 130 ≤ kW ≤ 560	FEL	*	*	*	*	*	*	*
100 = KVV = 000	NTE	0.28	0.60	4.4	0.03	*	*	*

BE IT FURTHER RESOLVED: Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

BE IT FURTHER RESOLVED: That the manufacturer has elected to combine engines from the $75 \le kW \le 560$ power categories into a single engine family. The listed engine models comply with the more stringent set of standards of the $130 \le kW \le 560$ power category in accordance with Section 1039.230(e) of the applicable California test procedures.

BE IT FURTHER RESOLVED: For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this _____ day of June 2023.

Robin U. Lang, Chief

Emissions Certification and Compliance Division

Attachment: Engine Models EO #: U-R-002-0848 Family: RCEXLO4.5AAL Date Applicable: 5/19/2023

					Displacement -		Peak Power -	Peak Power -	Peak Power -	Peak Power - Fuel		Peak Torque -	Peak Torque -	Peak Torque -	Peak Torque -					
Model	Code	Trim	Config	Displacement	Units	Peak Power	Units	Speed (rpm)	Fueling	Units	Peak Torque	Units	Speed (rpm)	Fuel	Fuel Units	OBD Status	OBD Fines (\$)	GHG	ECS #	Notes
34.5	OB1		14	4.5	Liters	200	horsepower	2500	140	mm3/stroke	575	lb-ft	1500	53	lb/hr	N/A	N/A	N/A	1	
34.5	OB2		14	4.5	Liters	188	horsepower	2500	143	mm3/stroke	575	lb-ft	1500	53	lb/hr	N/A	N/A	N/A	1	
84.5	OB3		14	4.5	Liters	173	horsepower	2500	143	mm3/stroke	575	lb-ft	1500	53	lb/hr	N/A	N/A	N/A	1	
84.5	OB4		14	4.5	Liters	200	horsepower	2200	138	mm3/stroke	575	lb-ft	1500	53	lb/hr	N/A	N/A	N/A	1	
84.5	OB5		14	4.5	Liters	188	horsepower	2200	143	mm3/stroke	575	lb-ft	1500	53	lb/hr	N/A	N/A	N/A	1	
34.5	OB6		14	4.5	Liters	173	horsepower	2200	144	mm3/stroke	575	lb-ft	1500	53	lb/hr	N/A	N/A	N/A	1	
34.5	OB7		14	4.5	Liters	188	horsepower	2000	144	mm3/stroke	575	lb-ft	1500	53	lb/hr	N/A	N/A	N/A	1	