\sim	~			-		
A	CI	ALI	FO	R	N	IA
WC 117	AIR	RESO	URCI	ES	BO	ARC

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2024	RLGCL02.5L4T	Diesel	Dedicated	Diesel	Variable and Constant Speed

Emission Control Systems					
[1]: Electronic Direct Injection (DFI), Turbocharger (TC), Exhaust Gas Recirculation (EGR), Electronic Control Module (ECM), Diesel Oxidation Catalyst (DOC), Periodic Trap Oxidizer (PTOX)	None				

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatthour (g/kWh-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (*).

	Criteria			Smoke Opacity			
Applicable Standard	NMHC+NOx	СО	PM	ACL	LUG	PEAK	
	STD	4.7	5.0	0.03	*	*	*
Tier 4 Final 37 ≤ kW < 56	FEL	*	*	*	*	*	*
07 2 800 4 00	NTE	5.9	6.2	0.04	*	*	*

BE IT FURTHER RESOLVED: Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

BE IT FURTHER RESOLVED: For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this <u>23rd</u> day of August 2023.

Polin U. Lang

Robin U. Lang, Chief *O* Emissions Certification and Compliance Division

ATTACHMENT: ENGINE MODELS

Family: RLGCL02.5L4T EO Number: U-R-059-0042 Date Applicable: 08/03/2023

					Peak Power F			Peak Torque					
lodel	Code	Trim	Config	Displacement	Power	Speed	Fueling	Torque	Speed	Fueling	ECS Num	GHG	Notes
-	-	-	-	L	kW	rpm	mm3/stroke	N-m	rpm	mm3/stroke	-	-	-
C25-T1	L4C25-T1		14	2.506	54	2500	52	249	1600	58.8	1	N/A	
C25-T2	L4C25-T2		14	2.506	51	2500	48.6	236	1600	55.4	1	N/A	
IC25-T3	L4C25-T3		14	2.506	47	2500	45	221	1600	51.6	1	N/A	
IC25-T4	L4C25-T4		14	2.506	43	2500	41.5	206	1600	48.6	1	N/A	
IC25-T2A	L4C25-T2A		14	2.506	51	2500	48.6	249	1600	58.8	1	N/A	
IC25-T3A	L4C25-T3A		14	2.506	47	2500	45	249	1600	58.8	1	N/A	
ICRV-T1	L4CRV-T1		14	2.506	54	2500	52	249	1600	58.8	1	N/A	
ICRV-T2A	L4CRV-T2A		14	2.506	51	2500	48.6	249	1600	58.8	1	N/A	
CRV-T2	L4CRV-T2		14	2.506	51	2500	48.6	236	1600	55.4	1	N/A	
ICRV-T3A	L4CRV-T3A		14	2.506	47	2500	45	249	1600	58.8	1	N/A	
CRV-T3	L4CRV-T3		14	2.506	47	2500	45	221	1600	51.6	1	N/A	
ICRV-T4	L4CRV-T4		14	2.506	43	2500	41.5	206	1600	48.6	1	N/A	
CRV-T5	L4CRV-T5		14	2.506	47	2300	49.8	234	1600	58.2	1	N/A	
ICRV-T6	L4CRV-T6		14	2.506	42	2300	44.4	208	1600	50.4	1	N/A	