

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2024	RPKXL07.0VL1	Diesel	Dedicated	Diesel	Variable and Constant Speed

Emission Control Systems	Special Features
[1]: Electronic Direct Injection (DDI), Charged Air Cooler (CAC), Exhaust Gas Recirculation (EGR), Electronic Control Module (ECM), Turbocharger (TC), Diesel Oxidation Catalyst (DOC), Periodic Trap Oxidizer (PTOX), Selective Catalytic Reduction – Urea (SCR-U), Ammonia Oxidation Catalyst (AMOX)	None

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbons (NMHC), nitrogen oxides (NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kWh-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (*).

Applicable Standard		Criteria				Smoke Opacity		
		NMHC	NOx	CO	PM	ACL	LUG	PEAK
Tier 4 Final 130 ≤ kW ≤ 560	STD	0.19	0.40	3.5	0.02	*	*	*
	FEL	*	*	*	0.01	*	*	*
	NTE	0.28	0.60	4.4	0.02	*	*	*

BE IT FURTHER RESOLVED: Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

BE IT FURTHER RESOLVED: That the manufacturer has elected to combine engines from the 75 ≤ kW ≤ 560 power categories into a single engine family. The listed engine models comply with the more stringent set of standards of the 130 ≤ kW ≤ 560 power category in accordance with Section 1039.230(e) of the applicable California test procedures.

BE IT FURTHER RESOLVED: For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this 12th day of October 2023.



Robin U. Lang, Chief
 Emissions Certification and Compliance Division

ATTACHMENT: ENGINE MODELS

Family: RPKXL07.0VL1 EO Number: U-R-022-0380 Date Applicable: 09/08/2023

Model	Code	Trim	Config	Displacement	Peak Power			Peak Torque			ECS Num	GHG	Notes
					Power	Speed	Fueling	Torque	Speed	Fueling			
-	-	-	-	L	hp	rpm	lb/hr	lb-ft	rpm	lb/hr	-	-	-
1206J-E70TA/C7.1	6186/2200	N/A	I6	7.01	202	2200	76.8	669	1400	60.2	1	N/A	N/A
1206J-E70TA/C7.1	4906/2200	N/A	I6	7.01	202	2200	76.4	641	1400	57.9	1	N/A	N/A
1206J-E70TA/C7.1	4908/2200	N/A	I6	7.01	174	2200	63.9	621	1400	54.6	1	N/A	N/A
1206J-E70TA/C7.1	4930/1800	N/A	I6	7.01	188	1800	66.5	664	1400	59.7	1	N/A	N/A
1206J-E70TA/C7.1	4932/1800	N/A	I6	7.01	168	1800	59.1	601	1400	54.8	1	N/A	N/A
1206J-E70TA/C7.1	4934/2200	N/A	I6	7.01	187	2200	71.1	667	1400	60.2	1	N/A	N/A
1206J-E70TA/C7.1	5098/2000	N/A	I6	7.01	176	2000	65.7	637	1400	56.6	1	N/A	N/A
1206J-E70TA/C7.1	4904/2200	N/A	I6	7.01	174	2200	66.8	621	1400	54.8	1	N/A	N/A
1206J-E70TA/C7.1	6270/2200	N/A	I6	7.01	173	2200	64.7	642	1400	56.9	1	N/A	N/A